



	Test Report issued under the responsibility of: NCB TÜV SÜD PSB Pte. Ltd. 15 International Business Park TÜV SÜD @ IBP Singapore 609937	
TEST REPORT IEC 62368-1 Audio/video, information and communication technology equipment Part 1: Safety requirements		
Report Number.....: 211-21251930-000 Date of issue.....: 2025-12-05 Total number of pages.....: 73		
Name of Testing Laboratory preparing the Report.....: TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch		
Applicant's name.....: XGIMI Technology CO., LTD. Address.....: Building No.4, Zone A, No.1129, Shijicheng Road, Chengdu High-tech Zone, Sichuan Pilot Free Trade Zone, 610041 Chengdu City, PEOPLE'S REPUBLIC OF CHINA		
Test specification: Standard.....: IEC 62368-1:2018 Test procedure.....: CB Scheme Non-standard test method.....: N/A		
TRF template used.....: IECEE OD-2020-F1:2021, Ed.1.4 Test Report Form No.: IEC62368_1E Test Report Form(s) Originator: UL(US) Master TRF.....: Dated 2022-04-14		
Copyright © 2022 IEC System of Conformity Assessment Schemes for Electrotechnical Equipment and Components (IECEE System). All rights reserved. This publication may be reproduced in whole or in part for non-commercial purposes as long as the IECEE is acknowledged as copyright owner and source of the material. IECEE takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context. If this Test Report Form is used by non-IECEE members, the IECEE/IEC logo and the reference to the CB Scheme procedure shall be removed. This report is not valid as a CB Test Report unless signed by an approved CB Testing Laboratory and appended to a CB Test Certificate issued by an NCB in accordance with IECEE 02.		
General disclaimer: The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Issuing CB Testing Laboratory. The authenticity of this Test Report and its contents can be verified by contacting the NCB, responsible for this Test Report.		

Test item description	Projector	
Trade Mark	 XGIMI	
Manufacturer	Same as applicant	
Model/Type reference	XR03B, XR06B	
Ratings	100V-240VAC, 7A MAX, 50Hz/60Hz	
Responsible Testing Laboratory (as applicable), testing procedure and testing location(s):		
☒	CB Testing Laboratory:	TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch
Testing location/ address		Building 12 & 13, Zhiheng Wisdomland Business Park, Guankou Erlu, Nantou, Nanshan District, Shenzhen, Guangdong 518052, China
Tested by (name, function, signature)		Cloris Zou Project Handler
Approved by (name, function, signature) ..		Eason Wan Designated Reviewer
		
☐	Testing procedure: CTF Stage 1:	
Testing location/ address		
Tested by (name, function, signature)		
Approved by (name, function, signature) ..		
☐	Testing procedure: CTF Stage 2:	
Testing location/ address		
Tested by (name, function, signature)		
Witnessed by (name, function, signature) .		
Approved by (name, function, signature) ..		
☐	Testing procedure: CTF Stage 3:	
☐	Testing procedure: CTF Stage 4:	
Testing location/ address		
Tested by (name, function, signature)		
Witnessed by (name, function, signature) .		
Approved by (name, function, signature) ..		
Supervised by (name, function, signature) :		

List of Attachments (including a total number of pages in each attachment): Attachment No. 1: 22 pages of EUROPEAN GROUP DIFFERENCES AND NATIONAL DIFFERENCES for EN IEC 62368-1:2020+A11:2020. Attachment No. 2: 57 pages of National and Group Differences for IEC 62368-1:2018 (Third Edition) as per CB Bulletin. Attachment No. 3: 17 pages of photograph.	
Summary of testing:	
Tests performed (name of test and test clause): The submitted samples were found to comply with the requirements of: - IEC 62368-1:2018 - UL 62368-1:2019/R:2021-10 - CSA C22.2 No. 62368-1:2019/U1:2021-10 All applicable tests as described in the compliance checklist were performed at model XR06B, and partial tests at model XR03B.	Testing location: TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch Building 12 & 13, Zhiheng Wisdomland Business Park, Guankou Erlu, Nantou, Nanshan District, Shenzhen, Guangdong 518052, China
Summary of compliance with National Differences (List of countries addressed): See the attachment No. 1 and No. 2 of National and Group Differences for details. ☒ The product fulfils the requirements of <u>EN IEC 62368-1:2020+A11:2020 and BS EN IEC 62368-1:2020+A11:2020.</u> This CB report also covers UL 62368-1:2019/R2021-10 and CSA C22.2 No.62368-1:2019/U1:2021-10 for project 6821025193001.	
Use of uncertainty of measurement for decisions on conformity (decision rule) : ☒ No decision rule is specified by the IEC standard, when comparing the measurement result with the applicable limit according to the specification in that standard. The decisions on conformity are made without applying the measurement uncertainty ("simple acceptance" decision rule, previously known as "accuracy method"). ☐ Other:... (to be specified, for example when required by the standard or client, or if national accreditation requirements apply) Information on uncertainty of measurement: The uncertainties of measurement are calculated by the laboratory based on application of criteria given by OD-5014 for test equipment and application of test methods, decision sheets and operational procedures of IECEE. IEC Guide 115 provides guidance on the application of measurement uncertainty principles and applying the decision rule when reporting test results within IECEE scheme, noting that the reporting of the measurement uncertainty for measurements is not necessary unless required by the test standard or customer. Calculations leading to the reported values are on file with the NCB and testing laboratory that conducted the testing.	

Copy of marking plate:

The artwork below may be only a draft. The use of certification marks on a product must be authorized by the respective NCBs that own these marks.



Marking plate



USB ports

Remarks:

1. The height dimension of CE symbol should not less than 5mm, and the height dimension of WEEE symbol should not less than 7mm.
2. The model "XR03B" on the marking plate can be replaced by others listed in the test report.
3. Above information was located on bottom enclosure of the apparatus.
4. For EU directives and regulations which have been harmonized with (EU) 2019/1020 in its Annex I, the name, registered trade name or registered trade mark, and contact details, including the postal address of the economic operator (EU manufacturer, EU importer, EU authorised representative, or EU fulfilment service provider where no other economic operator as mentioned in the first 3 options) shall be indicated on the product or on its packing, the parcel or an accompanying document.
5. The above markings are the minimum requirements required by the safety standard. For the final production samples, the additional markings which do not give rise to misunderstanding may be added.
6. The "TITAN" close to the trademark "XGIMI" is a part of product description.

Possible test case verdicts: - test case does not apply to the test object.....: N/A - test object does meet the requirement.....: P (Pass) - test object does not meet the requirement.....: F (Fail)	
Testing: Date of receipt of test item : 2025-10-14 Date (s) of performance of tests : 2025-10-14 to 2025-12-05	
General remarks: "(See Enclosure #)" refers to additional information appended to the report. "(See appended table)" refers to a table appended to the report. Throughout this report a ☐ comma / ☒ point is used as the decimal separator.	
Manufacturer's Declaration per sub-clause 4.2.5 of IEC62 02:	
The application for obtaining a CB Test Certificate includes more than one factory location and a declaration from the Manufacturer stating that the sample(s) submitted for evaluation is (are) representative of the products from each factory has been provided	☐ Yes ☒ Not applicable
When differences exist; they shall be identified in the General product information section.	
Name and address of factory (ies) : Yibin XGIMI Optoelectronic Co., Ltd. No.2, West Section 4, Changjiang North Road, Lingang Economic Development Zone, 644000 YiBin, Sichuan Province, PEOPLE'S REPUBLIC OF CHINA	
General product information and other remarks: 1. The product is intended to use with other information technology equipment or audio and Video equipment, and for indoor use only. 2. The product shall only be connected to a USB interface of version USB2.0(5VDC, 0.5A) and USB3.0(5VDC, 1.0A), which specified in user manual, and the maximum attainable current is USB2.0(5VDC, 2.0A) and USB3.0(5VDC, 2.2A). 3. The maximum operating temperature is 40°C. 4. Clearances were evaluated for operating altitude up to 5000m above sea level. 5. The power supply cordset of equipment must be evaluated when submitted to national approval. 6. The product was classified as RG2 projector according to IEC/EN 62471-5, refer to test report 68.140.25.0653.01 for details. 7. The product was classified as Class 1 Laser product according to IEC/EN 60825-1, refer to test report 68.184.25.0880.01 for details. 8. The remote control is powered by two "AAA" batteries. 9. Both models listed in the test report are identical except for different model No., internal DC fans, laser module and main board with a few differences. Unless otherwise specified, XR06B served as the representative model for all tests, and XR03B underwent only partial testing.	

OVERVIEW OF ENERGY SOURCES AND SAFEGUARDS				
Clause	Possible Hazard			
5	Electrically-caused injury			
Class and Energy Source (e.g. ES3: Primary circuit)	Body Part (e.g. Ordinary)	Safeguards		
		B	S	R
ES3: All primary circuits (to secondary circuits and accessible parts)	Ordinary person, Instructed person	N/A	N/A	Enclosure, Isolated transformer, Optocoupler, Y1-cap.
ES3: All primary circuits (to earthing part)	Ordinary person, Instructed person	Basic insulation	Protective bonding and protective earthing	N/A
ES3: Transformer (TH1) secondary pins of power supply board	Ordinary person, Instructed person	Separated from ES3 mains by a double safeguard or a reinforced safeguard	Touch voltage/ current on accessible parts didn't exceed ES1 under single fault condition	N/A
ES3: Appliance inlet (Primary Filter circuit)	Ordinary person, Instructed person	Approved ICX and bleeder resistors provided	Accessible voltage didn't exceed ES2 limits of Table 5 under fault condition (after 2s disconnection)	N/A
ES3: All primary circuits; ES3: Transformer (TH1) secondary pins of power supply board; ES3: Appliance inlet (Primary Filter circuit)	Skilled person	N/A (unintentional contact with parts during service condition is unlikely)	N/A	N/A (Skill safeguard)
ES1: Secondary circuits after DH1/DH2 of power supply board; ES1: Other secondary circuits /terminals; ES1: Batteries output (used in remote controller); ES1: Accessible enclosure	Ordinary person, Instructed person, Skilled person	N/A	N/A	N/A
6	Electrically-caused fire			
Class and Energy Source (e.g. PS2: 100 Watt circuit)	Material part (e.g. Printed board)	Safeguards		
		B	1 st S	2 nd S

PS3: All internal circuits/ components except for DC Fans, USB2.0/USB3.0 ports output, speaker; PS2: DC fans	Internal combustible material/ plastic enclosure	For “N” & “A” condition: 1, No ignition occurred. 2, No parts exceeding 90% of its spontaneous ignition temperature.	For control fire spread under single fault condition: 1, PCB is complied with min. V-1 material. 2, Internal wire insulation and tubing complied with Clause 6.5.1; 3, Motors complied with G.5.4; 4, Transformer complied with G.5.3; 5, All other components: at least V-2 except for mounted on min. V-1 material or small parts of combustible material.	For control fire spread under single fault condition: V-0 plastic enclosure provided.
PS1: USB2.0/USB3.0 ports output; PS1: Supply of speaker; PS1: Batteries output (used in remote controller)	Internal combustible material/ plastic enclosure	For “N” & “A” condition: 1, No ignition occurred. 2, No parts exceeding 90% of its spontaneous ignition temperature.	N/A	N/A
7	Injury caused by hazardous substances			
Class and Energy Source (e.g. Ozone)	Body Part (e.g., Skilled)	Safeguards		
		B	S	R
Batteries used in remote controller (Complied with Annex M)	Ordinary person, Instructed person, Skilled person	N/A	N/A	N/A
8	Mechanically-caused injury			
Class and Energy Source (e.g. MS3: Plastic fan blades)	Body Part (e.g. Ordinary)	Safeguards		
		B	S	R
MS2: Equipment mass	Ordinary person, Instructed person, Skilled person	Means of stabilize the equipment used (complied with clause 8.6)	N/A	N/A

MS1: Plastic fan blades MS1: Sharp edges and corners of accessible parts	Ordinary person, Instructed person, Skilled person	N/A	N/A	N/A
9	Thermal burn			
Class and Energy Source (e.g. TS1: Keyboard caps)	Body Part (e.g., Ordinary)	Safeguards		
		B	S	R
TS1: Accessible parts	Ordinary person, Instructed person, Skilled person	N/A	N/A	N/A
10	Radiation			
Class and Energy Source (e.g. RS1: PMP sound output)	Body Part (e.g., Ordinary)	Safeguards		
		B	S	R
Image projectors with lasers (according to IEC/EN 62471-5)	Ordinary person, Instructed person, Skilled person	N/A (Instructional safeguard also be provided)	N/A	N/A
Image projectors with lasers (according to IEC/EN 60825-1)	Ordinary person, Instructed person, Skilled person	N/A	N/A	N/A
LEDs for indicating lights (according to IEC/EN 62471)	Ordinary person, Instructed person, Skilled person	N/A	N/A	N/A
Supplementary Information: “B” – Basic Safeguard; “S” – Supplementary Safeguard; “R” – Reinforced Safeguard.				

ENERGY SOURCE DIAGRAM
Optional. Manufacturers are to provide the energy sources diagram identify declared energy sources and identifying the demarcations are between power sources. Recommend diagram be provided included in power supply and multipart systems. Insert diagram below. Example diagram designs are; Block diagrams; image(s) with layered data; mechanical drawings
☐ ES ☐ PS ☐ MS ☐ TS ☐ RS Remark: see above table “OVERVIEW OF ENERGY SOURCES AND SAFEGUARDS” for details.

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
4	GENERAL REQUIREMENTS		P
4.1.1	Acceptance of materials, components and subassemblies		P
4.1.2	Use of components	(See appended table 4.1.2)	P
4.1.3	Equipment design and construction		P
4.1.4	Specified ambient temperature for outdoor use (°C) :		N/A
4.1.5	Constructions and components not specifically covered		N/A
4.1.8	Liquids and liquid filled components (LFC)		N/A
4.1.15	Markings and instructions	(See Annex F)	P
4.4.3	Safeguard robustness		P
4.4.3.1	General		P
4.4.3.2	Steady force tests	(See Annex T.5)	P
4.4.3.3	Drop tests		N/A
4.4.3.4	Impact tests	(See Annex T.6)	P
4.4.3.5	Internal accessible safeguard tests		N/A
4.4.3.6	Glass impact tests		N/A
4.4.3.7	Glass fixation tests		N/A
	Glass impact test (1J)		N/A
	Push/pull test (10 N)		N/A
4.4.3.8	Thermoplastic material tests	(See Annex T.8)	P
4.4.3.9	Air comprising a safeguard	(See Annex T)	P
4.4.3.10	Accessibility, glass, safeguard effectiveness	All safeguards remain effective	P
4.4.4	Displacement of a safeguard by an insulating liquid		N/A
4.4.5	Safety interlocks		N/A
4.5	Explosion		P
4.5.1	General		P
4.5.2	No explosion during normal/abnormal operating condition	(See Annex B.2, B.3)	P
	No harm by explosion during single fault conditions	(See Annex B.4)	P
4.6	Fixing of conductors		P
	Fix conductors not to defeat a safeguard		P
	Compliance is checked by test..... :	(See Annex T.2)	P
4.7	Equipment for direct insertion into mains socket-outlets		N/A
4.7.2	Mains plug part complies with relevant standard .. :		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
4.7.3	Torque (Nm)		N/A
4.8	Equipment containing coin/button cell batteries		N/A
4.8.1	General	No coin/ button cell batteries	N/A
4.8.2	Instructional safeguard		N/A
4.8.3	Battery compartment door/cover construction		N/A
	Open torque test		N/A
4.8.4.2	Stress relief test		N/A
4.8.4.3	Battery replacement test		N/A
4.8.4.4	Drop test		N/A
4.8.4.5	Impact test		N/A
4.8.4.6	Crush test		N/A
4.8.5	Compliance		N/A
	30N force test with test probe		N/A
	20N force test with test hook		N/A
4.9	Likelihood of fire or shock due to entry of conductive object		P
4.10	Component requirements		P
4.10.1	Disconnect Device	(See Annex L)	P
4.10.2	Switches and relays		N/A

5	ELECTRICALLY-CAUSED INJURY		P
5.2	Classification and limits of electrical energy sources		P
5.2.2	ES1, ES2 and ES3 limits		P
5.2.2.2	Steady-state voltage and current limits	(See appended table 5.2)	P
5.2.2.3	Capacitance limits	(See appended table 5.2)	P
5.2.2.4	Single pulse limits	No single pulse introduced	N/A
5.2.2.5	Limits for repetitive pulses	No repetitive pulses introduced	N/A
5.2.2.6	Ringling signals	No means for connection to telephone network and no ringing signal generated	N/A
5.2.2.7	Audio signals	(See Annex E)	P
5.3	Protection against electrical energy sources		P
5.3.1	General Requirements for accessible parts to ordinary, instructed and skilled persons		P
5.3.1 a)	Accessible ES1/ES2 derived from ES2/ES3 circuits		P
5.3.1 b)	Skilled persons not unintentional contact ES3 bare conductors		P

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
5.3.2.1	Accessibility to electrical energy sources and safeguards		P
	Accessibility to outdoor equipment bare parts		N/A
5.3.2.2	Contact requirements		P
	Test with test probe from Annex V	The test probe cannot contact with the bare internal conductive part.	-
5.3.2.2 a)	Air gap – electric strength test potential (V)		N/A
5.3.2.2 b)	Air gap – distance (mm)	Air gap >0.26mm	P
5.3.2.3	Compliance		P
5.3.2.4	Terminals for connecting stripped wire		N/A
5.4	Insulation materials and requirements		P
5.4.1.2	Properties of insulating material		P
5.4.1.3	Material is non-hygroscopic	No hygroscopic insulating material used	N/A
5.4.1.4	Maximum operating temperature for insulating materials	(See appended table 5.4.1.4)	P
5.4.1.5	Pollution degrees	Pollution degree 2	P
5.4.1.5.2	Test for pollution degree 1 environment and for an insulating compound		N/A
5.4.1.5.3	Thermal cycling test		N/A
5.4.1.6	Insulation in transformers with varying dimensions		N/A
5.4.1.7	Insulation in circuits generating starting pulses		N/A
5.4.1.8	Determination of working voltage	(See appended table 5.4.1.8)	P
5.4.1.9	Insulating surfaces		P
5.4.1.10	Thermoplastic parts on which conductive metallic parts are directly mounted		P
5.4.1.10.2	Vicat test.....		N/A
5.4.1.10.3	Ball pressure test	(See appended table 5.4.1.10.3)	P
5.4.2	Clearances		P
5.4.2.1	General requirements		P
	Clearances in circuits connected to AC Mains, Alternative method		N/A
5.4.2.2	Procedure 1 for determining clearance	(See appended table 5.4.2)	P
	Temporary overvoltage	2000V _{peak}	—
5.4.2.3	Procedure 2 for determining clearance	(See appended table 5.4.2)	P
5.4.2.3.2.2	a.c. mains transient voltage	2500V _{peak}	—
5.4.2.3.2.3	d.c. mains transient voltage		—

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
5.4.2.3.2.4	External circuit transient voltage.....:		—
5.4.2.3.2.5	Transient voltage determined by measurement		—
5.4.2.4	Determining the adequacy of a clearance using an electric strength test	(See appended table 5.4.2)	N/A
5.4.2.5	Multiplication factors for clearances and test voltages	Clearance was evaluated for altitude up to 5000m above sea level, correction factor for clearance is 1.48	P
5.4.2.6	Clearance measurement	(See appended table 5.4.2)	P
5.4.3	Creepage distances		P
5.4.3.1	General		P
5.4.3.3	Material group	Material group IIIb is assumed to be used	—
5.4.3.4	Creepage distances measurement	(See appended table 5.4.3)	P
5.4.4	Solid insulation		P
5.4.4.1	General requirements		P
5.4.4.2	Minimum distance through insulation	(See appended table 5.4.4.2)	P
5.4.4.3	Insulating compound forming solid insulation		N/A
5.4.4.4	Solid insulation in semiconductor devices	Approved optocouplers used (See appended table 4.1.2)	P
5.4.4.5	Insulating compound forming cemented joints		N/A
5.4.4.6	Thin sheet material		P
5.4.4.6.1	General requirements		P
5.4.4.6.2	Separable thin sheet material		P
	Number of layers (pcs)	-TH1: 2 layers of insulation tape wrapped on core (min. thickness 0.05mm for each layer insulation tape	P
5.4.4.6.3	Non-separable thin sheet material		N/A
	Number of layers (pcs)		N/A
5.4.4.6.4	Standard test procedure for non-separable thin sheet material	(See appended table 5.4.9)	N/A
5.4.4.6.5	Mandrel test		N/A
5.4.4.7	Solid insulation in wound components		P
5.4.4.9	Solid insulation at frequencies >30 kHz, E_P , K_R , d , V_{PW} (V)	(See appended Table 5.4.4.9)	P
	Alternative by electric strength test, tested voltage (V), K_R	(See appended Table 5.4.4.9)	P
5.4.5	Antenna terminal insulation		P
5.4.5.1	General		P

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
5.4.5.2	Voltage surge test	10kV, 50 times	P
5.4.5.3	Insulation resistance (MΩ)..... :	>100	P
	Electric strength test		N/A
5.4.6	Insulation of internal wire as part of supplementary safeguard	No such wires	N/A
5.4.7	Tests for semiconductor components and for cemented joints		N/A
5.4.8	Humidity conditioning		P
	Relative humidity (%), temperature (°C), duration (h)	95% RH, 40°C, 120h	—
5.4.9	Electric strength test		P
5.4.9.1	Test procedure for type test of solid insulation..... :	(See appended table 5.4.9)	P
5.4.9.2	Test procedure for routine test		N/A
5.4.10	Safeguards against transient voltages from external circuits	No external circuits	N/A
5.4.10.1	Parts and circuits separated from external circuits	(See appended table 5.4.9)	N/A
5.4.10.2	Test methods		N/A
5.4.10.2.1	General		N/A
5.4.10.2.2	Impulse test	(See appended table 5.4.9)	N/A
5.4.10.2.3	Steady-state test..... :	(See appended table 5.4.9)	N/A
5.4.10.3	Verification for insulation breakdown for impulse test		N/A
5.4.11	Separation between external circuits and earth		N/A
5.4.11.1	Exceptions to separation between external circuits and earth		N/A
5.4.11.2	Requirements		N/A
	SPDs bridge separation between external circuit and earth		N/A
	Rated operating voltage U_{op} (V)..... :		—
	Nominal voltage U_{peak} (V)..... :		—
	Max increase due to variation ΔU_{sp}		—
	Max increase due to ageing ΔU_{sa}		—
5.4.11.3	Test method and compliance	(See appended table 5.4.9)	N/A
5.4.12	Insulating liquid		N/A
5.4.12.1	General requirements		N/A
5.4.12.2	Electric strength of an insulating liquid	(See appended table 5.4.9)	N/A
5.4.12.3	Compatibility of an insulating liquid	(See appended table 5.4.9)	N/A
5.4.12.4	Container for insulating liquid		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
5.5	Components as safeguards		P
5.5.1	General		P
5.5.2	Capacitors and RC units	(See appended table 4.1.2)	P
5.5.2.1	General requirement	(See appended table 4.1.2)	P
5.5.2.2	Safeguards against capacitor discharge after disconnection of a connector	(See appended table 5.5.2.2)	P
5.5.3	Transformers	(See Annex G.5.3)	P
5.5.4	Optocouplers	(See Annex G.12)	P
5.5.5	Relays		N/A
5.5.6	Resistors		N/A
5.5.7	SPDs	Used between L and N	N/A
5.5.8	Insulation between the mains and an external circuit consisting of a coaxial cable		N/A
5.5.9	Safeguards for socket-outlets in outdoor equipment		N/A
	RCD rated residual operating current (mA)		—
5.6	Protective conductor		P
5.6.2	Requirement for protective conductors		P
5.6.2.1	General requirements	Considered	P
5.6.2.2	Colour of insulation	Green-and-yellow wire	P
5.6.3	Requirement for protective earthing conductors	The suitable certified power supply cordset shall be assessed to the national standard.	N/A
	Protective earthing conductor size (mm ²)	Rated current: 7A, Min. 0.75mm ² or 18AWG.	—
	Protective earthing conductor serving as a reinforced safeguard		N/A
	Protective earthing conductor serving as a double safeguard		N/A
5.6.4	Requirements for protective bonding conductors		P
5.6.4.1	Protective bonding conductors		P
	Protective bonding conductor size (mm ²).	Min. 18AWG (0.75mm ²)	—
5.6.4.2	Protective current rating (A).....	Max. 20A	P
5.6.5	Terminals for protective conductors		P
5.6.5.1	Terminal size for connecting protective earthing conductors (mm).....	Approved appliance inlet used	P

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
	Terminal size for connecting protective bonding conductors (mm)	Protective bonding conductors size: 0.75mm ² ; Nominal thread diameter: 3.5mm	P
5.6.5.2	Corrosion		P
5.6.6	Resistance of the protective bonding system		P
5.6.6.1	Requirements		P
5.6.6.2	Test Method..... :	(See appended table 5.6.6.2)	P
5.6.6.3	Resistance (Ω) or voltage drop..... :	(See appended table 5.6.6.2)	P
5.6.7	Reliable connection of a protective earthing conductor		N/A
5.6.8	Functional earthing		N/A
	Conductor size (mm ²)..... :		N/A
	Class II with functional earthing marking		N/A
	Appliance inlet cl & cr (mm)..... :		N/A
5.7	Prospective touch voltage, touch current and protective conductor current		P
5.7.2	Measuring devices and networks		P
5.7.2.1	Measurement of touch current	(See appended table 5.7.4)	P
5.7.2.2	Measurement of voltage	(See appended table 5.2.2.2)	P
5.7.3	Equipment set-up, supply connections and earth connections		P
5.7.4	Unearthed accessible parts	(See appended table 5.7.4)	P
5.7.5	Earthed accessible conductive parts	(See appended table 5.7.5)	P
5.7.6	Requirements when touch current exceeds ES2 limits		N/A
	Protective conductor current (mA)..... :		N/A
	Instructional Safeguard..... :		N/A
5.7.7	Prospective touch voltage and touch current associated with external circuits	No such external circuits	N/A
5.7.7.1	Touch current from coaxial cables		N/A
5.7.7.2	Prospective touch voltage and touch current associated with paired conductor cables		N/A
5.7.8	Summation of touch currents from external circuits		N/A
	a) Equipment connected to earthed external circuits, current (mA)		N/A
	b) Equipment connected to unearthed external circuits, current (mA)..... :		N/A
5.8	Backfeed safeguard in battery backed up supplies		N/A
	Mains terminal ES		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
	Air gap (mm)		N/A

6	ELECTRICALLY- CAUSED FIRE		P
6.2	Classification of PS and PIS		P
6.2.2	Power source circuit classifications	(See appended table 6.2.2)	P
6.2.3	Classification of potential ignition sources		P
6.2.3.1	Arcing PIS	(See appended table 6.2.3.1)	P
6.2.3.2	Resistive PIS	(See appended table 6.2.3.2)	P
6.3	Safeguards against fire under normal operating and abnormal operating conditions		P
6.3.1	No ignition and attainable temperature value less than 90 % defined by ISO 871 or less than 300 °C for unknown materials	(See appended table B.1.5, B.2.6 and B.3)	P
	Combustible materials outside fire enclosure	(See appended table 4.1.2)	P
6.4	Safeguards against fire under single fault conditions		P
6.4.1	Safeguard method		P
6.4.2	Reduction of the likelihood of ignition under single fault conditions in PS1 circuits		P
6.4.3	Reduction of the likelihood of ignition under single fault conditions in PS2 and PS3 circuits		P
6.4.3.1	Supplementary safeguards		P
6.4.3.2	Single Fault Conditions	(See appended table B.4)	P
	Special conditions for temperature limited by fuse		P
6.4.4	Control of fire spread in PS1 circuits		P
6.4.5	Control of fire spread in PS2 circuits		P
6.4.5.2	Supplementary safeguards		P
6.4.6	Control of fire spread in PS3 circuits	-Printed board: rated V-1 or better; -Internal wire insulation and tubing complied with Clause 6.5.1; - Motors complied with G.5.4; - Transformers complied with G.5.3; - All other components: at least V-2 except for mounted on min. V-1 material or small parts of combustible material; -Fire enclosure material: rated V-0.	P
6.4.7	Separation of combustible materials from a PIS		N/A
6.4.7.2	Separation by distance		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
6.4.7.3	Separation by a fire barrier		N/A
6.4.8	Fire enclosures and fire barriers		P
6.4.8.2	Fire enclosure and fire barrier material properties		P
6.4.8.2.1	Requirements for a fire barrier		N/A
6.4.8.2.2	Requirements for a fire enclosure	Fire enclosure material: rated V-0	P
6.4.8.3	Constructional requirements for a fire enclosure and a fire barrier		P
6.4.8.3.1	Fire enclosure and fire barrier openings		P
6.4.8.3.2	Fire barrier dimensions		N/A
6.4.8.3.3	Top openings and properties		N/A
	Openings dimensions (mm)..... :	No top openings	N/A
6.4.8.3.4	Bottom openings and properties		P
	Openings dimensions (mm)..... :	No bottom openings below a PIS as shown in Figure 42	P
	Flammability tests for the bottom of a fire enclosure		N/A
	Instructional Safeguard..... :		N/A
6.4.8.3.5	Side openings and properties		P
	Openings dimensions (mm)..... :	No side openings(below a PIS located in a PS3 circuit) that fall within the area indicated by the 5 degree angle in Figure 44.	P
6.4.8.3.6	Integrity of a fire enclosure, condition met: a), b) or c)..... :		N/A
6.4.8.4	Separation of a PIS from a fire enclosure and a fire barrier distance (mm) or flammability rating..... :	Fire enclosure is made of V-0 class material	P
6.4.9	Flammability of insulating liquid..... :		N/A
6.5	Internal and external wiring		P
6.5.1	General requirements	(See appended table 4.1.2)	P
6.5.2	Requirements for interconnection to building wiring..... :		N/A
6.5.3	Internal wiring size (mm ²) for socket-outlets..... :		N/A
6.6	Safeguards against fire due to the connection to additional equipment		P

7	INJURY CAUSED BY HAZARDOUS SUBSTANCES	P
7.2	Reduction of exposure to hazardous substances	N/A
7.3	Ozone exposure	N/A
7.4	Use of personal safeguards or personal protective equipment (PPE)	N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
	Personal safeguards and instructions :		—
7.5	Use of instructional safeguards and instructions		N/A
	Instructional safeguard (ISO 7010) :		—
7.6	Batteries and their protection circuits		P

8	MECHANICALLY-CAUSED INJURY		P
8.2	Mechanical energy source classifications		P
8.3	Safeguards against mechanical energy sources		P
8.4	Safeguards against parts with sharp edges and corners		P
8.4.1	Safeguards		P
	Instructional Safeguard..... :	MS1 classification, no safeguard required	N/A
8.4.2	Sharp edges or corners		P
8.5	Safeguards against moving parts		P
8.5.1	Fingers, jewellery, clothing, hair, etc., contact with MS2 or MS3 parts	All plastic fan blades: MS1 classification.	N/A
	MS2 or MS3 part required to be accessible for the function of the equipment		N/A
	Moving MS3 parts only accessible to skilled person		N/A
8.5.2	Instructional safeguard :		N/A
8.5.4	Special categories of equipment containing moving parts		N/A
8.5.4.1	General		N/A
8.5.4.2	Equipment containing work cells with MS3 parts		N/A
8.5.4.2.1	Protection of persons in the work cell		N/A
8.5.4.2.2	Access protection override		N/A
8.5.4.2.2.1	Override system		N/A
8.5.4.2.2.2	Visual indicator		N/A
8.5.4.2.3	Emergency stop system		N/A
	Maximum stopping distance from the point of activation (m)..... :		N/A
	Space between end point and nearest fixed mechanical part (mm) :		N/A
8.5.4.2.4	Endurance requirements		N/A
	Mechanical system subjected to 100 000 cycles of operation		N/A
	- Mechanical function check and visual inspection		N/A
	- Cable assembly :		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
8.5.4.3	Equipment having electromechanical device for destruction of media		N/A
8.5.4.3.1	Equipment safeguards		N/A
8.5.4.3.2	Instructional safeguards against moving parts		N/A
8.5.4.3.3	Disconnection from the supply		N/A
8.5.4.3.4	Cut type and test force (N).....		N/A
8.5.4.3.5	Compliance		N/A
8.5.5	High pressure lamps		N/A
	Explosion test.....		N/A
8.5.5.3	Glass particles dimensions (mm)		N/A
8.6	Stability of equipment		P
8.6.1	General	MS2 classification	P
	Instructional safeguard		N/A
8.6.2	Static stability	All appearance were considered.	P
8.6.2.2	Static stability test	The equipment is placed on a plane at an angle of 10° from the horizontal and rotated slowly through an angle of 360° about its normal vertical axis; during the tests, the equipment was not tip over.	P
8.6.2.3	Downward force test		N/A
8.6.3	Relocation stability		N/A
	Wheels diameter (mm)	No wheels used	—
	Tilt test		N/A
8.6.4	Glass slide test		N/A
8.6.5	Horizontal force test		N/A
8.7	Equipment mounted to wall, ceiling or other structure		N/A
8.7.1	Mount means type		N/A
8.7.2	Test methods		N/A
	Test 1, additional downwards force (N).....		N/A
	Test 2, number of attachment points and test force (N).....		N/A
	Test 3 Nominal diameter (mm) and applied torque (Nm).....		N/A
8.8	Handles strength		N/A
8.8.1	General	No handle	N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
8.8.2	Handle strength test		N/A
	Number of handles.....:		—
	Force applied (N)		—
8.9	Wheels or casters attachment requirements		N/A
8.9.2	Pull test	No wheels or casters attachment	N/A
8.10	Carts, stands and similar carriers		N/A
8.10.1	General	No carts, stands or similar carriers	N/A
8.10.2	Marking and instructions.....:		N/A
8.10.3	Cart, stand or carrier loading test		N/A
	Loading force applied (N)		N/A
8.10.4	Cart, stand or carrier impact test		N/A
8.10.5	Mechanical stability		N/A
	Force applied (N)		—
8.10.6	Thermoplastic temperature stability		N/A
8.11	Mounting means for slide-rail mounted equipment (SRME)		N/A
8.11.1	General	No such equipment	N/A
8.11.2	Requirements for slide rails		N/A
	Instructional Safeguard.....:		N/A
8.11.3	Mechanical strength test		N/A
8.11.3.1	Downward force test, force (N) applied.....:		N/A
8.11.3.2	Lateral push force test		N/A
8.11.3.3	Integrity of slide rail end stops		N/A
8.11.4	Compliance		N/A
8.12	Telescoping or rod antennas		N/A
	Button/ball diameter (mm)		—

9	THERMAL BURN INJURY		P
9.2	Thermal energy source classifications		P
9.3	Touch temperature limits		P
9.3.1	Touch temperatures of accessible parts	(See appended table 9.3)	P
9.3.2	Test method and compliance		P
9.4	Safeguards against thermal energy sources		P
9.5	Requirements for safeguards		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
9.5.1	Equipment safeguard	TS1 classification, no safeguard required	N/A
9.5.2	Instructional safeguard		N/A
9.6	Requirements for wireless power transmitters		N/A
9.6.1	General	No wireless power transmitters	N/A
9.6.2	Specification of the foreign objects		N/A
9.6.3	Test method and compliance		N/A

10	RADIATION		P
10.2	Radiation energy source classification		P
10.2.1	General classification		P
	Lasers		—
	Lamps and lamp systems	LEDs used for indicating lights: Exempt group	—
	Image projectors	RG2 according to IEC/EN 62471-5; Class 1 according to IEC/EN 60825-1.	—
	X-Ray		—
	Personal music player		—
10.3	Safeguards against laser radiation		P
	The standard(s) equipment containing laser(s) comply	Image projector with lasers (according to IEC/EN 60825-1)	P
10.4	Safeguards against optical radiation from lamps and lamp systems (including LED types)		P
10.4.1	General requirements	The image projector was classified as RG2 projector according to IEC/EN 62471-5	P
	Instructional safeguard provided for accessible radiation level needs to exceed		N/A
	Risk group marking and location	See copy of marking plate	P
	Information for safe operation and installation		P
10.4.2	Requirements for enclosures		N/A
	UV radiation exposure		N/A
10.4.3	Instructional safeguard	The instructional safeguard complied with the requirements of IEC/EN 62471-5 for Risk Group 2.	P
10.5	Safeguards against X-radiation		N/A
10.5.1	Requirements		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
	Instructional safeguard for skilled persons		—
10.5.3	Maximum radiation (pA/kg).....		—
10.6	Safeguards against acoustic energy sources		N/A
10.6.1	General		N/A
10.6.2	Classification		N/A
	Acoustic output $L_{Aeq,T}$, dB(A).....		N/A
	Unweighted RMS output voltage (mV).....		N/A
	Digital output signal (dBFS).....		N/A
10.6.3	Requirements for dose-based systems		N/A
10.6.3.1	General requirements		N/A
10.6.3.2	Dose-based warning and automatic decrease		N/A
10.6.3.3	Exposure-based warning and requirements		N/A
	30 s integrated exposure level (MEL30)		N/A
	Warning for MEL ≥ 100 dB(A)		N/A
10.6.4	Measurement methods		N/A
10.6.5	Protection of persons		N/A
	Instructional safeguards		N/A
10.6.6	Requirements for listening devices (headphones, earphones, etc.)		N/A
10.6.6.1	Corded listening devices with analogue input		N/A
	Listening device input voltage (mV)		N/A
10.6.6.2	Corded listening devices with digital input		N/A
	Max. acoustic output $L_{Aeq,T}$, dB(A)		N/A
10.6.6.3	Cordless listening devices		N/A
	Max. acoustic output $L_{Aeq,T}$, dB(A)		N/A

B	NORMAL OPERATING CONDITION TESTS, ABNORMAL OPERATING CONDITION TESTS AND SINGLE FAULT CONDITION TESTS		P
B.1	General		P
B.1.5	Temperature measurement conditions	(See appended table B.1.5)	P
B.2	Normal operating conditions		P
B.2.1	General requirements	(See Test Item Particulars and appended test tables)	P
	Audio Amplifiers and equipment with audio amplifiers	(See Annex E)	P
B.2.3	Supply voltage and tolerances		P
B.2.5	Input test	(See appended table B.2.5)	P

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
B.3	Simulated abnormal operating conditions		P
B.3.1	General		P
B.3.2	Covering of ventilation openings	(See appended table B.3)	P
	Instructional safeguard :		N/A
B.3.3	DC mains polarity test		N/A
B.3.4	Setting of voltage selector		N/A
B.3.5	Maximum load at output terminals	(See appended table B.3)	P
B.3.6	Reverse battery polarity	(See Annex M)	P
B.3.7	Audio amplifier abnormal operating conditions	(See Annex E)	P
B.3.8	Safeguards functional during and after abnormal operating conditions :	(See appended table B.3)	P
B.4	Simulated single fault conditions		P
B.4.1	General		P
B.4.2	Temperature controlling device	No such device	N/A
B.4.3	Blocked motor test		P
B.4.4	Functional insulation		P
B.4.4.1	Short circuit of clearances for functional insulation	(See appended table B.4)	P
B.4.4.2	Short circuit of creepage distances for functional insulation	(See appended table B.4)	P
B.4.4.3	Short circuit of functional insulation on coated printed boards		N/A
B.4.5	Short-circuit and interruption of electrodes in tubes and semiconductors	(See appended table B.4)	P
B.4.6	Short circuit or disconnection of passive components	(See appended table B.4)	P
B.4.7	Continuous operation of components	No such components	N/A
B.4.8	Compliance during and after single fault conditions :	(See appended table B.4)	P
B.4.9	Battery charging and discharging under single fault conditions	(See Annex M)	P

C	UV RADIATION		N/A
C.1	Protection of materials in equipment from UV radiation		N/A
C.1.2	Requirements	No UV radiation	N/A
C.1.3	Test method		N/A
C.2	UV light conditioning test		N/A
C.2.1	Test apparatus..... :		N/A
C.2.2	Mounting of test samples		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
C.2.3	Carbon-arc light-exposure test		N/A
C.2.4	Xenon-arc light-exposure test		N/A
D	TEST GENERATORS		P
D.1	Impulse test generators		P
D.2	Antenna interface test generator		P
D.3	Electronic pulse generator		N/A
E	TEST CONDITIONS FOR EQUIPMENT CONTAINING AUDIO AMPLIFIERS		P
E.1	Electrical energy source classification for audio signals		P
	Maximum non-clipped output power (W)..... :	8.97W for each	—
	Rated load impedance (Ω) :	4 Ω (2pcs provided for model XR03B) 4 Ω (one provided for model XR06B)	—
	Open-circuit output voltage (V)..... :	5.98V for each	—
	Instructional safeguard :	No safeguard necessary	—
E.2	Audio amplifier normal operating conditions		P
	Audio signal source type :	(See appended table B.2.5)	—
	Audio output power (W)..... :	1.12W for each	—
	Audio output voltage (V) :	2.11V for each	—
	Rated load impedance (Ω) :	4 Ω (2pcs provided for model XR03B) 4 Ω (one provided for model XR06B)	—
	Requirements for temperature measurement	(See Table B.1.5)	P
E.3	Audio amplifier abnormal operating conditions	(See Table B.3, B.4)	P
F	EQUIPMENT MARKINGS, INSTRUCTIONS, AND INSTRUCTIONAL SAFEGUARDS		P
F.1	General		P
	Language :	English and French version	—
F.2	Letter symbols and graphical symbols		P
F.2.1	Letter symbols according to IEC60027-1		P
F.2.2	Graphic symbols according to IEC, ISO or manufacturer specific		P
F.3	Equipment markings		P
F.3.1	Equipment marking locations	Located on the exterior of the bottom enclosure and the location of the marking was	P

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
		mentioned in the instructions.	
F.3.2	Equipment identification markings		P
F.3.2.1	Manufacturer identification	Trademark: 	P
F.3.2.2	Model identification	See page 2 for details	P
F.3.3	Equipment rating markings		P
F.3.3.1	Equipment with direct connection to mains		P
F.3.3.2	Equipment without direct connection to mains		N/A
F.3.3.3	Nature of the supply voltage	~	P
F.3.3.4	Rated voltage.....	100V-240V	P
F.3.3.5	Rated frequency	50Hz/60Hz	P
F.3.3.6	Rated current or rated power.....	7A MAX	P
F.3.3.7	Equipment with multiple supply connections	Single supply connection	N/A
F.3.4	Voltage setting device	No voltage setting device	N/A
F.3.5	Terminals and operating devices		P
F.3.5.1	Mains appliance outlet and socket-outlet markings	No mains appliance outlet and socket-outlet	N/A
F.3.5.2	Switch position identification marking.....	No switches	N/A
F.3.5.3	Replacement fuse identification and rating markings	"T8AH 250V~" was marked on PCB near the fuse F1	P
	Instructional safeguards for neutral fuse		N/A
F.3.5.4	Replacement battery identification marking	Relevant warnings were mentioned in user manual	P
F.3.5.5	Neutral conductor terminal		N/A
F.3.5.6	Terminal marking location		P
F.3.6	Equipment markings related to equipment classification		P
F.3.6.1	Class I equipment		P
F.3.6.1.1	Protective earthing conductor terminal	Approved appliance inlet used	P
F.3.6.1.2	Protective bonding conductor terminals	Not be identified	P
F.3.6.2	Equipment class marking	Class I equipment	N/A
F.3.6.3	Functional earthing terminal marking		N/A
F.3.7	Equipment IP rating marking	IP20, no marking is needed	N/A
F.3.8	External power supply output marking		N/A
F.3.9	Durability, legibility and permanence of marking		P
F.3.10	Test for permanence of markings		P
F.4	Instructions		P
	a) Information prior to installation and initial use		P

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
	b) Equipment for use in locations where children not likely to be present		N/A
	c) Instructions for installation and interconnection		P
	d) Equipment intended for use only in restricted access area		N/A
	e) Equipment intended to be fastened in place		N/A
	f) Instructions for audio equipment terminals		N/A
	g) Protective earthing used as a safeguard		P
	h) Protective conductor current exceeding ES2 limits		N/A
	i) Graphic symbols used on equipment		P
	j) Permanently connected equipment not provided with all-pole mains switch		N/A
	k) Replaceable components or modules providing safeguard function		N/A
	l) Equipment containing insulating liquid		N/A
	m) Installation instructions for outdoor equipment		N/A
F.5	Instructional safeguards		P

G	COMPONENTS		P
G.1	Switches		N/A
G.1.1	General	No switches used	N/A
G.1.2	Ratings, endurance, spacing, maximum load		N/A
G.1.3	Test method and compliance		N/A
G.2	Relays		N/A
G.2.1	Requirements		N/A
G.2.2	Overload test		N/A
G.2.3	Relay controlling connectors supplying power to other equipment		N/A
G.2.4	Test method and compliance		N/A
G.3	Protective devices		P
G.3.1	Thermal cut-offs		N/A
	Thermal cut-outs separately approved according to IEC 60730 with conditions indicated in a) & b)		N/A
	Thermal cut-outs tested as part of the equipment as indicated in c)		N/A
G.3.1.2	Test method and compliance		N/A
G.3.2	Thermal links		N/A
G.3.2.1	a) Thermal links tested separately according to IEC 60691 with specifics		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
	b) Thermal links tested as part of the equipment		N/A
G.3.2.2	Test method and compliance		N/A
G.3.3	PTC thermistors	Secondary approved PTC thermistor used (See appended table 4.1.2)	P
G.3.4	Overcurrent protection devices	Approved current fuse provided (See appended table 4.1.2)	P
G.3.5	Safeguards components not mentioned in G.3.1 to G.3.4		N/A
G.3.5.1	Non-resettable devices suitably rated and marking provided		N/A
G.3.5.2	Single faults conditions		N/A
G.4	Connectors		P
G.4.1	Spacings		P
G.4.2	Mains connector configuration..... :	Approved appliance inlet used	P
G.4.3	Plug is shaped that insertion into mains socket-outlets or appliance coupler is unlikely	Mismating of connectors to mains plugs or sockets are impossible.	P
G.5	Wound components		P
G.5.1	Wire insulation in wound components	Approved TIW used as primary winding of transformer (TH1)	P
G.5.1.2	Protection against mechanical stress	Separated by insulation tape and tube used on TIW of the transformer (TH1)	P
G.5.2	Endurance test		N/A
G.5.2.1	General test requirements		N/A
G.5.2.2	Heat run test		N/A
	Test time (days per cycle)		—
	Test temperature (°C)..... :		—
G.5.2.3	Wound components supplied from the mains		N/A
G.5.2.4	No insulation breakdown		N/A
G.5.3	Transformers		P
G.5.3.1	Compliance method..... :	The isolation transformer meets the requirements given in G.5.3.2 and G.5.3.3	P
	Position	(See appended table 4.1.2)	P
	Method of protection	Electronic protection	P
G.5.3.2	Insulation		P

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
	Protection from displacement of windings..... :	Fixed by bobbin and insulation tape	—
G.5.3.3	Transformer overload tests	(See appended table B.3)	P
G.5.3.3.1	Test conditions		P
G.5.3.3.2	Winding temperatures	Maximum temperatures of windings did not exceed the limits given in Table G.3. During the test, the transformer did not emit flames or molten metal and withstand the electric strength test in 5.4.9.1	P
G.5.3.3.3	Winding temperatures - alternative test method		N/A
G.5.3.4	Transformers using FIW		N/A
G.5.3.4.1	General		N/A
	FIW wire nominal diameter..... :		—
G.5.3.4.2	Transformers with basic insulation only		N/A
G.5.3.4.3	Transformers with double insulation or reinforced insulation..... :		N/A
G.5.3.4.4	Transformers with FIW wound on metal or ferrite core		N/A
G.5.3.4.5	Thermal cycling test and compliance		N/A
G.5.3.4.6	Partial discharge test		N/A
G.5.3.4.7	Routine test		N/A
G.5.4	Motors		P
G.5.4.1	General requirements	DC Fan used (See appended table 4.1.2)	P
G.5.4.2	Motor overload test conditions		P
G.5.4.3	Running overload test		N/A
G.5.4.4.2	Locked-rotor overload test		N/A
	Test duration (days)..... :		—
G.5.4.5	Running overload test for DC motors	No happened in overload	N/A
G.5.4.5.2	Tested in the unit		N/A
G.5.4.5.3	Alternative method		N/A
G.5.4.6	Locked-rotor overload test for DC motors		P
G.5.4.6.2	Tested in the unit	(See append table B.3)	P
	Maximum Temperature..... :	Maximum temperatures of windings did not exceed the limits given in Table G.3.	P
G.5.4.6.3	Alternative method		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
G.5.4.7	Motors with capacitors		N/A
G.5.4.8	Three-phase motors		N/A
G.5.4.9	Series motors		N/A
	Operating voltage		—
G.6	Wire Insulation		P
G.6.1	General		P
G.6.2	Enamelled winding wire insulation		N/A
G.7	Mains supply cords		N/A
G.7.1	General requirements		N/A
	Type.....	The suitable certified power supply cordset shall be assessed to the national standard.	—
G.7.2	Cross sectional area (mm ² or AWG)		N/A
G.7.3	Cord anchorages and strain relief for non-detachable power supply cords	Detachable power supply cord used	N/A
G.7.3.2	Cord strain relief		N/A
G.7.3.2.1	Requirements		N/A
	Strain relief test force (N).....		N/A
G.7.3.2.2	Strain relief mechanism failure		N/A
G.7.3.2.3	Cord sheath or jacket position, distance (mm)		N/A
G.7.3.2.4	Strain relief and cord anchorage material		N/A
G.7.4	Cord Entry		N/A
G.7.5	Non-detachable cord bend protection		N/A
G.7.5.1	Requirements		N/A
G.7.5.2	Test method and compliance		N/A
	Overall diameter or minor overall dimension, <i>D</i> (mm)		—
	Radius of curvature after test (mm)		—
G.7.6	Supply wiring space		N/A
G.7.6.1	General requirements		N/A
G.7.6.2	Stranded wire		N/A
G.7.6.2.1	Requirements		N/A
G.7.6.2.2	Test with 8 mm strand		N/A
G.8	Varistors		P
G.8.1	General requirements	Approved varistor used (See appended table 4.1.2)	P

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
G.8.2	Safeguards against fire		N/A
G.8.2.1	General	The varistor located more than 13mm from plastic enclosure	N/A
G.8.2.2	Varistor overload test		N/A
G.8.2.3	Temporary overvoltage test		N/A
G.9	Integrated circuit (IC) current limiters		N/A
G.9.1	Requirements	No such component	N/A
	IC limiter output current (max. 5A)..... :		—
	Manufacturers' defined drift :		—
G.9.2	Test Program		N/A
G.9.3	Compliance		N/A
G.10	Resistors		N/A
G.10.1	General		N/A
G.10.2	Conditioning		N/A
G.10.3	Resistor test		N/A
G.10.4	Voltage surge test		N/A
G.10.5	Impulse test		N/A
G.10.6	Overload test		N/A
G.11	Capacitors and RC units		P
G.11.1	General requirements	Approved Y1 capacitors and X2 capacitors used. (See appended table 4.1.2)	P
G.11.2	Conditioning of capacitors and RC units		P
G.11.3	Rules for selecting capacitors		P
G.12	Optocouplers		P
	Optocouplers comply with IEC 60747-5-5 with specifics	Approved optocoupler used (See appended table 4.1.2)	P
	Type test voltage $V_{ini,a}$:	Considered	—
	Routine test voltage, $V_{ini,b}$:	Considered	—
G.13	Printed boards		P
G.13.1	General requirements		P
G.13.2	Uncoated printed boards		P
G.13.3	Coated printed boards		N/A
G.13.4	Insulation between conductors on the same inner surface		N/A
G.13.5	Insulation between conductors on different surfaces		N/A
	Distance through insulation :		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
	Number of insulation layers (pcs) :		—
G.13.6	Tests on coated printed boards		N/A
G.13.6.1	Sample preparation and preliminary inspection		N/A
G.13.6.2	Test method and compliance		N/A
G.14	Coating on components terminals		N/A
G.14.1	Requirements :	(See Clause G.13)	N/A
G.15	Pressurized liquid filled components		N/A
G.15.1	Requirements		N/A
G.15.2	Test methods and compliance		N/A
G.15.2.1	Hydrostatic pressure test		N/A
G.15.2.2	Creep resistance test		N/A
G.15.2.3	Tubing and fittings compatibility test		N/A
G.15.2.4	Vibration test		N/A
G.15.2.5	Thermal cycling test		N/A
G.15.2.6	Force test		N/A
G.15.3	Compliance		N/A
G.16	IC including capacitor discharge function (ICX)		P
G.16.1	Condition for fault tested is not required	Approved ICX used (See appended table 4.1.2)	N/A
	ICX with associated circuitry tested in equipment		N/A
	ICX tested separately		N/A
G.16.2	Tests		N/A
	Smallest capacitance and smallest resistance specified by ICX manufacturer for impulse test..... :		—
	Mains voltage that impulses to be superimposed on :		—
	Largest capacitance and smallest resistance for ICX tested by itself for 10000 cycles test :		—
G.16.3	Capacitor discharge test..... :		N/A

H	CRITERIA FOR TELEPHONE RINGING SIGNALS	N/A
H.1	General	N/A
H.2	Method A	N/A
H.3	Method B	N/A
H.3.1	Ringling signal	N/A
H.3.1.1	Frequency (Hz) :	—
H.3.1.2	Voltage (V) :	—

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
H.3.1.3	Cadence; time (s) and voltage (V)		—
H.3.1.4	Single fault current (mA):		—
H.3.2	Tripping device and monitoring voltage		N/A
H.3.2.1	Conditions for use of a tripping device or a monitoring voltage		N/A
H.3.2.2	Tripping device		N/A
H.3.2.3	Monitoring voltage (V)		N/A

J	INSULATED WINDING WIRES FOR USE WITHOUT INTERLEAVED INSULATION		P
J.1	General		P
	Winding wire insulation	Approved TIW used in transformer TH1	—
	Solid round winding wire, diameter (mm)		N/A
	Solid square and rectangular (flatwise bending) winding wire, cross-sectional area (mm ²).....		N/A
J.2/J.3	Tests and Manufacturing		—

K	SAFETY INTERLOCKS		N/A
K.1	General requirements		N/A
	Instructional safeguard		N/A
K.2	Components of safety interlock safeguard mechanism		N/A
K.3	Inadvertent change of operating mode		N/A
K.4	Interlock safeguard override		N/A
K.5	Fail-safe		N/A
K.5.1	Under single fault condition		N/A
K.6	Mechanically operated safety interlocks		N/A
K.6.1	Endurance requirement		N/A
K.6.2	Test method and compliance		N/A
K.7	Interlock circuit isolation		N/A
K.7.1	Separation distance for contact gaps & interlock circuit elements		N/A
	In circuit connected to mains, separation distance for contact gaps (mm).....		N/A
	In circuit isolated from mains, separation distance for contact gaps (mm).....		N/A
	Electric strength test before and after the test of K.7.2		N/A
K.7.2	Overload test, Current (A)		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
K.7.3	Endurance test		N/A
K.7.4	Electric strength test		N/A

L	DISCONNECT DEVICES		P
L.1	General requirements	The mains plug used as disconnect device	P
L.2	Permanently connected equipment		N/A
L.3	Parts that remain energized		N/A
L.4	Single-phase equipment	The mains plug disconnect both poles simultaneously	P
L.5	Three-phase equipment		N/A
L.6	Switches as disconnect devices		N/A
L.7	Plugs as disconnect devices		P
L.8	Multiple power sources		N/A
	Instructional safeguard :		N/A

M	EQUIPMENT CONTAINING BATTERIES AND THEIR PROTECTION CIRCUITS		P
M.1	General requirements		P
M.2	Safety of batteries and their cells		N/A
M.2.1	Batteries and their cells comply with relevant IEC standards :		N/A
M.3	Protection circuits for batteries provided within the equipment	2pcs AAA batteries used in remote controller	P
M.3.1	Requirements		P
M.3.2	Test method		P
	Overcharging of a rechargeable battery		N/A
	Excessive discharging		P
	Unintentional charging of a non-rechargeable battery		P
	Reverse charging of a rechargeable battery		N/A
M.3.3	Compliance	(See appended table M.3)	P
M.4	Additional safeguards for equipment containing a portable secondary lithium battery		N/A
M.4.1	General		N/A
M.4.2	Charging safeguards		N/A
M.4.2.1	Requirements		N/A
M.4.2.2	Compliance :		N/A
M.4.3	Fire enclosure :		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
M.4.4	Drop test of equipment containing a secondary lithium battery		N/A
M.4.4.2	Preparation and procedure for the drop test		N/A
M.4.4.3	Drop, Voltage on reference and dropped batteries (V); voltage difference during 24 h period (%): :		N/A
M.4.4.4	Check of the charge/discharge function		N/A
M.4.4.5	Charge / discharge cycle test		N/A
M.4.4.6	Compliance		N/A
M.5	Risk of burn due to short-circuit during carrying		N/A
M.5.1	Requirement		N/A
M.5.2	Test method and compliance		N/A
M.6	Safeguards against short-circuits		N/A
M.6.1	External and internal faults		N/A
M.6.2	Compliance		N/A
M.7	Risk of explosion from lead acid and NiCd batteries		N/A
M.7.1	Ventilation preventing explosive gas concentration		N/A
	Calculated hydrogen generation rate :		N/A
M.7.2	Test method and compliance		N/A
	Minimum air flow rate, Q (m ³ /h)..... :		N/A
M.7.3	Ventilation tests		N/A
M.7.3.1	General		N/A
M.7.3.2	Ventilation test – alternative 1		N/A
	Hydrogen gas concentration (%)..... :		N/A
M.7.3.3	Ventilation test – alternative 2		N/A
	Obtained hydrogen generation rate..... :		N/A
M.7.3.4	Ventilation test – alternative 3		N/A
	Hydrogen gas concentration (%)..... :		N/A
M.7.4	Marking :		N/A
M.8	Protection against internal ignition from external spark sources of batteries with aqueous electrolyte		N/A
M.8.1	General		N/A
M.8.2	Test method		N/A
M.8.2.1	General		N/A
M.8.2.2	Estimation of hypothetical volume V_z (m ³ /s) :		—
M.8.2.3	Correction factors :		—
M.8.2.4	Calculation of distance d (mm) :		—

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
M.9	Preventing electrolyte spillage		N/A
M.9.1	Protection from electrolyte spillage		N/A
M.9.2	Tray for preventing electrolyte spillage		N/A
M.10	Instructions to prevent reasonably foreseeable misuse		P
	Instructional safeguard :	Relevant warnings were mentioned in user manual	P
N	ELECTROCHEMICAL POTENTIALS		P
	Material(s) used :	Considered	—
O	MEASUREMENT OF CREEPAGE DISTANCES AND CLEARANCES		P
	Value of X (mm)..... :	Considered	—
P	SAFEGUARDS AGAINST CONDUCTIVE OBJECTS		P
P.1	General		P
P.2	Safeguards against entry or consequences of entry of a foreign object		P
P.2.1	General		P
P.2.2	Safeguards against entry of a foreign object		N/A
	Location and Dimensions (mm) :		—
P.2.3	Safeguards against the consequences of entry of a foreign object	The openings are not located vertically or by a 5°vertical projection above bare conductive parts of a safeguard or PIS or bare conductive parts of ES3 or PS3 circuits.	P
P.2.3.1	Safeguard requirements		N/A
	The ES3 and PS3 keep-out volume in Figure P.3 not applicable to transportable equipment		N/A
	Transportable equipment with metalized plastic parts..... :		N/A
P.2.3.2	Consequence of entry test..... :		N/A
P.3	Safeguards against spillage of internal liquids		N/A
P.3.1	General	No such liquids	N/A
P.3.2	Determination of spillage consequences		N/A
P.3.3	Spillage safeguards		N/A
P.3.4	Compliance		N/A
P.4	Metallized coatings and adhesives securing parts		N/A
P.4.1	General		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
P.4.2	Tests		N/A
	Conditioning, T _c (°C)		—
	Duration (weeks)		—

Q	CIRCUITS INTENDED FOR INTERCONNECTION WITH BUILDING WIRING		P
Q.1	Limited power sources		P
Q.1.1	Requirements		P
	a) Inherently limited output		N/A
	b) Impedance limited output		N/A
	c) Regulating network limited output	(See appended table Q.1)	P
	d) Overcurrent protective device limited output		N/A
	e) IC current limiter complying with G.9		N/A
Q.1.2	Test method and compliance	(See appended table Q.1)	P
	Current rating of overcurrent protective device (A)		N/A
Q.2	Test for external circuits – paired conductor cable		N/A
	Maximum output current (A)		N/A
	Current limiting method		—

R	LIMITED SHORT CIRCUIT TEST		N/A
R.1	General		N/A
R.2	Test setup		N/A
	Overcurrent protective device for test		—
R.3	Test method		N/A
	Cord/cable used for test		—
R.4	Compliance		N/A

S	TESTS FOR RESISTANCE TO HEAT AND FIRE		N/A
S.1	Flammability test for fire enclosures and fire barrier materials of equipment where the steady state power does not exceed 4 000 W		N/A
	Samples, material		—
	Wall thickness (mm)		—
	Conditioning (°C)		—
	Test flame according to IEC 60695-11-5 with conditions as set out		N/A
	- Material not consumed completely		N/A
	- Material extinguishes within 30s		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
	- No burning of layer or wrapping tissue		N/A
S.2	Flammability test for fire enclosure and fire barrier integrity		N/A
	Samples, material		—
	Wall thickness (mm)		—
	Conditioning (°C)		—
S.3	Flammability test for the bottom of a fire enclosure		N/A
S.3.1	Mounting of samples		N/A
S.3.2	Test method and compliance		N/A
	Mounting of samples		—
	Wall thickness (mm)		—
S.4	Flammability classification of materials		N/A
S.5	Flammability test for fire enclosures and fire barrier materials of equipment where the steady state power exceeding 4 000 W		N/A
	Samples, material		—
	Wall thickness (mm)		—
	Conditioning (°C)		—

T	MECHANICAL STRENGTH TESTS		P
T.1	General		P
T.2	Steady force test, 10 N	(See appended table T.2)	P
T.3	Steady force test, 30 N		N/A
T.4	Steady force test, 100 N		N/A
T.5	Steady force test, 250 N	(See appended table T.5)	P
T.6	Enclosure impact test	(See appended table T.6)	P
	Fall test		P
	Swing test		P
T.7	Drop test		N/A
T.8	Stress relief test.....	(See appended table T.8)	P
T.9	Glass Impact Test		N/A
T.10	Glass fragmentation test		N/A
	Number of particles counted.....		N/A
T.11	Test for telescoping or rod antennas		N/A
	Torque value (Nm)		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
U	MECHANICAL STRENGTH OF CATHODE RAY TUBES (CRT) AND PROTECTION AGAINST THE EFFECTS OF IMPLOSION		N/A
U.1	General		N/A
	Instructional safeguard :		N/A
U.2	Test method and compliance for non-intrinsically protected CRTs		N/A
U.3	Protective screen		N/A

V	DETERMINATION OF ACCESSIBLE PARTS		P
V.1	Accessible parts of equipment		P
V.1.1	General		P
V.1.2	Surfaces and openings tested with jointed test probes		P
V.1.3	Openings tested with straight unjointed test probes		P
V.1.4	Plugs, jacks, connectors tested with blunt probe		N/A
V.1.5	Slot openings tested with wedge probe		N/A
V.1.6	Terminals tested with rigid test wire		N/A
V.2	Accessible part criterion		P

X	ALTERNATIVE METHOD FOR DETERMINING CLEARANCES FOR INSULATION IN CIRCUITS CONNECTED TO AN AC MAINS NOT EXCEEDING 420 V PEAK (300 V RMS)		N/A
	Clearance	(See appended table X)	N/A

Y	CONSTRUCTION REQUIREMENTS FOR OUTDOOR ENCLOSURES		N/A
Y.1	General	For indoor use only	N/A
Y.2	Resistance to UV radiation		N/A
Y.3	Resistance to corrosion		N/A
Y.3	Resistance to corrosion		N/A
Y.3.1	Metallic parts of outdoor enclosures are resistant to effects of water-borne contaminants by		N/A
Y.3.2	Test apparatus		N/A
Y.3.3	Water – saturated sulphur dioxide atmosphere		N/A
Y.3.4	Test procedure		N/A
Y.3.5	Compliance		N/A
Y.4	Gaskets		N/A
Y.4.1	General		N/A
Y.4.2	Gasket tests		N/A
Y.4.3	Tensile strength and elongation tests		N/A

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
	Alternative test methods :		N/A
Y.4.4	Compression test		N/A
Y.4.5	Oil resistance		N/A
Y.4.6	Securing means	(See Annex P.4)	N/A
Y.5	Protection of equipment within an outdoor enclosure		N/A
Y.5.1	General		N/A
Y.5.2	Protection from moisture		N/A
	Relevant tests of IEC 60529 or Y.5.3 :		N/A
Y.5.3	Water spray test		N/A
Y.5.4	Protection from plants and vermin		N/A
Y.5.5	Protection from excessive dust		N/A
Y.5.5.1	General		N/A
Y.5.5.2	IP5X equipment		N/A
Y.5.5.3	IP6X equipment		N/A
Y.6	Mechanical strength of enclosures		N/A
Y.6.1	General		N/A
Y.6.2	Impact test :	(See Table T.6)	N/A

IEC 62368-1							
Clause	Requirement + Test			Result - Remark			Verdict
5.2	TABLE: Classification of electrical energy sources						P
Supply Voltage	Location (e.g. circuit designation)	Test conditions	Parameters				ES Class
			U (V)	I (mA)	Type ¹⁾	Additional Info ²⁾	
264VAC	All primary circuits	Normal:	--	--	--	--	ES3 (declared)
		Abnormal:	--	--	--	--	
		Single fault:	--	--	--	--	
264VAC	Transformer (TH1) secondary pins	Normal:	--	--	--	--	ES3 (declared)
		Abnormal:	--	--	--	--	
		Single fault:	--	--	--	--	
264VAC	TH1 pin 7,8 (11,12) - 9,10 (after DH1, DH2)	Normal	49.18VDC	--	SS	--	ES1
		Abnormal	--	--	--	--	--
		Single fault – SC: DH1	0	--	SS	--	ES1
264VAC	USB3.0 port output “+” to “-”	Normal	5.07VDC	--	SS	--	ES1
		Abnormal	--	--	--	--	--
		Single fault – SC: UU2 pin 1-6	5.07VDC	--	SS	--	ES1
		Single fault – SC: RU19	5.07VDC	--	SS	--	ES1
264VAC	USB2.0 port output “+” to “-”	Normal	5.00VDC	--	SS	--	ES1
		Abnormal	--	--	--	--	--
		Single fault – SC: QMS2 pin D-S (bypass FU2)	5.00VDC	--	SS	--	ES1
Supplementary information:							
Abbreviation: SC=Short Circuit, OC=Open Circuit							
1) Type: Steady state (SS), Capacitance (CP), Single pulse (SP), Repetitive pulses (RP), etc.							
2) Additional Info: Frequency, Pulse duration, Pulse off time, Capacitance value, etc.							
3) Models XR06B and XR03B were considered and recorded the worst result.							

5.4.1.8	TABLE: Working voltage measurement				P
Location		RMS voltage (V)	Peak voltage (V)	Frequency (kHz)	Comments
TH1 pin 1-7,8		204	404	51.3	--
TH1 pin 1-9,10		234	458	51.3	--
TH1 pin 1-11,12		278	512	51.3	Max. V_{RMS} & V_{peak}
TH1 pin 2-7,8		182	348	51.3	--

IEC 62368-1				
Clause	Requirement + Test		Result - Remark	Verdict
TH1 pin 2-9,10	166	292	51.3	--
TH1 pin 2-11,12	165	312	51.3	--
TH1 pin 4-7,8	177	375	51.3	--
TH1 pin 4-9,10	174	377	51.3	--
TH1 pin 4-11,12	188	428	51.3	--
TH1 pin 5-7,8	180	418	51.3	--
TH1 pin 5-9,10	174	368	51.3	--
TH1 pin 5-11,12	180	404	51.3	--
TH1 pin 6-7,8	189	436	51.3	--
TH1 pin 6-9,10	175	384	51.3	--
TH1 pin 6-11,12	176	384	51.3	--
Optocoupler primary to secondary (PH1) (Max.)	212	362	0.06	--
CY4 primary to secondary	172	362	0.06	--
CY1 primary to earth	106	197	0.06	--
CY2 primary to earth	121	220	0.06	--
Supplementary information:				
Tested at model XR06B.				

5.4.1.10.2	TABLE: Vicat softening temperature of thermoplastics				N/A
Method.....:			ISO 306 / B50		—
Object/ Part No./Material		Manufacturer/trademark	Thickness (mm)	T softening (°C)	
--		--	--	--	
Supplementary information:					

5.4.1.10.3	TABLE: Ball pressure test of thermoplastics			P
Allowed impression diameter (mm)		≤ 2 mm		—
Object/Part No./Material	Manufacturer/trademark	Thickness (mm)	Test temperature (°C)	Impression diameter (mm)
AC Connector (CN1) Refer table 4.1.2	Refer table 4.1.2	Min. 2.5	125	Max. 1.2
Supplementary information:				
The material of the transformer's bobbin is phenolic, no test is required.				

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict

5.4.2, 5.4.3	TABLE: Minimum Clearances/Creepage distance							P
Clearance (cl) and creepage distance (cr) at/of/between:	U _p (V)	U _{rms} (V)	Freq ¹⁾ (kHz)	Required cl (mm)	cl (mm)	E.S. ²⁾ (V)	Required cr (mm)	cr (mm)
L to N before fuse F1 (BI)	340	240	<30	2.3	4.4	--	2.4	4.4
Across fuse F1(BI)	340	240	<30	2.3	9.2	--	2.4	9.2
L trace before fuse to primary trace (BI)	340	240	<30	2.3	4.4	--	2.4	4.4
Primary trace/components to earthed metal cover (BI)	340	240	<30	2.3	3.3	--	2.4	6.9
Across Y-cap CY1, CY2 (BI)	340	240	<30	2.3	7.1	--	2.4	7.1
Across Y-cap CY4 (BI)	362	240	<30	2.3	7.6	--	2.4	7.6
Across optocoupler (PH1)	362	240	<30	2.3	7.6	--	2.4	7.6
Primary trace to secondary trace under transformer TH1 (RI)	512	278	*	4.5	7.6	--	5.6	7.6
TH1: core to primary windings/pins (RI)	512	278	*	4.5	7.1	--	5.6	7.1
TH1 core to around primary components (RI)	512	278	*	4.5	8.0	--	5.6	8.0
TH1: Primary windings/pins to secondary windings (RI)	512	278	*	4.5	7.1	--	5.6	7.1
Primary live parts to secondary components/wires (RI)	340	240	<30	4.5	>5.9	--	4.8	>6.3
Primary live parts to accessible surface (RI)	340	240	<30	4.5	>5.9	--	4.8	>6.3
Supplementary information:								

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
1) Only for frequency above 30 kHz 2) Complete Electric Strength voltage (E.S. (V) when 5.4.2.4 applied) 1. * means the frequency above and below 30kHz. 2. Provide Material Group IIIb; 3. BI: basic insulation; SI: supplementary insulation; DI: double insulation; RI: reinforced insulation; 4. The core of transformer (TH1) was considered as secondary part. 5. At least two layers insulation tape was wrapped on bottom core of transformer TH1, used as reinforced insulation. 6. The insulation sheet under/above the power supply board used as basic insulation. 7. Heat shrinkable tube used on L/N lead wire as basic insulation and secondary lead wires of power supply board as supplementary insulation. 8. Glue used to fix between CY1 and CY2. 9. Limit from Table 14 based on the required withstand voltage (2500Vpeak), which is higher than Table 10 and Table 11. 10. Unit was evaluated for altitude up to 5000m above sea level correction factor for clearance is 1.48. 11. Both models XR06B and XR03B were considered and recorded the worst result.			

5.4.4.2	TABLE: Minimum distance through insulation				P
Distance through insulation (DTI) at/of	Peak voltage (V)	Insulation	Required DTI (mm)	Measured DTI (mm)	
Plastic enclosure	340	Reinforced	0.4	Min. 1.50	
Bobbin of TH1	512	Reinforced	0.4	Min. 0.71	
*Optocoupler (PH1)	362	Reinforced	0.4	Min. 0.40	
*Heat shrinkable tube (used on secondary lead wires of power supply board)	340	Supplementary	0.4	Min. 0.40	
Supplementary information:					
* means that the tests were evaluation on all alternative sources, with the same results.					

IEC 62368-1						
Clause	Requirement + Test			Result - Remark		Verdict
5.4.4.9	TABLE: Solid insulation at frequencies >30 kHz					P
Insulation material	E_P	Frequency (kHz)	K_R	Thickness d (mm)	Insulation	V_{PW} (Vpk)
Transformer TH1 bobbin	--	51.3	0.39	0.71	Reinforced	512
Supplementary information:						
As an alternative method, the electric strength test according to 5.4.9.1 was applied, see appended table 5.4.9.						

5.4.9	TABLE: Electric strength tests			P
Test voltage applied between:		Voltage shape (Surge, Impulse, AC, DC, etc.)	Test voltage (V)	Breakdown Yes / No
Functional:				
--		--	--	--
Basic/supplementary:				
L and N before fuse (F1 disconnected)		DC	2500	No
L/N to earthing metal parts		DC	2500	No
*Heat shrinkable tube (wrapped on L/N lead wires and secondary lead wires of power supply board)		DC	2500	No
*Insulation sheet under/above power board		DC	2500	No
Reinforced:				
L/N to plastic enclosure with metal foil		DC	4000	No
L/N to secondary unearthed terminals		DC	4000	No
Transformer TH1: core to primary windings/pins		DC	4000	No
Transformer TH1: primary windings to secondary windings		DC	4000	No
*Each layer of two layers insulation tape (used in TH1)		DC	4000	No
Routine Tests:				
--		--	--	--
Supplementary information:				
1. All the electric strength tests were conducted after humidity conditioning which comply to clause 5.4.8. 2. * means that the tests were evaluation on all alternative sources, with the same results. 3. Both models XR06B and XR03B were considered and recorded the worst result.				

5.5.2.2	TABLE: Stored discharge on capacitors					P
Location	Supply voltage (V)	Operating and fault condition ¹⁾	Switch position	Measured voltage (Vpk)	ES Class	

IEC 62368-1					
Clause	Requirement + Test		Result - Remark		Verdict
Phase to Neutral	264	Normal operation	--	8	ES1
Phase to Earth	264	Normal operation	--	4	ES1
Neutral to Earth	264	Normal operation	--	4	ES1
Phase to Neutral	264	RP14 OC	--	12	ES1
Supplementary information:					
X-capacitors installed for testing: CX1=CX2=0.68uF					
☒ bleeding resistor rating: RP5= RP7= 10MΩ					
☒ ICX: U1					
1) Normal operating condition (e.g., normal operation, or open fuse); SC= short circuit, OC= open circuit					
2) Test Location: Phase to Neutral; Phase to Phase; Phase to Earth; and/or Neutral to Earth					

5.6.6	TABLE: Resistance of protective conductors and terminations				P
Location	Test current (A)	Duration (min)	Voltage drop (V)	Resistance (Ω)	
Earth pin of AC inlet to earthed metal parts	40	2	0.20	0.005	
Earth pin of AC inlet to earthed metal parts	32	2	0.16	0.005	
Supplementary information:					
Both models XR06B and XR03B were considered and recorded the worst result.					

5.7.4	TABLE: Unearthed accessible parts					P
Location	Operating and fault conditions	Supply Voltage (VAC)	Parameters			ES class
			Voltage (V _{rms} or V _{pk})	Current (A _{rms} or A _{pk})	Freq. (Hz)	
Accessible plastic enclosure with metal foil and either pole of the supply source	Normal Condition	264	--	0.08mA _{peak}	60	ES1
	Abnormal Condition:	--	--	--	--	--
	Fault Condition: SC CP6 (Fuse opened)	264	--	0.14mA _{peak}	60	ES1
	Fault Condition: Earth opened	264	--	0.09mA _{peak}	60	ES1
Secondary unearthed terminals and either pole of the supply source	Normal	264	--	0.11mA _{peak}	60	ES1
	Abnormal	--	--	--	--	--
	Fault Condition: SC CP6 (Fuse opened)	264	--	0.19mA _{peak}	60	ES1
	Fault Condition: Earth opened	264	--	0.16A _{peak}	60	ES1
Supplementary information:						
Both models XR06B and XR03B were considered and recorded the worst result.						

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict

5.7.5	TABLE: Earthed accessible conductive part			P
Supply voltage (V)	264Vac/60Hz			—
Phase(s)	[X] Single Phase; [] Three Phase: [] Delta [] Wye			
Power Distribution System	[X] TN [X]TT [] IT			
Location	Fault Condition No in IEC 60990 clause 6.2.2	Touch current (mA)	Comment	
Measured to protective earthing terminal	1 (Earth opened)	0.33mA _{pk}	--	
	1 (Neutral opened)	0.26mA _{pk}	--	
Supplementary Information:				
Both models XR06B and XR03B were considered and recorded the worst result.				

5.8	TABLE: Backfeed safeguard in battery backed up supplies					N/A
Location	Supply voltage (V)	Operating and fault condition	Time (s)	Open-circuit voltage (V)	Touch current (A)	ES Class
--	--	--	--	--	--	--
Supplementary information:						
Abbreviation: SC= short circuit, OC= open circuit						

6.2.2	TABLE: Power source circuit classifications					P
Location	Operating and fault condition	Voltage (V)	Current (A)	Max. Power ¹⁾ (W)	Time (S)	PS class
All internal circuits/ components except for DC Fans, USB2.0/USB3.0 ports output, speaker	Normal, abnormal and fault condition	--	--	--	--	PS3 (declared)
Batteries output (used in remote controller)*	Normal	1.40	1.10	1.54	>3s	PS1

IEC 62368-1						
Clause	Requirement + Test			Result - Remark		Verdict
USB2.0 port output	Normal	4.83	2.0	9.66	>3s	PS1
	Single fault – SC: QMS2 pin D-S (bypass FU2)	4.83	2.0	9.66	>3s	PS1
USB3.0 port output	Normal	4.82	2.2	10.60	>3s	PS1
	Single fault – SC: UU2 pin 1-6	4.82	2.2	10.60	>3s	PS1
	Single fault – SC: RU16	4.82	2.2	10.60	>3s	PS1
Supply of DC Fan for model XR06B	Normal	10.34	5.0	51.70	>5s	PS2
	Single fault – SC: RX4	10.34	5.0	51.70	>5s	PS2
Supply of DC Fan 1 for model XR03B	Normal	10.16	6.0	60.96	>5s	PS2
	Single fault – SC: RX4	10.16	6.0	60.96	>5s	PS2
Supply of DC Fan 2 for model XR03B	Normal	10.44	4.5	46.98	>5s	PS2
	Single fault – SC: RX4	10.44	4.5	46.98	>5s	PS2
Supply of speaker	Normal	2.11	0.53	1.12	>3s	PS1
	Single fault – Max. non-clipped output power	5.98	1.50	8.97	>3s	PS1
Supplementary information:						
Abbreviation: SC= short circuit; OC= open circuit 1) Measured after 3 s for PS1 and measured after 5 s for PS2 and PS3. 2) *means that the remote controller was supplied by 2pcs fresh batteries. 3) All DC fans are in parallel with same circuits. 4) Unless otherwise specified, both models XR06B and XR03B were considered and recorded the worst result.						

6.2.3.1	TABLE: Determination of Arcing PIS				P
Location		Open circuit voltage after 3 s (Vpk)	Measured r.m.s current (A)	Calculated value	Arcing PIS? Yes / No
All internal circuits /components		> 50Vpk	--	> 15VA	Yes*
Supplementary information:					
* All internal circuits/components were considered as arcing PIS.					
An Arcing PIS requires a minimum of 50 V (peak) a.c. or d.c. An Arcing PIS is established when the product of the open circuit voltage (V_p) and normal operating condition rms current (I_{rms}) is greater than 15.					

IEC 62368-1				
Clause	Requirement + Test		Result - Remark	Verdict
6.2.3.2	TABLE: Determination of resistive PIS			P
Location		Operating and fault condition	Dissipate power (W)	Resistive PIS? Yes / No
All internal circuits/components except for USB2.0/USB3.0 ports output and speaker		--	>15	Yes*
Supplementary information:				
* All internal circuits/components except for USB2.0/USB3.0 ports output and speaker were considered as resistive PIS. A combination of voltmeter, VA and ammeter IA may be used instead of a wattmeter. If a separate voltmeter and ammeter are used, the product of (VA x IA) is used to determine Resistive PIS classification. A Resistive PIS: (a) dissipates more than 15 W, measured after 30 s of normal operation, <u>or</u> (b) under single fault conditions has either a power exceeding 100 W measured immediately after the introduction of the fault if electronic circuits, regulators or PTC devices are used, or has an available power exceeding 15 W measured 30 s after introduction of the fault.				

8.5.5	TABLE: High pressure lamp				N/A
Lamp manufacturer		Lamp type	Explosion method	Longest axis of glass particle (mm)	Particle found beyond 1 m Yes / No
--		--	--	--	--
Supplementary information:					

9.6	TABLE: Temperature measurements for wireless power transmitters							N/A
Supply voltage (V)..... :			--					—
Max. transmit power of transmitter (W)..... :			--					—
Foreign objects	w/o receiver and direct contact		with receiver and direct contact		with receiver and at distance of 2 mm		with receiver and at distance of 5 mm	
	Object (°C)	Ambient (°C)	Object (°C)	Ambient (°C)	Object (°C)	Ambient (°C)	Object (°C)	Ambient (°C)
--	--	--	--	--	--	--	--	--
Supplementary information:								

IEC 62368-1					
Clause	Requirement + Test			Result - Remark	Verdict
5.4.1.4, 9.3, B.1.5, B.2.6	TABLE: Temperature measurements				P
Supply voltage (V)	90V/ 60Hz ¹⁾	264V/ 60Hz ¹⁾	90V/ 60Hz ²⁾	264V/ 60Hz ²⁾	—
Ambient temperature during test T_{amb} (°C)	See below	See below	See below	See below	—
Maximum measured temperature T of part/at:	T (°C)				Allowed T_{max} (°C)
AC inlet	53.6	50.1	53.9	44.8	70
Primary lead wires connected to power supply board	52.9	49.7	53.2	44.2	105
AC connector CN1	50.5	46.2	51.2	44.8	85
CX1 body	69.8	51.0	68.6	46.4	85
LP2 winding	64.2	48.3	62.8	45.3	130
LP4 winding	70.7	51.3	69.4	46.5	130
CY1 body	51.9	46.8	52.1	45.1	125
RV1 body	71.6	52.2	70.6	46.0	85
CP6 body	57.3	50.5	57.7	46.0	105
LP1 winding	92.1	64.5	89.5	50.2	130
PCB near BD2	96.9	64.4	95.5	52.4	130
PCB near QP4	98.6	65.4	97.1	53.2	130
PCB near QH1	71.8	64.1	70.3	50.9	130
LH1 winding	70.2	63.2	69.2	50.2	130
TH1 core	102.1	88.0	99.7	69.0	130
TH1 winding	105.3	91.0	102.8	70.0	130
PCB near DB1	87.4	61.7	85.0	49.1	130
CY4 body	89.6	80.2	87.8	58.2	125
Optocoupler PH1	68.8	63.6	68.6	50.2	110
PCB near DH1	100.3	83.8	97.2	56.6	130
CH6 body	84.8	76.3	83.3	61.5	105
L1 winding	67.2	62.7	66.9	54.5	130
Insulation sheet under power board	67.9	58.0	67.0	46.4	Ref.
Metal heat sink	65.3	58.8	68.0	63.3	Ref.
Internal wire for main board	51.1	50.0	52.5	58.5	80
PCB near US1 (on main board)	67.1	65.9	66.9	62.2	130
PCB near UD8 (on main board)	62.9	61.6	62.8	50.7	130
PCB near UP7 (on main board)	54.3	53.3	54.9	47.6	130
Internal wire for speaker	56.3	55.4	56.3	47.4	80

IEC 62368-1							
Clause	Requirement + Test				Result - Remark		Verdict
Internal wire for motor	62.3	61.1	62.2	50.1	80		
DC fan right	50.4	49.2	51.5	50.3	Ref.		
DC fan left	44.6	43.5	45.8	43.0	Ref.		
Enclosure inside near Fan vent (side)	53.7	51.4	56.7	50.2	Ref.		
Enclosure inside near USB port (rear)	52.8	51.1	52.6	49.1	Ref.		
Enclosure inside near power board (bottom)	52.3	51.0	56.7	49.5	Ref.		
Enclosure inside near main board (top)	52.7	46.6	53.1	50.5	Ref.		
Ambient	40.0	40.0	40.0	40.0	--		
Touch temperature for accessible parts							
Enclosure outside near Fan vent (side)	30.1	31.1	32.8	31.4	77*		
Enclosure outside near USB port (rear)	33.5	30.4	33.8	30.0	77*		
Enclosure outside near power board (bottom)	35.0	30.9	32.1	29.0	77*		
Enclosure outside near main board (top)	33.3	30.1	31.8	29.0	77*		
Button	32.5	28.8	31.8	28.1	77*		
Lens surface	42.1	40.0	40.1	36.8	71*		
Ambient	25.0	25.0	25.0	25.0	77*		
Temperature T of winding:	t ₁ (°C)	R ₁ (Ω)	t ₂ (°C)	R ₂ (Ω)	T (°C)	Allowed T _{max} (°C)	Insulation class
--	--	--	--	--	--	--	--
Supplementary information:							
- Thermal coupler method used for above temperature tests. - * means that surfaces touched occasionally for very short periods (> 1 s and < 10 s). - Tests was conducted at HDMI mode with maximum power consumption configuration, three vertical bar signal and 1kHz sine wave input, adjust volume to 1/8 max.non-clipped output power at speaker, and DC fans with min. air flow installed. USB2.0 port loading 5VDC/2.0A(max. attainable) and USB3.0 port loading 5VDC/2.2A(max. attainable) during test. - ¹⁾ For model XR06B, ²⁾ For model XR03B.							

B.2.5		TABLE: Input test						P
U (V)	Hz	I (A)	I rated (A)	P (W)	P rated (W)	Fuse No	I fuse (A)	Condition/status
Tested at model XR06B								
90	50	4.694	--	421.4	--	F1	421.4	HDMI mode, Maximum normal condition
100	50	4.190	7.0	417.9	--	F1	417.9	
240	50	1.667	7.0	396.4	--	F1	396.4	
264	50	1.508	--	395.2	--	F1	395.2	
90	60	4.703	--	422.7	--	F1	422.7	
100	60	4.196	7.0	418.2	--	F1	418.2	

IEC 62368-1									
Clause		Requirement + Test					Result - Remark		Verdict
240	60	1.672	7.0	398.0	--	F1	398.0		
264	60	1.517	--	396.9	--	F1	396.9		
Tested at model XR03B									
90	50	4.485	--	402.9	--	F1	4.485	HDMI mode, Maximum normal condition	
100	50	3.991	7.0	398.8	--	F1	3.991		
240	50	1.590	7.0	379.7	--	F1	1.590		
264	50	1.442	--	378.8	--	F1	1.442		
90	60	4.491	--	403.2	--	F1	4.491		
100	60	4.006	7.0	399.1	--	F1	4.006		
240	60	1.595	7.0	380.2	--	F1	1.595		
264	60	1.446	--	379.9	--	F1	1.446		
Supplementary information:									
Maximum normal condition: Three vertical bar signal and 1kHz sine wave input, projection display adjusted to obtain maximum power consumption configuration, the speaker was adjusted to 1/8 Max. non-clipped output power, and DC fans with min. air flow installed. USB2.0 port loading 5VDC/2.0A(max. attainable) and USB3.0 port loading 5VDC/2.2A(max. attainable) during test.									

B.3, B.4		TABLE: Abnormal operating and fault condition tests					P
Ambient temperature T _{amb} (°C)..... :				23.4 (unless otherwise specified)		—	
Power source for EUT: Manufacturer, model/type, outputrating .. :				--		—	
Component No.	Condition	Supply voltage (VAC)	Test time	Fuse no.	Fuse current (A)	Observation	
Tested at model XR06B							
Openings	Blocked	264	1hr 42mins	F1	1.517	Unit operated normally, no damage, no hazard. TH1 core: 73.2°C; TH1 winding: 76.2°C; PCB (main board): 51.1°C; Plastic enclosure outside: 32.2°C; Button: 29.8°C; Lens surface: 40.9°C; Ambient: 25.0°C	

IEC 62368-1						
Clause	Requirement + Test				Result - Remark	Verdict
Speaker	Maximum non-clipped output power	264	1hr 59mins	F1	1.581	Unit operated normally, no damage, no hazard. TH1 core: 76.4°C; TH1 winding: 79.6°C; PCB (main board): 54.8°C; Plastic enclosure outside: 34.1°C; Button: 30.6°C; Lens surface: 41.3°C; Ambient: 25.0°C
DC Fan (left)	Locked	264	7hrs	F1	1.517-0.106	Unit operated normally, and shut down after 15 minutes. no damage, no hazard. TH1 core: 64.1°C; TH1 winding: 67.6°C; PCB (main board): 49.4°C; Plastic enclosure outside: 30.5°C; DC fan right: 33.1°C; DC fan left: 40.5°C; Button: 32.9°C; Lens surface: 29.3°C; Ambient: 25.0°C
DC Fan (right)	Locked	264	7hrs	F1	1.517-0.106	Unit operated normally, and shut down after 15 minutes. no damage, no hazard. TH1 core: 64.0°C; TH1 winding: 67.0°C; PCB (main board): 49.2°C; Plastic enclosure outside: 30.9°C; DC fan right: 40.9°C; DC fan left: 34.8°C; Button: 33.2°C; Lens surface: 30.8°C; Ambient: 25.0°C
Speaker	SC	264	10mins	F1	1.499	Speaker shut down, other function operated as normal, no damage, no hazard.

IEC 62368-1						
Clause	Requirement + Test				Result - Remark	Verdict
TH1 pin 7,8-9 (after DH2)	OL	264	4hrs 03mins	FP1	2.428 Max.	The max. extra loaded current was 7.0A and max. temperature was obtained. Over it, unit shut down immediately, no damage, no hazards. TH1 core: 103.5°C; TH1 winding: 110.0°C; PCB (main board): 51.4°C; Plastic enclosure outside: 32.7°C; Button: 35.1°C; Lens surface: 42.8°C; Ambient: 25.0°C
BD2*	SC	264	<1s	F1	>22 to 0	Fuse (F1) open immediately, no hazard.
BD1*	SC	264	<1s	F1	>22 to 0	Fuse (F1) open immediately, no hazard.
CP6*	SC	264	<1s	F1	>22 to 0	Fuse (F1) open immediately, no hazard.
QP1 pin D-S*	SC	264	<1s	F1	>22 to 0	Fuse (F1) open immediately, no hazard.
QP1 pin D-G*	SC	264	<1s	F1	>22 to 0	Fuse (F1) open immediately, no hazard.
QP1 pin S-G	SC	264	10mins	F1	0.106	Unit shut down immediately, no damage, no hazard.
QH4 pin D-S*	SC	264	<1s	F1	>22 to 0	Fuse (F1) open immediately, no hazard.
QH4 pin D-G*	SC	264	<1s	F1	>22 to 0	Fuse (F1) open immediately, no hazard.
QH4 pin S-G	SC	264	10mins	F1	0.106	Unit shut down immediately, no damage, no hazard.
U1 pin 1-16*	SC	264	<1s	F1	>22 to 0	Fuse (F1) open immediately, no hazard.
U1 pin 3-16	SC	264	10mins	F1	0.106	Unit shut down immediately, no damage, no hazard.
U1 pin 13-16	SC	264	10mins	F1	0.106	Unit shut down immediately, no damage, no hazard.
PH1 pin 1-2	SC	264	10mins	F1	0.106	Unit shut down immediately, no damage, no hazard.
PH1 pin 3-4	SC	264	10mins	F1	0.106	Unit shut down immediately, no damage, no hazard.
TH1 pin 1-2	SC	264	10mins	F1	0.106	Unit shut down immediately, no damage, no hazard.
TH1 pin 4-5	SC	264	10mins	F1	0.106	Unit shut down immediately, no damage, no hazard.

IEC 62368-1						
Clause	Requirement + Test				Result - Remark	Verdict
TH1 pin 5-6	SC	264	10mins	F1	0.106	Unit shut down immediately, no damage, no hazard.
TH1 pin 7,8-9	SC	264	10mins	F1	0.106	Unit shut down immediately, no damage, no hazard.
TH1 pin 11,12-10	SC	264	10mins	F1	0.106	Unit shut down immediately, no damage, no hazard.
CH3	SC	264	10mins	F1	0.106	Unit shut down immediately, no damage, no hazard.
USB2.0 output (bypass FU2)	SC	264	10mins	F1	1.460	USB2.0 output shut down immediately, unit normal work, no damaged, no hazard.
USB3.0 output	SC	264	10mins	F1	1.451	USB3.0 output shut down immediately, unit normal work, no damaged, no hazard.
One battery [#]	Reversed	--	10mins	--	--	Unit shutdown, batteries no explosion, no chemical leaks, no damage, no hazards.
Batteries Output [#]	SC	3VDC	10mins	--	--	No explosion, no chemical leaks, no damage, no hazards.
Tested at model XR03B						
Openings	Blocked	264	1hr 33mins	F1	1.446	Unit operated normally, no damage, no hazard. TH1 core: 71.6°C; TH1 winding: 74.3°C; PCB (main board): 50.8°C; Plastic enclosure outside: 32.1°C; Button: 30.5°C; Lens surface: 40.5°C; Ambient: 25.0°C
Speaker	Maximum non-clipped output power	264	1hr 46mins	F1	1.509	Unit operated normally, no damage, no hazard. TH1 core: 75.0°C; TH1 winding: 78.1°C; PCB (main board): 52.6°C; Plastic enclosure outside: 32.8°C; Button: 30.7°C; Lens surface: 41.9°C; Ambient: 25.0°C

IEC 62368-1						
Clause	Requirement + Test				Result - Remark	Verdict
DC Fan (left)	Locked	264	7hrs	F1	1.446-0.096	Unit operated normaly, and shut down after 4 mintutes. no damage, no hazard. TH1 core: 63.7°C; TH1 winding: 67.2°C; PCB (main board): 49.2°C; Plastic enclosure outside: 31.7°C; Button: 33.4°C; Lens surface: 29.6°C; Ambient: 25.0°C
DC Fan (right)	Locked	264	7hrs	F1	1.446-0.096	Unit operated normaly, and shut down after 15 mintutes. no damage, no hazard. TH1 core: 61.1°C; TH1 winding: 64.3°C; PCB (main board): 47.4°C; Plastic enclosure outside: 32.9°C; DC fan right: 39.1°C; DC fan left: 32.5°C; Button: 30.2°C; Lens surface: 35.9°C; Ambient: 25.0°C
Supplementary information:						
1) SC: short circuit, OL: overload, OC: open circuit; CD: components damaged; 2) The electric strength tests conducted successfully after the completion of abnormal condition test and fault condition test. 3) Temperature limits under the abnormal condition: Transformer TH1 wingding: 190°C(Class F); PCB: 130°C; DC fan: Reference; Accessible plastic parts: 87°C (>1s and <10s). 4) *: test repeated for all alternative sources listed in table 4.1.2 and same result came out. 5) # means 2pcs fresh batteries were used in the remote controller for test. 6) Tests was conducted at HDMI mode with maximum power consumption configuration, three vertical bar signal and 1kHz sine wave input, adjust volume to 1/8 max.non-clipped output power at speaker, and DC fans with min. air flow installed. USB2.0 port loading 5VDC/2.0A(max. attainable) and USB3.0 port loading 5VDC/2.2A(max. attainable) during test.						

M.3	TABLE: Protection circuits for batteries provided within the equipment					N/A
Is it possible to install the battery in a reverse polarity position?:			--		—	
Equipment Specification	Charging					
	Voltage (V)		Current (A)			
	--		--			
Manufacturer/type	Battery specification					
	Non-rechargeable batteries		Rechargeable batteries			
	Discharging	Unintentional	Charging	Discharging	Reverse	

IEC 62368-1							
Clause	Requirement + Test				Result - Remark		Verdict
	current (A)	charging current (A)	Voltage (V)	Current (A)	current (A)	charging current (A)	
--	--	--	--	--	--	--	--
Note: The tests of M.3.2 are applicable only when above appropriate data is not available.							
Specified battery temperature (°C)				--			
Component No.	Fault condition	Charge/ discharge mode	Test time	Temp. (°C)	Current (A)	Voltage (V)	Observation
--	--	--	--	--	--	--	--
Supplementary information:							
Only “AAA” alkaline battery use in remote controller.							

M.4.2	TABLE: Charging safeguards for equipment containing a secondary lithium battery					N/A
Maximum specified charging voltage (V)					--	—
Maximum specified charging current (A)					--	—
Highest specified charging temperature (°C)					--	—
Lowest specified charging temperature (°C)					--	—
Battery manufacturer/type	Operating and fault condition	Measurement			Observation	
		Charging voltage (V)	Charging current (A)	Temp. (°C)		
--	--	--	--	--	--	
Supplementary information:						
Abbreviation: SC= short circuit; OC= open circuit; MSCV= maximum specified charging voltage; MSCC= maximum specified charging current; HSCT= highest specified charging temperature; LSCT= lowest specified charging temperature						

Q.1	TABLE: Circuits intended for interconnection with building wiring (LPS)						P
Output Circuit	Condition	U _{oc} (V)	Time (s)	I _{sc} (A)		S (VA)	
				Meas.	Limit	Meas.	Limit
USB2.0 port	Normal operation	4.99	5	2.0	8	9.66	100
	Single fault – SC: QMS2 pin D-S (bypass FU2)	4.99	5	2.0	8	9.66	100
USB3.0 port	Normal operation	5.07	5	2.2	8	10.6	100
	Single fault – SC: UU2 pin 1-6	5.07	5	2.2	8	10.6	100
	Single fault – SC: RU16	5.07	5	2.2	8	10.6	100

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
Supplementary information:			
SC=Short circuit			
Both models XR06B and XR03B were considered and recorded the worst result.			

T.2, T.3, T.4, T.5	TABLE: Steady force test					P
Location/Part	Material	Thickness (mm)	Probe	Force (N)	Test Duration (s)	Observation
Internal component and wires	--	--	--	10	5	Clearances and creepage distances still complied with the requirements of this standard
Top enclosure	Plastic	Min. 1.5	Circular plane surface 30 mm in diameter	250	5	Enclosure remained intact, no damage, no hazard
Bottom enclosure	Plastic	Min. 1.5	Circular plane surface 30 mm in diameter	250	5	Enclosure remained intact, no damage, no hazard
Side enclosure	Plastic	Min. 1.5	Circular plane surface 30 mm in diameter	250	5	Enclosure remained intact, no damage, no hazard
Supplementary information:						

T.6, T.9	TABLE: Impact test				P
Location/Part		Material	Thickness (mm)	Height (mm)	Observation
Top enclosure		Plastic	Min. 1.5	1300	Enclosure remained intact, no damage, no hazard
Bottom enclosure		Plastic	Min. 1.5	1300	Enclosure remained intact, no damage, no hazard
Side enclosure		Plastic	Min. 1.5	1300	Enclosure remained intact, no damage, no hazard
Supplementary information:					

T.7	TABLE: Drop test				N/A
Location/Part	Material	Thickness (mm)	Height (mm)	Observation	
--	--	--	--	--	
Supplementary information:					

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict

T.8	TABLE: Stress relief test					P
Location/Part	Material	Thickness (mm)	Oven Temperature (°C)	Duration (h)	Observation	
Enclosure	Plastic	Min. 1.5	70	7	No damaged, no hazards	
Insulation sheet under/above power supply board	Plastic	Min. 0.4	77.9	7	No damaged, no hazards	
Supplementary information:						

X	TABLE: Alternative method for determining minimum clearances distances				N/A
Clearance distanced between:	Peak of working voltage (V)	Required cl (mm)	Measured cl (mm)		
--	--	--	--		
Supplementary information:					

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict

4.1.2	TABLE: Critical components information					P
Object / part No.	Manufacturer/ trademark	Type / model	Technical data	Standard	Mark(s) of conformity ¹⁾	
Plastic enclosure	Guangdong Aldex Advanced Plastics Co., Ltd.	PC/ABS-551(X)	V-0, 60 °C, Min. thickness 1.6mm	UL 94, IEC 60695-11-10, CSA C22.2 No. 0.17, IEC/EN IEC 62368-1, UL 62368-1, CSA C22.2 No. 62368-1	cURus & Tested with appliance	
Plastic material of laser module	TEIJIN LIMITED RESIN AND PLASTIC	GN-3630H	V-0, 80°C, min. thickness 1.6mm	UL 94, IEC 60695-11-10, CSA C22.2 No. 0.17	cURus	
Insulation sheet under and above power supply board	SABIC JAPAN L L C	FR1(E1) (GG1)	VTM-0, 125°C, min. thickness: 0.25 mm	UL 94, IEC 60695-11-10, IEC/EN IEC 62368-1, UL 62368-1, CSA C22.2 No. 62368-1	UR & Tested with appliance	
(Alternative)	Nantong Huapu photoelectric Material Co., Ltd	EFR86EFR87EFR83	VTM-0, 80°C, min. thickness: 0.25 mm	UL 94, IEC 60695-11-10, IEC/EN IEC 62368-1, UL 62368-1, CSA C22.2 No. 62368-1	UR & Tested with appliance	
(Alternative)	SABIC JAPAN L L C	FR700	V-0, min. 125°C, min. thickness: 0.25 mm	UL 94, IEC 60695-11-10, CSA C22.2 No. 0.17, IEC/EN IEC 62368-1, UL 62368-1, CSA C22.2 No. 62368-1	cURus E207780 & Tested with appliance	
(Alternative)	SABIC INNOVATIVE PLASTICS US L L C	FR700(GG)	V-0, min. 125°C, min. thickness: 0.25 mm	UL 94, IEC 60695-11-10, IEC/EN IEC 62368-1, UL 62368-1, CSA C22.2 No. 62368-1	UR & Tested with appliance	

IEC 62368-1					
Clause	Requirement + Test			Result - Remark	Verdict
(Alternative)	FORMEX, DIV OF ILLINOIS TOOL WORKS INC	FORMEX GK-(a)(d)(f2)	VTM-0, 115°C, min. thickness: 0.25 mm	UL 94, IEC 60695-11-10, CSA C22.2 No. 0.17, IEC/EN IEC 62368-1, UL 62368-1, CSA C22.2 No. 62368-1	cURus & Tested with appliance
(Alternative)	DUPONT HONGJI FILMS FOSHAN CO LTD	EM, EP, EM1	VTM-2, 105°C, min. thickness: 0.25 mm	UL 94, IEC 60695-11-10, CSA C22.2 No. 0.17, IEC/EN IEC 62368-1, UL 62368-1, CSA C22.2 No. 62368-1	cURus & Tested with appliance
(Alternative)	JIANGSU YUXING FILM TECHNOLOGY CO LTD	6021	VTM-2, 105°C, min. thickness: 0.25 mm	UL 94, IEC 60695-11-10, IEC/EN IEC 62368-1, UL 62368-1, CSA C22.2 No. 62368-1	UR & Tested with appliance
(Alternative)	SICHUAN DONGFANG INSULATING MATERIAL CO LTD	DFR3716A(d)	V-0, min. 110°C, min. thickness: 0.25 mm	UL 94, IEC 60695-11-10, IEC/EN IEC 62368-1, UL 62368-1, CSA C22.2 No. 62368-1	UR & Tested with appliance
Speaker (2pcs provided) for model XR03B	Interchangeable	Interchangeable	4ohm, 12W	--	--
Plastic enclosure of speaker cover model XR03B	Interchangeable	Interchangeable	Min. V-0, 80°C	UL 94, IEC 60695-11-10, CSA C22.2 No. 0.17	cURus
Speaker (one provided) for model XR06B	Interchangeable	Interchangeable	4ohm, 10W	--	--
DC Fans (4pcs provided) for model XR06B	NIDEC ADVANCED MOTOR CORP.	D1225R12B9YP-K1	12VDC, 0.61A, Min. 3800 RPM, V-0 plastic	UL 507, IEC/EN IEC 62368-1, UL 62368-1, CSA C22.2 No. 62368-1	UR TUV RH & Tested with appliance

IEC 62368-1					
Clause	Requirement + Test		Result - Remark		Verdict
DC Fan (JX2, JX3) (2pcs provided for model XR03B)	YIJIE ELECTRONIC	DAHD0401B	12VDC, 0.68A 2800±10% RPM, V-0 plastic	UL 507, IEC/EN IEC 62368-1, UL 62368-1, CSA C22.2 No. 62368-1	UR & Tested with appliance
DC Fan (JX1) (one provided for model XR03B)	YIJIE ELECTRONIC	DAHC0251H	12VDC, 0.60A 3000±10% RPM, V-0 plastic	UL 507, IEC/EN IEC 62368-1, UL 62368-1, CSA C22.2 No. 62368-1	UR TUV SUD & Tested with appliance
Laser diode used for model XR06B	NICHIA CORPORATION	NUBB38	VF: 39.4V, IF: 3.0A, 455nm, 57W	IEC/EN 60825-1	TÜV SÜD
		NURB22	VF: 22.5V, IF: 3.2A, 643nm, 26.8W	IEC/EN 60825-1	
Laser diode used for model XR03B	NICHIA CORPORATION	NUBB38	VF: 39.4V, IF: 3.0A, 455nm, 57W	IEC/EN 60825-1	TÜV SÜD
		NURB21	VF: 11.3V, IF: 3.2A, 643nm, 13.5W	IEC/EN 60825-1	
		NURB22	VF: 22.5V, IF: 3.2A, 643nm, 26.8W	IEC/EN 60825-1	
Appliance inlet	INALWAYS ELECTRONICS INC	0707 series	10A, 250Vac, C14, 70°C	IEC/EN 60320-1, UL 60320-1, CAN/CSA-C22.2 No. 60320.1	cURus ENEC
Primary lead wires (connecting between AC inlet and power supply board CN1)	Kunshan Xinghongmeng Electronic Co Ltd	1015	600V, 18AWG, 105°C, VW-1	UL 758, UL 2556	UR
(Alternative)	XINYA ELECTRONIC CO LTD	1015	600V, 18AWG, 105°C, VW-1	UL 758, UL 2556	UR
(Alternative)	Interchangeable	Interchangeable	Min. 300V, Min. 18AWG, Min. 105°C, VW-1	UL 758, UL 2556	UR
Earthing wire (green-and-yellow)	Kunshan Xinghongmeng Electronic Co Ltd	1015	600V, 18AWG, 105°C, VW-1	UL 758, UL 2556	UR

IEC 62368-1					
Clause	Requirement + Test		Result - Remark		Verdict
(Alternative)	XINYA ELECTRONIC CO LTD	1015	600V, 18AWG, 105°C, VW-1	UL 758, UL 2556	UR
(Alternative)	Interchangeable	Interchangeable	Min. 300V, Min. 18AWG, Min. 105°C, VW-1	UL 758, UL 2556	UR
Secondary lead wires (connecting power supply board to main board/laser module)	Kunshan Xinghongmeng Electronic Co Ltd	10064	24AWG, 30V, 105°C, VW-1	UL 758, UL 2556	UR
(Alternative)	SUZHOU RENDE TECHNOLOGY CO LTD	10064	24AWG, 30V, 105°C, VW-1	UL 758, UL 2556	UR
(Alternative)	Kunshan Xinghongmeng Electronic Co Ltd	1571	28AWG, 30V, 80°C, VW-1	UL 758, UL 2556	UR
(Alternative)	XINYA ELECTRONIC CO LTD	1571	28AWG, 30V, 80°C, VW-1	UL 758, UL 2556	UR
Internal secondary wires except for connecting power supply board to main board/laser module	Interchangeable	Interchangeable	Min. 28AWG, Min. 30V, Min. 80°C, VW-1 or FT1	UL 758, UL 2556	UR
Heat shrinkable tube (wrapped on primary lead wires and secondary wires of power supply board)	SHENZHEN WOER HEAT-SHRINKABLE MATERIAL CO LTD	RSFR, RSFR(CB), RSFR-H	VW-1, 125°C, Min.300VAC, min. thickness: 0.4mm	UL 224, CSA-C22.2 No. 198.1, IEC/EN IEC 62368-1, UL 62368-1, CSA C22.2 No. 62368-1	cURus & Tested with appliance
(Alternative)	CHANGYUAN ELECTRONICS GROUP CO LTD	CB-HFT	VW-1, 125°C, 600VAC, min. thickness: 0.4mm	UL 224, CSA-C22.2 No. 198.1, IEC/EN IEC 62368-1, UL 62368-1, CSA C22.2 No. 62368-1	cURus & Tested with appliance

IEC 62368-1					
Clause	Requirement + Test		Result - Remark		Verdict
All PCBs	SHEN ZHEN SUN & LYNN CIRCUITS CO LTD	SL-2, SL-D, SL- HD, SL-M, SL- HM, SL-2M, SL- 4M, SL-M2	V-0, 130°C	UL 94, UL 796	UR
(Alternative)	Interchangeable	Interchangeable	V-1 or better, 130°C	UL 94, UL 796	UR
Secondary PTC (FU2) on main board	POLYTRONICS TECHNOLOGY CORP	SMD1206P110T FT	V _{max} : 8Vdc, 85 °C, I _n : 1.10A, I _t : 2.20A I _{max} : 100A	IEC/EN 62319-1, IEC/EN 62319-1- 1, IEC/EN 60738-1, IEC/EN 60738-1- 1, Clauses 15, 17, annex J of IEC 60730-1, UL 1434	TUV RH UR
Components & materials used on power supply board:					
PCB	Interchangeable	Interchangeable	V-1 or better, 130°C	UL 94, UL 796	UR
AC connector (CN1)	CKM Electronics Co Ltd	3962WV-5P series, 3962WR-5P series, 3962WR	Min. 250VAC, min. 7A, min. 85°C, V-0	UL 1977, CSA C22.2 No. 182.3, IEC/EN IEC 62368-1, UL 62368-1, CSA C22.2 No. 62368-1	cURus & Tested with appliance
Fuse (F1)	Hollyland Company Limited	50CT, 50CT(P)	T8AH, 250VAC	IEC/EN 60127-1, IEC/EN 60127-2, UL 248-1, UL 248-14, CSA-C22.2 No. 248.1, CSA-C22.2 No. 248.14	VDE cURus
(Alternative)	Conquer Electronics Co., Ltd.	UDA, UDA-A	T8AH, 250VAC	IEC/EN 60127-1, IEC/EN 60127-2, UL 248-1, UL 248-14, CSA-C22.2 No. 248.1, CSA-C22.2 No. 248.14	VDE cURus

IEC 62368-1					
Clause	Requirement + Test		Result - Remark		Verdict
(Alternative)	Suzhou Walter Electronic Co. Ltd.	TSC-Serie(s) (for VDE), TSC, TSC+P (for UL)	T8AH, 250VAC	IEC/EN 60127-1, IEC/EN 60127-2, UL 248-1, UL 248-14, CSA-C22.2 No. 248.1, CSA-C22.2 No. 248.14	VDE cURus
(Alternative)	XC Electronics (Shen Zhen) Corp. Ltd.	5H	T8AH, 250VAC	IEC/EN 60127-1, IEC/EN 60127-2, UL 248-1, UL 248-14, CSA-C22.2 No. 248.1, CSA-C22.2 No. 248.14	VDE cURus
(Alternative)	Dongguan Better Electronics Technology Co., Ltd.	524	T8AH, 250VAC	IEC/EN 60127-1, IEC/EN 60127-2, UL 248-1, UL 248-14, CSA-C22.2 No. 248.1, CSA-C22.2 No. 248.14	VDE cURus
Thermistor (RT1, RT3)	Interchangeable	Interchangeable	NTC, 0.7Ω at 25°C, min. 4A	--	--
Varistor (RV1)	Thinking Electronic Industrial Co., Ltd.	TVR14681	Min. 420VAC, Min. 105°C, min. V-0 coating	UL 1449, CSA C22.2 No. 269.5, IEC/EN IEC 61051-1, IEC/EN IEC 61051-2, IEC 61051-2-2, IEC 62368-1/ Annex G.8.1	cURus VDE TUV RH
(Alternative)	Thinking Electronic Industrial Co., Ltd.	TVR14681-M	Min. 420VAC, Min. 125°C, min. V-0 coating	UL 1449, CSA C22.2 No. 269.5, IEC/EN IEC 61051-1, IEC/EN IEC 61051-2, IEC 61051-2-2, IEC 62368-1/ Annex G.8.1	TUV RH VDE cURus

IEC 62368-1					
Clause	Requirement + Test		Result - Remark		Verdict
(Alternative)	Centra Science Corp.	CNR-14D681K	Min. 420VAC, Min. 105°C, min. V-0 coating	UL 1449, CSA C22.2 No. 269.5, IEC/EN IEC 61051-1, IEC/EN IEC 61051-2, IEC 61051-2-2, IEC 62368-1/ Annex G.8.1	VDE cURus
(Alternative)	BestBright Electronics Co. Ltd	681KD14, 14D681K	Min. 420VAC, Min. 105°C, min. V-0 coating	UL 1449, CSA C22.2 No. 269.5, IEC 61051-1, IEC 61051-2, IEC 61051-2-2, IEC 62368-1/ Annex G.8.1	VDE cURus
(Alternative)	Guangdong Huiwan Electronics Technology Co., LTD.	V-681K-14 DEH for VDE, V-681K-14D H, V-681K-14E H for UL	Min. 420VAC, Min. 125°C, min. V-0 coating	UL 1449, CSA C22.2 No. 269.5, IEC 61051-1, IEC 61051-2, IEC 61051-2-2, IEC 62368-1/ Annex G.8.1	VDE cURus
(Alternative)	Shantou High-New Technology Dev. Zone Songtian Enterprise Co., Ltd.	14D681K	Min. 420VAC, Min. 125°C, min. V-0 coating	UL 1449, CSA C22.2 No. 269.5, IEC 61051-1, IEC 61051-2, IEC 61051-2-2 IEC 62368-1/ Annex G.8.1	VDE cURus
(Alternative)	Xiamen Wanming Electronics Co., Ltd.	14D681K for VDE, WMR14D681K for UL	Min. 420VAC, Min. 85°C, min. V-0 coating	UL 1449, CSA C22.2 No. 269.5, IEC/EN 61051-1, IEC 61051-2, IEC 61051-2-2 IEC 62368-1/ Annex G.8.1	VDE cURus

IEC 62368-1					
Clause	Requirement + Test		Result - Remark		Verdict
(Alternative)	Fujian Qiaoguang Electronic Technology co., Ltd.	FTR14D681K	Min. 420VAC, Min. 125°C, min. V-0 coating	UL 1449, CSA C22.2 No. 269.5, IEC/EN IEC 61051-1, IEC/EN IEC 61051-2, IEC 61051-2-2 IEC 62368-1/ Annex G.8.1	VDE cURus
X-Capacitor (CX1, CX2)	Shenzhen Jinghao Capacitor Co., Ltd.	CBB62B	Max. 0.68uF, Min. 250VAC, 40/110/56, X2 type	IEC/EN 60384-14, UL 60384-14, CAN/CSA-E60384-14	VDE cURus
(Alternative)	Europtronic (SuZhou) Co. Ltd.	MPX	Max. 0.68uF, Min. 250VAC, 40/105/21, X2 type	IEC/EN 60384-14, UL 60384-14, CAN/CSA-E60384-14	VDE cURus
(Alternative)	Europtronic (SuZhou) Co. Ltd.	MPX2	Max. 0.68uF, Min. 250VAC, 40/110/56, X2 type	IEC/EN 60384-14, UL 60384-14, CAN/CSA-E60384-14	VDE cURus
(Alternative)	Xiamen Faratronic Co., Ltd.	MKP62	Max. 0.68uF, Min. 250VAC, 40/100/56 or 40/105/56 or 40/110/56, X2 type	IEC/EN 60384-14, UL 60384-14, CAN/CSA-E60384-14	VDE cURus
(Alternative)	Nistronics (Jiangxi) Co., Ltd.	MPR	Max. 0.68uF, Min. 250VAC, 40/100/21 or 40/110/56, X2 type	IEC/EN 60384-14, UL 60384-14, CAN/CSA-E60384-14	VDE cURus
(Alternative)	Yangzhou Nissei Electronics Co., Ltd.	MP1	Max. 0.68uF, Min. 250VAC, 40/110/56 or 40/100/21, X2 type	IEC/EN 60384-14, UL 60384-14, CAN/CSA-E60384-14	VDE cURus
(Alternative)	Shenzhen Yimanfeng Science And Technology Co., Ltd.	X2-MPX/MKP (for VDE) MPX/MKP (for UL)	Max. 0.68uF, Min. 250VAC, 40/100/21 or 40/110/56, X2 type	IEC/EN 60384-14, UL 60384-14, CAN/CSA-E60384-14	VDE cURus
(Alternative)	Ultra Tech Xiphi Enterprise Co. Ltd.	HQX	Max. 0.68uF, Min. 250VAC, 40/110/56, X2 type	IEC/EN 60384-14, UL 60384-14, CAN/CSA-E60384-14	VDE cURus

IEC 62368-1					
Clause	Requirement + Test		Result - Remark		Verdict
(Alternative)	Sichuan Sincerity Technology Co., Ltd.	MPX/MKP	Max. 0.68uF, Min. 250VAC, 40/110/56, X2 type	IEC/EN 60384-14, UL 60384-14, CAN/CSA-E60384-14	VDE cURus
(Alternative)	Sichuan Zhongxing Electr. Co.Ltd.	MKP61	Max. 0.68uF, Min. 250VAC, 40/085/21 or 40/100/21 or 40/110/56, X2 type	IEC/EN 60384-14, UL 60384-14, CAN/CSA-E60384-14	VDE cURus
(Alternative)	GUANGDONG FENGMING ELECTRONIC TECH. CO., LTD.	MKP-X2	Max. 0.68uF, Min. 250VAC, 40/105/21 or 40/110/56, X2 type	IEC/EN 60384-14, UL 60384-14, CAN/CSA-E60384-14	VDE cURus
Bleeder resistor (RP5, RP7)	Interchangeable	Interchangeable	Max. 10MΩ , Min. 1/4W	--	--
Discharge ICX (U1)	Chengdu Monolithic Power Systems Co., Ltd.	HF81	100-240V~, 50-60Hz (Tested for 85-265V~, 47-63Hz)	IEC 62368-1	CB issued by Nemko
(Alternative)	CHIPOWN	PN8200	85-265Vac (with tolerance considered), 50-60Hz	IEC 62368-1	CB issued by UL-CCIC
(Alternative)	Power Integrations, Inc.	CAP200DG	240VAC, 50-60Hz nominal	IEC 62368-1	CB issued by Nemko
(Alternative)	Chengdu Monolithic Power Systems Co., Ltd.	HR1270	100-240VAC, 50-60 Hz (Tested for 85-265VAC, 47-63Hz)	IEC 62368-1	CB issued by Nemko
(Alternative)	NXP Semiconductors Taiwan Ltd	TEA8918YZT (Y = 0-9, B-J or blank; Z = 0-9, A-Z or blank)	100-240VAC, 47-63Hz	IEC 62368-1	CB issued by TÜV RH
(Alternative)	NXP Semiconductors Taiwan Ltd	TEA8919YZT/N (Y=B, G-Z, 0-9 or blank, Z and N=0 to 9, A to Z or Blank)	100-240VAC, 47-63Hz	IEC 62368-1	CB issued by TÜV RH
Y-Capacitor (CY1, CY2)	Walsin Technology Corp.	AH	Max. 470pF, Min. 250VAC, 40/125/21, Y1 type	IEC/EN 60384-14, UL 60384-14, CAN/CSA-E60384-14	VDE cURus

IEC 62368-1					
Clause	Requirement + Test		Result - Remark		Verdict
(Alternative)	Yinan Don's Electronic Component Co., Ltd.	CT81	Max. 470pF, Min. 250VAC, 25/125/21, Y1 type	IEC/EN 60384-14, UL 60384-14, CAN/CSA-E60384-14	VDE cURus
(Alternative)	TDK Corporation	CD	Max. 470pF, Min. 250VAC, 55/125/21, Y1 type	IEC/EN 60384-14, UL 60384-14, CAN/CSA-E60384-14	VDE cURus
(Alternative)	Xiamen Wanming Electronics Co., Ltd.	HJ	Max. 470pF, Min. 250VAC, 40/125/21, Y1 type	IEC/EN 60384-14, UL 60384-14, CAN/CSA-E60384-14	VDE cURus
(Alternative)	KunShan WanSheng Electronics Co., Ltd.	CT7	Max. 470pF, Min. 250VAC, 40/125/21, Y1 type	IEC/EN 60384-14, UL 60384-14, CAN/CSA-E60384-14	VDE cURus
(Alternative)	Guangdong Huiwan Electronics Technology Co., LTD.	AR	Max. 470pF, Min. 250VAC, 40/125/21, Y1 type	IEC/EN 60384-14, UL 60384-14, CAN/CSA-E60384-14	VDE cURus
Y-Capacitor (CY4)	Sichuan Teruixiang Technology International Co Ltd	TRX	Max. 1000pF, Min. 250VAC, 40/125/21, Y1 type	IEC/EN 60384-14, UL 60384-14, CAN/CSA-E60384-14	ENEC CB issued by CQC cURus
(Alternative)	ANSHAN KEIFAT ELECTRONIC CERAMIC TECHNICAL CO LTD	CT7	Max. 1000pF, Min. 250VAC, 25/125/21, Y1 type	IEC/EN 60384-14, UL 60384-14, CAN/CSA-E60384-14	VDE cURus
(Alternative)	Interchangeable	Interchangeable	Max. 1000pF, Min. 250VAC, 25/125/21 or 40/125/21, Y1 type	IEC/EN 60384-14, UL 60384-14, CAN/CSA-E60384-14	cURus, VDE or equal EU mark
Optocoupler (PH1)	Renesas Electronics Corporation	PS2381-1 (for VDE), PS2381-1 (c) (for UL)	Reinforced Insulation, Ext. Cl./Cr. ≥ 8.0mm, Dti. ≥ 0.4mm, 115°C, Vini,a/Vini,b: 6000Vpeak	IEC/EN IEC 60747-5-5, IEC/EN IEC 62368-1, UL 1577	VDE UR

IEC 62368-1					
Clause	Requirement + Test		Result - Remark		Verdict
(Alternative)	Lite-On Technology Corporation	LTV-10xx x = (0;1;2;3;4;5;6;7;8;9)	Reinforced Insulation, Ext. Cl./Cr. $\geq 8.0\text{mm}$, Dti. $\geq 0.4\text{mm}$, 115°C , Vini,a/Vini,b: $6000\text{V}_{\text{peak}}$	IEC/EN IEC 60747-5-5, IEC/EN IEC 62368-1, UL 1577, CSA Component Acceptance Service Notice No. 5A	VDE cURus
(Alternative)	Everlight Electronics Co., Ltd.	EL101X ("X" may be 0 to 9) for UL, EL101(0;1;2;3;4;5;6;7;8;9) V for VDE	Reinforced Insulation, Ext. Cl./Cr. $\geq 8.1\text{mm}$, Dti. $\geq 0.4\text{mm}$, 110°C , Vini,a/Vini,b: $6000\text{V}_{\text{peak}}$	IEC/EN IEC 60747-5-5, IEC/EN IEC 62368-1, UL 1577, CSA Component Acceptance Service Notice No. 5A	VDE cURus
(Alternative)	CT Microelectronics Far East Ltd (For UL), CT Micro International Corporation (For VDE)	CT101(X1)(X2)-W (For UL), CT1(X1)1(X2)(X3) V (Y)(Z)-(H)(G), CT1(X1)1(X2)(X3) V (Y)(Z)-W-(H)(G) (For VDE)	Reinforced Insulation, Ext. Cl./Cr. $\geq 8.0\text{mm}$, Dti. $\geq 0.4\text{mm}$, 110°C , Vini,a/Vini,b: $4000\text{V}_{\text{peak}}$	IEC/EN 60747-5-5, IEC/EN IEC 62368-1, UL 1577, CSA Component Acceptance Service Notice No. 5A	VDE cURus
(Alternative)	Shenzhen Orient Components Co. Ltd.	OR10XXXX (for VDE); OR10xx (for UL)	Reinforced Insulation, Ext. Cl./Cr. $\geq 8.0\text{mm}$, Dti. $\geq 0.4\text{mm}$, 125°C , Vini,a/Vini,b: $6000\text{V}_{\text{peak}}$	IEC/EN IEC 60747-5-5, IEC/EN IEC 62368-1, UL 1577, CSA Component Acceptance Service Notice No. 5A	VDE cURus
(Alternative)	VISHAY Semiconductor GmbH	VOL617A (For VDE), VOL617A+ (For UL)	Reinforced Insulation, Ext. Cl./Cr. $\geq 8.0\text{mm}$, Dti. $\geq 0.4\text{mm}$, 110°C , Vini,a/Vini,b: $6000\text{V}_{\text{peak}}$	IEC/EN IEC 60747-5-5, IEC/EN IEC 62368-1, UL 1577, CSA Component Acceptance Service Notice No. 5A	VDE cURus

IEC 62368-1					
Clause	Requirement + Test		Result - Remark		Verdict
(Alternative)	Toshiba Electronic Devices & Storage Corporation	TLP383 Option (D4) (For VDE); P383 (For UL)	Reinforced Insulation, Ext. Cl./Cr. $\geq 8.0\text{mm}$, Dti. $\geq 0.4\text{mm}$, 125°C , Vini,a/Vini,b: $6000\text{V}_{\text{peak}}$	IEC/EN IEC 60747-5-5, IEC/EN IEC 62368-1, UL 1577, CSA Component Acceptance Service Notice No. 5A	VDE cURus
(Alternative)	NingBo Qunxin Microelectronics Co., LTD	QX10yy-UNY-WVZZ (For VDE); QX10xx-UNY-W (For UL)	Reinforced Insulation, Ext. Cl./Cr. $\geq 8.0\text{mm}$, Dti. $\geq 0.4\text{mm}$, 125°C , Vini,a/Vini,b: $5000\text{V}_{\text{peak}}$	IEC/EN IEC 60747-5-5, UL 1577, CSA Component Acceptance Service Notice No. 5A	VDE cURus
(Alternative)	Xiamen Hualian Semiconductor Technology Co. LTD	HPC101xx-x (For VDE); HPC1018 (For UL)	Reinforced Insulation, Ext. Cl./Cr. $\geq 8.0\text{mm}$, Dti. $\geq 0.4\text{mm}$, 110°C , Vini,a/Vini,b: $6000\text{V}_{\text{peak}}$	IEC/EN IEC 60747-5-5, UL 1577, CSA Component Acceptance Service Notice No. 5A	VDE cURus
PFC inductor (LP1)	Shenzhen MEGMEET Electrical CO., LTD	MPL600-S4-LP2	$500\mu\text{H} \pm 12\%$, Min. 130°C	IEC/EN IEC 62368-1, UL 62368-1, CSA C22.2 No. 62368-1	Tested with appliance
-Magnet wire	Interchangeable	Interchangeable	Min. 130°C	UL 1446	UR
-Base	KINGBOARD LAMINATES HOLDINGS LTD	KB-6150	V-0, 130°C	UL 94	UR
-Margin tape	JINGJIANG YAHUA PRESSURE SENSITIVE GLUE CO LTD	WF* (c)(h)	130°C	UL 510A	UR
Filter choke (LP2, LP3)	Shenzhen MEGMEET Electrical CO., LTD	SQ2418-V-5.3mH	5.3mH, Min. 130°C	IEC/EN IEC 62368-1, UL 62368-1, CSA C22.2 No. 62368-1	Tested with appliance
-Bobbin	CHANG CHUN PLASTICS CO LTD	T200HF, T375HF	Phenolic, V-0, 150°C , Min. thickness: 0.45mm	UL 94	UR

IEC 62368-1					
Clause	Requirement + Test		Result - Remark		Verdict
-(Alternative)	SUMITOMO BAKELITE CO LTD	PM-9823	Phenolic, V-0, 150°C, min. thickness 0.45mm	UL 94	UR
-Magnet wire	Interchangeable	Interchangeable	Min. 130°C	UL 1446	UR
Filter choke (LP4)	Shenzhen MEGMEET Electrical CO., LTD	MP660SG-5Q64- L1	15-60uH, Min. 130°C	IEC/EN IEC 62368-1, UL 62368-1, CSA C22.2 No. 62368-1	Tested with appliance
-Base	SUMITOMO BAKELITE CO LTD	PM-9823	Phenolic, V-0, 150°C, min. thickness 0.45mm	UL 94	UR
-Magnet wire	Interchangeable	Interchangeable	Min. 130°C	UL 1446	UR
-Triple insulation wire	GREAT LEOFON INDUSTRIAL CO LTD	TRW(F)* for UL, TRW(F) Serie(s) for VDE	Reinforced insulation, 155°C	IEC/EN IEC 62368-1, UL 2353	VDE UR
PFC inductor (LH1)	Shenzhen MEGMEET Electrical CO., LTD	MPL-500W-LH2	45uH±5%, Min. 130°C	IEC/EN IEC 62368-1, UL 62368-1, CSA C22.2 No. 62368-1	Tested with appliance
-Margin tape	JINGJIANG YAHUA PRESSURE SENSITIVE GLUE CO LTD	CT* (c)(g)	130°C	UL 510A	UR
-Magnet wire	Interchangeable	Interchangeable	Min. 130°C	UL 1446	UR
-Insulation tube	CHANGYUAN ELECTRONICS GROUP CO LTD	CB-TT-T	200°C, 300V, VW-1	UL 224	UR
-(Alternative)	GREAT HOLDING INDUSTRIAL CO LTD	TFT	200°C, 300V, VW-1	UL 224	UR
-Polymeric Materials	KINGBOARD LAMINATES HOLDINGS LTD	KB-6150	V-0, 130°C	UL 94, UL 746E	UR
-Varnish	Shanghai Huachenya New Material Co.,Ltd.	JS-844@	155 °C	UL 1446	UR
-(Alternative)	HANG CHEUNG COATINGS (HUIYANG) LTD	8562*	155 °C	UL 1446	UR

IEC 62368-1					
Clause	Requirement + Test		Result - Remark		Verdict
Transformer (TH1)	Shenzhen MEGMEET Electrical CO., LTD	PQ3225-50V10A	Class F	IEC/EN IEC 62368-1, UL 62368-1, CSA C22.2 No. 62368-1	Tested with appliance
-Electrical insulation system	Shenzhen MEGMEET Electrical Co., Ltd	G-F	Class F	UL 1446	UR
-Magnet wire	Interchangeable	Interchangeable	Min. 155°C	UL 1446	UR
-Bobbin	SUMITOMO BAKELITE CO LTD	PM-9823	Phenolic, V-0, 150°C, min. thickness: 0.70mm	UL 94	UR
-(Alternative)	CHANG CHUN PLASTICS CO LTD	T200HF, T375HF	Phenolic, V-0, 150°C, min. thickness: 0.70mm	UL 94	UR
-Triple insulation wire	E&B TECHNOLOGY CO LTD	E&B-XXX*YYZF, E&B-XXXP	Reinforced insulation, 155°C	IEC/EN IEC 62368-1, UL 2353	VDE UR
-Insulation tape	JINGJIANG YAHUA PRESSURE SENSITIVE GLUE CO LTD	PF* (d)(g)	180°C	UL 510A	UR
-(Alternative)	XINFENG GHILLIE ELECTRICAL MATERIALS CO LTD	JL-N408	180°C	UL 510A	UR
-Margin Tape	JINGJIANG YAHUA PRESSURE SENSITIVE GLUE CO LTD	WF* (c)(h)	130°C	UL 510A	UR
-Insulation tube	CHANGYUAN ELECTRONICS GROUP CO LTD	CB-TT-T	200°C, 300V, VW-1	UL 224	UR
-Varnish	ELANTAS North America, Inc	V1630FS	155 °C	UL 1446	UR
-(Alternative)	John C Dolph Co	BC-346A	155 °C	UL 1446	UR
Supplementary information:					
1) Provided evidence ensures the agreed level of compliance. See OD-2039. License available upon request.					

Attachment No. 1

IEC62368_1E - ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
ATTACHMENT TO TEST REPORT IEC 62368-1 EUROPEAN GROUP DIFFERENCES AND NATIONAL DIFFERENCES (Audio/video, information and communication technology equipment - Part 1: Safety requirements)			
Differences according to : EN IEC 62368-1:2020+A11:2020			
Attachment Form No : EU_GD_IEC62368_1E			
Attachment Originator : UL(Demko)			
Master Attachment : 2021-02-04			
Copyright © 2021 IEC System for Conformity Testing and Certification of Electrical Equipment (IECEE), Geneva, Switzerland. All rights reserved.			
	CENELEC COMMON MODIFICATIONS (EN)		--
	Clause numbers in the cells that are shaded light grey are clause references in EN IEC 62368-1:2020+A11:2020. All other clause numbers in that column, except for those in the paragraph below, refers to IEC 62368-1:2018. Clauses, subclauses, notes, tables, figures and annexes which are additional to those in IEC 62368-1:2018 are prefixed "Z".		P
	Add the following annexes: Annex ZA (normative) Normative references to international publications with their corresponding European publications Annex ZB (normative) Special national conditions Annex ZC (informative) A-deviations Annex ZD (informative) IEC and CENELEC code designations for flexible cords		P
1	Modification to Clause 3.		
3.3.19	Sound exposure <i>Replace 3.3.19 of IEC 62368-1 with the following definitions:</i>		N/A

Attachment No. 1

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
3.3.19.1	momentary exposure level, MEL metric for estimating 1 s sound exposure level from the HD 483-1 S2 test signal applied to both channels, based on EN 50332-1:2013, 4.2. Note 1 to entry: MEL is measured as A-weighted levels in dB. Note 2 to entry: See B.3 of EN 50332-3:2017 for additional information.		N/A
3.3.19.3	sound exposure, E A-weighted sound pressure (p) squared and integrated over a stated period of time, T Note 1 to entry: The SI unit is $\text{Pa}^2 \text{ s}$. $E = \int_0^T p(t)^2 dt$		N/A
3.3.19.4	sound exposure level, SEL logarithmic measure of sound exposure relative to a reference value, E_0 , typically the 1 kHz threshold of hearing in humans. Note 1 to entry: SEL is measured as A-weighted levels in dB. $SEL = 10 \lg \left(\frac{E}{E_0} \right) \text{ dB}$ Note 2 to entry: See B.4 of EN 50332-3:2017 for additional information.		N/A
3.3.19.5	digital signal level relative to full scale, dBFS levels reported in dBFS are always r.m.s. Full scale level, 0 dBFS, is the level of a dc-free 997-Hz sine wave whose undithered positive peak value is positive digital full scale, leaving the code corresponding to negative digital full scale unused Note 1 to entry: It is invalid to use dBFS for non-r.m.s. levels. Because the definition of full scale is based on a sine wave, the level of signals with a crest factor lower than that of a sine wave may exceed 0 dBFS. In particular, square wave signals may reach +3,01 dBFS.		N/A
2	Modification to Clause 10		
10.6	Safeguards against acoustic energy sources Replace 10.6 of IEC 62368-1 with the following:		N/A

Attachment No. 1

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
10.6.1.1	Introduction Safeguard requirements for protection against long-term exposure to excessive sound pressure levels from personal music players closely coupled to the ear are specified below. Requirements for earphones and headphones intended for use with personal music players are also covered. A personal music player is a portable equipment intended for use by an ordinary person, that: – is designed to allow the user to listen to audio or audiovisual content / material; and – uses a listening device, such as headphones or earphones that can be worn in or on or around the ears; and – has a player that can be body worn (of a size suitable to be carried in a clothing pocket) and is intended for the user to walk around with while in continuous use (for example, on a street, in a subway, at an airport, etc.). EXAMPLES Portable CD players, MP3 audio players, mobile phones with MP3 type features, PDAs or similar equipment. Personal music players shall comply with the requirements of either 10.6.2 or 10.6.3. NOTE 1 Protection against acoustic energy sources from telecom applications is referenced to ITU-T P.360. NOTE 2 It is the intention of the Committee to allow the alternative methods for now, but to only use the dose measurement method as given in 10.6.5 in future. Therefore, manufacturers are encouraged to implement 10.6.5 as soon as possible. Listening devices sold separately shall comply with the requirements of 10.6.6. These requirements are valid for music or video mode only. The requirements do not apply to: – professional equipment; NOTE 3 Professional equipment is equipment sold through special sales channels. All products sold through normal electronics stores are considered not to be professional equipment. – hearing aid equipment and other devices for assistive listening; – the following type of analogue personal music players: • long distance radio receiver (for example, a multiband radio receiver or world band radio receiver, an AM radio receiver), and • cassette player/recorder;		N/A

Attachment No. 1

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
	NOTE 4 This exemption has been allowed because this technology is falling out of use and it is expected that within a few years it will no longer exist. This exemption will not be extended to other technologies. – a player while connected to an external amplifier that does not allow the user to walk around while in use. For equipment that is clearly designed or intended primarily for use by children, the limits of the relevant toy standards may apply. The relevant requirements are given in EN 71-1:2011, 4.20 and the related tests methods and measurement distances apply.		
10.6.1.2	Non-ionizing radiation from radio frequencies in the range 0 to 300 GHz The amount of non-ionizing radiation is regulated by European Council Recommendation 1999/519/EC of 12 July 1999 on the limitation of exposure of the general public to electromagnetic fields (0 Hz to 300 GHz). For intentional radiators, ICNIRP guidelines should be taken into account for Limiting Exposure to Time-Varying Electric, Magnetic, and Electromagnetic Fields (up to 300 GHz). For hand-held and body mounted devices, attention is drawn to EN 50360 and EN 50566.		N/A
10.6.2	Classification of devices without the capacity to estimate sound dose		N/A
10.6.2.1	General This standard is transitioning from short-term based (30 s) requirements to long-term based (40 hour) requirements. These clauses remain in effect only for devices that do not comply with sound dose estimation as stipulated in EN 50332-3. For classifying the acoustic output $L_{Aeq,T}$, measurements are based on the A-weighted equivalent sound pressure level over a 30 s period. For music where the average sound pressure (long term $L_{Aeq,T}$) measured over the duration of the song is lower than the average produced by the programme simulation noise, measurements may be done over the duration of the complete song. In this case, T becomes the duration of the song. NOTE Classical music, acoustic music and broadcast typically has an average sound pressure (long term $L_{Aeq,T}$) which is much lower than the average programme simulation noise. Therefore, if the player is capable to analyse the content and compare it with the programme simulation noise, the warning		N/A

Attachment No. 1

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
	does not need to be given as long as the average sound pressure of the song does not exceed the required limit. For example, if the player is set with the programme simulation noise to 85 dB, but the average music level of the song is only 65 dB, there is no need to give a warning or ask an acknowledgement as long as the average sound level of the song is not above the basic limit of 85 dB.		
10.6.2.2	RS1 limits (to be superseded, see 10.6.3.2) RS1 is a class 1 acoustic energy source that does not exceed the following: – for equipment provided as a package (player with its listening device), and with a proprietary connector between the player and its listening device, or where the combination of player and listening device is known by other means such as setting or automatic detection, the $L_{Aeq,T}$ acoustic output shall be ≤ 85 dB when playing the fixed “programme simulation noise” described in EN 50332-1. – for equipment provided with a standardized connector (for example, a 3,5 phone jack) that allows connection to a listening device for general use, the unweighted r.m.s. output voltage shall be ≤ 27 mV (analogue interface) or -25 dBFS (digital interface) when playing the fixed “programme simulation noise” described in EN 50332-1. – The RS1 limits will be updated for all devices as per 10.6.3.2.		N/A
10.6.2.3	RS2 limits (to be superseded, see 10.6.3.3) RS2 is a class 2 acoustic energy source that does not exceed the following: – for equipment provided as a package (player with its listening device), and with a proprietary connector between the player and its listening device, or when the combination of player and listening device is known by other means such as setting or automatic 130 detection, the $L_{Aeq,T}$ acoustic output shall be ≤ 100 dB(A) when playing the fixed “programme simulation noise” as described in EN 50332-1. – for equipment provided with a standardized connector (for example, a 3,5 phone jack) that allows connection to a listening device for general use, the unweighted r.m.s. output voltage shall be ≤ 150 mV (analogue interface) or -10 dBFS (digital interface) when playing the fixed “programme simulation noise” as described in EN 50332-1.		N/A

Attachment No. 1

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
10.6.2.4	RS3 limits RS3 is a class 3 acoustic energy source that exceeds RS2 limits.		N/A
10.6.3	Classification of devices (new)		N/A
10.6.3.1	General Previous limits (10.6.2) created abundant false negative and false positive PMP sound level warnings. New limits, compliant with The Commission Decision of 23 June 2009, are given below.		N/A
10.6.3.2	RS1 limits (new) RS1 is a class 1 acoustic energy source that does not exceed the following: – for equipment provided as a package (player with its listening device), and with a proprietary connector between the player and its listening device, or where the combination of player and listening device is known by other means such as setting or automatic detection, the $L_{Aeq,T}$ acoustic output shall be ≤ 80 dB when playing the fixed “programme simulation noise” described in EN 50332-1. – for equipment provided with a standardized connector (for example, a 3,5 phone jack) that allows connection to a listening device for general use, the unweighted r.m.s. output voltage shall be ≤ 15 mV (analogue interface) or -30 dBFS (digital interface) when playing the fixed “programme simulation noise” described in EN 50332-1.		N/A
10.6.3.3	RS2 limits (new) RS2 is a class 2 acoustic energy source that does not exceed the following: – for equipment provided as a package (player with its listening device), and with a proprietary connector between the player and its listening device, or where the combination of player and listening device is known by other means such as setting or automatic detection, the weekly sound exposure level, as described in EN 50332-3, shall be ≤ 80 dB when playing the fixed “programme simulation noise” described in EN 50332-1. – for equipment provided with a standardized connector (for example, a 3,5 phone jack) that allows connection to a listening device for general use, the unweighted r.m.s. output level, integrated over one week, as described in EN50332-3, shall be ≤ 15 mV (analogue interface) or -30 dBFS (digital interface) when playing the fixed “programme simulation noise” described in EN 50332-1.		N/A

Attachment No. 1

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
10.6.4	Requirements for maximum sound exposure		N/A
10.6.4.1	Measurement methods All volume controls shall be turned to maximum during tests. Measurements shall be made in accordance with EN 50332-1 or EN 50332-2 as applicable.		N/A
10.6.4.2	Protection of persons Except as given below, protection requirements for parts accessible to ordinary persons, instructed persons and skilled persons are given in 4.3. NOTE 1 Volume control is not considered a safeguard . Between RS2 and an ordinary person , the basic safeguard may be replaced by an instructional safeguard in accordance with Clause F.5, except that the instructional safeguard shall be placed on the equipment, or on the packaging, or in the instruction manual. Alternatively, the instructional safeguard may be given through the equipment display during use. The elements of the instructional safeguard shall be as follows:  – element 1a: the symbol , IEC 60417-6044 (2011-01) – element 2: “High sound pressure” or equivalent wording – element 3: “Hearing damage risk” or equivalent wording – element 4: “Do not listen at high volume levels for long periods.” or equivalent wording An equipment safeguard shall prevent exposure of an ordinary person to an RS2 source without intentional physical action from the ordinary person and shall automatically return to an output level not exceeding what is specified for an RS1 source when the power is switched off. The equipment shall provide a means to actively inform the user of the increased sound level when the equipment is operated with an output exceeding RS1. Any means used shall be acknowledged by the user before activating a mode of operation which allows for an output exceeding RS1. The acknowledgement does not need to be repeated more than once every 20 h of cumulative listening time.		N/A

Attachment No. 1

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
	NOTE 2 Examples of means include visual or audible signals. Action from the user is always needed. NOTE 3 The 20 h listening time is the accumulative listening time, independent of how often and how long the personal music player has been switched off. A skilled person shall not be unintentionally exposed to RS3.		
10.6.5	Requirements for dose-based systems		N/A
10.6.5.1	General requirements Personal music players shall give the warnings as provided below when tested according to EN 50332-3, using the limits from this clause. The manufacturer may offer optional settings to allow the users to modify when and how they wish to receive the notifications and warnings to promote a better user experience without defeating the safeguards. This allows the users to be informed in a method that best meets their physical capabilities and device usage needs. If such optional settings are offered, an administrator (for example, parental restrictions, business/educational administrators, etc.) shall be able to lock any optional settings into a specific configuration. The personal music player shall be supplied with easy to understand explanation to the user of the dose management system, the risks involved, and how to use the system safely. The user shall be made aware that other sources may significantly contribute to their sound exposure, for example work, transportation, concerts, clubs, cinema, car races, etc.		N/A
10.6.5.2	Dose-based warning and requirements When a dose of 100 % CSD is reached, and at least at every 100 % further increase of CSD, the device shall warn the user and require an acknowledgement. In case the user does not acknowledge, the output level shall automatically decrease to compliance with class RS1. The warning shall at least clearly indicate that listening above 100 % CSD leads to the risk of hearing damage or loss.		N/A
10.6.5.3	Exposure-based requirements With only dose-based requirements, cause and effect could be far separated in time, defying the purpose of educating users about safe listening practice. In addition to dose-based requirements,		N/A

Attachment No. 1

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
	a PMP shall therefore also put a limit to the short-term sound level a user can listen at. The exposure-based limiter (EL) shall automatically reduce the sound level not to exceed 100 dB(A) or 150 mV integrated over the past 180 s, based on methodology defined in EN 50332-3. The EL settling time (time from starting level reduction to reaching target output) shall be 10 s or faster. Test of EL functionality is conducted according to EN 50332-3, using the limits from this clause. For equipment provided as a package (player with its listening device), the level integrated over 180 s shall be 100 dB or lower. For equipment provided with a standardized connector, the unweighted level integrated over 180 s shall be no more than 150 mV for an analogue interface and no more than -10 dBFS for a digital interface. NOTE In case the source is known not to be music (or test signal), the EL may be disabled.		
10.6.6	Requirements for listening devices (headphones, earphones, etc.)		N/A
10.6.6.1	Corded listening devices with analogue input With 94 dB L_{Aeq} acoustic pressure output of the listening device, and with the volume and sound settings in the listening device (for example, built-in volume level control, additional sound features like equalization, etc.) set to the combination of positions that maximize the measured acoustic output, the input voltage of the listening device when playing the fixed “programme simulation noise” as described in EN 50332-1 shall be ≥ 75 mV. NOTE The values of 94 dB and 75 mV correspond with 85 dB and 27 mV or 100 dB and 150 mV.		N/A
10.6.6.2	Corded listening devices with digital input With any playing device playing the fixed “programme simulation noise” described in EN 50332-1, and with the volume and sound settings in the listening device (for example, built-in volume level control, additional sound features like equalization, etc.) set to the combination of positions that maximize the measured acoustic output, the $L_{Aeq,T}$ acoustic output of the listening device shall be ≤ 100 dB with an input signal of -10 dBFS.		N/A

Attachment No. 1

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
10.6.6.3	Cordless listening devices In cordless mode, – with any playing and transmitting device playing the fixed programme simulation noise described in EN 50332-1; and – respecting the cordless transmission standards, where an air interface standard exists that specifies the equivalent acoustic level; and – with volume and sound settings in the receiving device (for example, built-in volume level control, additional sound features like equalization, etc.) set to the combination of positions that maximize the measured acoustic output for the above mentioned programme simulation noise, the $L_{Aeq,T}$ acoustic output of the listening device shall be ≤ 100 dB with an input signal of -10 dBFS.		N/A
10.6.6.4	Measurement method <i>Measurements shall be made in accordance with EN 50332-2 as applicable.</i>		N/A

Attachment No. 1

IEC 62368-1						
Clause	Requirement + Test			Result - Remark		Verdict
3	Modification to the whole document					
	Delete all the “country” notes in the reference document according to the following list:					N/A
	0.2.1	Note 1 and 2	1	Note 4 and 5	3.3.8.1	Note 2
	3.3.8.3	Note 1	4.1.15	Note	4.7.3	Note 1 and 2
	5.2.2.2	Note	5.4.2.3.2.2 Table 12	Note c	5.4.2.3.2.4	Note 1 and 3
	5.4.2.3.2.4 Table 13	Note 2	5.4.2.5	Note 2	5.4.5.1	Note
	5.4.10.2.1	Note	5.4.10.2.2	Note	5.4.10.2.3	Note
	5.5.2.1	Note	5.5.6	Note	5.6.4.2.1	Note 2 and 3 and 4
	5.6.8	Note 2	5.7.6	Note	5.7.7.1	Note 1 and Note 2
	8.5.4.2.3	Note	10.2.1 Table 39	Note 3 and 4 and 5	10.5.3	Note 2
	~~10.6.1~~	Note 3	F.3.3.6	Note 3	Y.4.1	Note
	Y.4.5	Note				
4	Modification to Clause 1					
1	Add the following note: NOTE Z1 The use of certain substances in electrical and electronic equipment is restricted within the EU: see Directive 2011/65/EU.					N/A
5	Modification to 4.Z1					
4.Z1	Add the following new subclause after 4.9: To protect against excessive current, short-circuits and earth faults in circuits connected to an a.c. mains, protective devices shall be included either as integral parts of the equipment or as parts of the building installation, subject to the following, a), b) and c): a) except as detailed in b) and c), protective devices necessary to comply with the requirements of B.3.1 and B.4 shall be included as parts of the equipment; b) for components in series with the mains input to the equipment such as the supply cord, appliance coupler, r.f.i. filter and switch, short-circuit and earth fault protection may be provided by protective					P

Attachment No. 1

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
	devices in the building installation; c) it is permitted for pluggable equipment type B or permanently connected equipment, to rely on dedicated overcurrent and short-circuit protection in the building installation, provided that the means of protection, e.g. fuses or circuit breakers, is fully specified in the installation instructions. If reliance is placed on protection in the building installation, the installation instructions shall so state, except that for pluggable equipment type A the building installation shall be regarded as providing protection in accordance with the rating of the wall socket outlet.		
6	Modification to 5.4.2.3.2.4		
5.4.2.3.2.4	Add the following to the end of this subclause: The requirement for interconnection with external circuit is in addition given in EN 50491-3:2009.		N/A
7	Modification to 10.2.1		
10.2.1	Add the following to ^{c)} and ^{d)} in table 39: For additional requirements, see 10.5.1.		N/A
8	Modification to 10.5.1		
10.5.1	Add the following after the first paragraph: For RS 1 compliance is checked by measurement under the following conditions: In addition to the normal operating conditions, all controls adjustable from the outside by hand, by any object such as a tool or a coin, and those internal adjustments or pre-sets which are not locked in a reliable manner, are adjusted so as to give maximum radiation whilst maintaining an intelligible picture for 1 h, at the end of which the measurement is made. NOTE Z1 Soldered joints and paint lockings are examples of adequate locking. The dose-rate is determined by means of a radiation monitor with an effective area of 10 cm², at any point 10 cm from the outer surface of the apparatus. Moreover, the measurement shall be made under fault conditions causing an increase of the high voltage, provided an intelligible picture is maintained for 1 h, at the end of which the measurement is made.		N/A

Attachment No. 1

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
	For RS1, the dose-rate shall not exceed 1 μ Sv/h taking account of the background level. NOTE Z2 These values appear in Directive 96/29/Euratom of 13 May 1996.		
9	Modification to G.7.1		
G.7.1	Add the following note: NOTE Z1 The harmonized code designations corresponding to the IEC cord types are given in Annex ZD.	The suitable certified power supply cordset shall be assessed to the national standard.	N/A
10	Modification to Bibliography		
	Add the following notes for the standards indicated: IEC 60130-9 NOTE Harmonized as EN 60130-9. IEC 60269-2 NOTE Harmonized as HD 60269-2. IEC 60309-1 NOTE Harmonized as EN 60309-1. IEC 60364 NOTE some parts harmonized in HD 384/HD 60364 series. IEC 60601-2-4 NOTE Harmonized as EN 60601-2-4. IEC 60664-5 NOTE Harmonized as EN 60664-5. IEC 61032:1997 NOTE Harmonized as EN 61032:1998 (not modified). IEC 61508-1 NOTE Harmonized as EN 61508-1. IEC 61558-2-1 NOTE Harmonized as EN 61558-2-1. IEC 61558-2-4 NOTE Harmonized as EN 61558-2-4. IEC 61558-2-6 NOTE Harmonized as EN 61558-2-6. IEC 61643-1 NOTE Harmonized as EN 61643-1. IEC 61643-21 NOTE Harmonized as EN 61643-21. IEC 61643-311 NOTE Harmonized as EN 61643-311. IEC 61643-321 NOTE Harmonized as EN 61643-321. IEC 61643-331 NOTE Harmonized as EN 61643-331.		N/A
11	ADDITION OF ANNEXES		
ZB	ANNEX ZB, SPECIAL NATIONAL CONDITIONS (EN)		N/A

Attachment No. 1

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
4.1.15	Denmark, Finland, Norway and Sweden To the end of the subclause the following is added: Class I pluggable equipment type A intended for connection to other equipment or a network shall, if safety relies on connection to reliable earthing or if surge suppressors are connected between the network terminals and accessible parts, have a marking stating that the equipment shall be connected to an earthed mains socket-outlet. The marking text in the applicable countries shall be as follows: In Denmark: "Apparatets stikprop skal tilsluttes en stikkontakt med jord som giver forbindelse til stikproppens jord." In Finland: "Laite on liitettävä suojakoskettimilla varustettuun pistorasiaan" In Norway: "Apparatet må tilkoples jordet stikkontakt" In Sweden: "Apparaten skall anslutas till jordat uttag"		P
4.7.3	United Kingdom To the end of the subclause the following is added: The torque test is performed using a socket-outlet complying with BS 1363, and the plug part shall be assessed to the relevant clauses of BS 1363. Also see Annex G.4.2 of this annex		N/A
5.2.2.2	Denmark After the 2nd paragraph add the following: A warning (marking safeguard) for high touch current is required if the touch current exceeds the limits of 3,5 mA a.c. or 10 mA d.c.		N/A
5.4.11.1 and Annex G	Finland and Sweden To the end of the subclause the following is added: For separation of the telecommunication network from earth the following is applicable: If this insulation is solid, including insulation forming part of a component, it shall at least consist of either • two layers of thin sheet material, each of which shall pass the electric strength test below, or • one layer having a distance through insulation of at least 0,4 mm, which shall pass the electric strength test below.		N/A

Attachment No. 1

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
	If this insulation forms part of a semiconductor component (e.g. an optocoupler), there is no distance through insulation requirement for the insulation consisting of an insulating compound completely filling the casing, so that clearances and creepage distances do not exist, if the component passes the electric strength test in accordance with the compliance clause below and in addition • passes the tests and inspection criteria of 5.4.8 with an electric strength test of 1,5 kV multiplied by 1,6 (the electric strength test of 5.4.9 shall be performed using 1,5 kV), and • is subject to routine testing for electric strength during manufacturing, using a test voltage of 1,5 kV. It is permitted to bridge this insulation with a capacitor complying with EN 60384-14:2005, subclass Y2. A capacitor classified Y3 according to EN 60384-14:2005, may bridge this insulation under the following conditions: • the insulation requirements are satisfied by having a capacitor classified Y3 as defined by EN 60384-14, which in addition to the Y3 testing, is tested with an impulse test of 2,5 kV defined in 5.4.11; • the additional testing shall be performed on all the test specimens as described in EN 60384-14; the impulse test of 2,5 kV is to be performed before the endurance test in EN 60384-14, in the sequence of tests as described in EN 60384-14.		
5.5.2.1	Norway After the 3rd paragraph the following is added: Due to the IT power system used, capacitors are required to be rated for the applicable line-to-line voltage (230 V).		N/A

Attachment No. 1

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
5.5.6	Finland, Norway and Sweden To the end of the subclause the following is added: Resistors used as basic safeguard or bridging basic insulation in class I pluggable equipment type A shall comply with G.10.1 and the test of G.10.2.		N/A
5.6.1	Denmark Add to the end of the subclause Due to many existing installations where the socket-outlets can be protected with fuses with higher rating than the rating of the socket-outlets the protection for pluggable equipment type A shall be an integral part of the equipment. <i>Justification:</i> In Denmark an existing 13 A socket outlet can be protected by a 20 A fuse.		N/A
5.6.4.2.1	Ireland and United Kingdom After the indent for pluggable equipment type A, the following is added: – the protective current rating is taken to be 13 A, this being the largest rating of fuse used in the mains plug.		P
5.6.4.2.1	France After the indent for pluggable equipment type A, the following is added: – in certain cases, the protective current rating of the circuit supplied from the mains is taken as 20 A instead of 16 A.		N/A
5.6.5.1	To the second paragraph the following is added: The range of conductor sizes of flexible cords to be accepted by terminals for equipment with a rated current over 10 A and up to and including 13 A is: 1,25 mm² to 1,5 mm² in cross-sectional area.		N/A
5.6.8	Norway To the end of the subclause the following is added: Equipment connected with an earthed mains plug is classified as class I equipment. See the Norway marking requirement in 4.1.15. The symbol IEC 60417-6092, as specified in F.3.6.2, is accepted.		N/A

Attachment No. 1

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
5.7.6	Denmark To the end of the subclause the following is added: The installation instruction shall be affixed to the equipment if the protective conductor current exceeds the limits of 3,5 mA a.c. or 10 mA d.c.		N/A
5.7.6.2	Denmark To the end of the subclause the following is added: The warning (marking safeguard) for high touch current is required if the touch current or the protective current exceed the limits of 3,5 mA .		N/A
5.7.7.1	Norway and Sweden To the end of the subclause the following is added: The screen of the television distribution system is normally not earthed at the entrance of the building and there is normally no equipotential bonding system within the building. Therefore the protective earthing of the building installation needs to be isolated from the screen of a cable distribution system. It is however accepted to provide the insulation external to the equipment by an adapter or an interconnection cable with galvanic isolator, which may be provided by a retailer, for example. The user manual shall then have the following or similar information in Norwegian and Swedish language respectively, depending on in what country the equipment is intended to be used in: “Apparatus connected to the protective earthing of the building installation through the mains connection or through other apparatus with a connection to protective earthing – and to a television distribution system using coaxial cable, may in some circumstances create a fire hazard. Connection to a television distribution system therefore has to be provided through a device providing electrical isolation below a certain frequency range (galvanic isolator, see EN 60728-11)” NOTE In Norway, due to regulation for CATV-installations, and in Sweden, a galvanic isolator shall provide electrical insulation below 5 MHz. The insulation shall withstand a dielectric strength of 1,5 kV r.m.s., 50 Hz or 60 Hz, for 1 min. Translation to Norwegian (the Swedish text will also be accepted in Norway):		N/A

Attachment No. 1

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
	“Apparater som er koplet til beskyttelsesjord via nettplugg og/eller via annet jordtilkoplet utstyr – og er tilkoplet et koaksialbasert kabel-TV nett, kan forårsake brannfare. For å unngå dette skal det ved tilkopling av apparater til kabel-TV nett installeres en galvanisk isolator mellom apparatet og kabel-TV nettet.” Translation to Swedish: ”Apparater som är kopplad till skyddsjord via jordat vägguttag och/eller via annan utrustning och samtidigt är kopplad till kabel-TV nät kan i vissa fall medföra risk för brand. För att undvika detta skall vid anslutning av apparaten till kabel-TV nät galvanisk isolator finnas mellan apparaten och kabel-TV nätet.”.		
8.5.4.2.3	United Kingdom Add the following after the 2nd dash bullet in 3rd paragraph: An emergency stop system complying with the requirements of IEC 60204-1 and ISO 13850 is required where there is a risk of personal injury.		N/A
B.3.1 and B.4	Ireland and United Kingdom The following is applicable: To protect against excessive currents and short-circuits in the primary circuit of direct plug-in equipment, tests according to Annexes B.3.1 and B.4 shall be conducted using an external miniature circuit breaker complying with EN 60898-1, Type B, rated 32A. If the equipment does not pass these tests, suitable protective devices shall be included as an integral part of the direct plug-in equipment, until the requirements of Annexes B.3.1 and B.4 are met		N/A
G.4.2	Denmark To the end of the subclause the following is added: Supply cords of single phase appliances having a rated current not exceeding 13 A shall be provided with a plug according to DS 60884-2-D1:2011. CLASS I EQUIPMENT provided with socket-outlets with earth contacts or which are intended to be used in locations where protection against indirect contact is required according to the wiring rules shall be provided with a plug in accordance with standard sheet DK 2-1a or DK 2-5a.		N/A

Attachment No. 1

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
	If a single-phase equipment having a RATED CURRENT exceeding 13 A or if a polyphase equipment is provided with a supply cord with a plug, this plug shall be in accordance with the standard sheets DK 6-1a in DS 60884-2-D1 or EN 60309-2. Mains socket outlets intended for providing power to Class II apparatus with a rated current of 2,5 A shall be in accordance DS 60884-2-D1:2011 standard sheet DKA 1-4a. Other current rating socket outlets shall be in compliance with Standard Sheet DKA 1-3a or DKA 1-1c. Mains socket-outlets with earth shall be in compliance with DS 60884-2-D1:2011 Standard Sheet DK 1-3a, DK 1-1c, DK1-1d, DK 1-5a or DK 1-7a <i>Justification:</i> Heavy Current Regulations, Section 6c		
G.4.2	United Kingdom To the end of the subclause the following is added: The plug part of direct plug-in equipment shall be assessed to BS 1363: Part 1, 12.1, 12.2, 12.3, 12.9, 12.11, 12.12, 12.13, 12.16, and 12.17, except that the test of 12.17 is performed at not less than 125 °C. Where the metal earth pin is replaced by an Insulated Shutter Opening Device (ISOD), the requirements of clauses 22.2 and 23 also apply.		N/A
G.7.1	United Kingdom To the first paragraph the following is added: Equipment which is fitted with a flexible cable or cord and is designed to be connected to a mains socket conforming to BS 1363 by means of that flexible cable or cord shall be fitted with a 'standard plug' in accordance with the Plugs and Sockets etc. (Safety) Regulations 1994, Statutory Instrument 1994 No. 1768, unless exempted by those regulations. NOTE "Standard plug" is defined in SI 1768:1994 and essentially means an approved plug conforming to BS 1363 or an approved conversion plug.		N/A

Attachment No. 1

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
G.7.1	Ireland To the first paragraph the following is added: Apparatus which is fitted with a flexible cable or cord shall be provided with a plug in accordance with Statutory Instrument 525: 1997, "13 A Plugs and Conversion Adapters for Domestic Use Regulations: 1997. S.I. 525 provides for the recognition of a standard of another Member State which is equivalent to the relevant Irish Standard		N/A
G.7.2	Ireland and United Kingdom To the first paragraph the following is added: A power supply cord with a conductor of 1,25 mm ² is allowed for equipment which is rated over 10 A and up to and including 13 A.		N/A

Attachment No. 1

IEC 62368-1			
Clause	Requirement + Test	Result - Remark	Verdict
ZC	ANNEX ZC, NATIONAL DEVIATIONS (EN)		N/A
10.5.2	Germany The following requirement applies: For the operation of any cathode ray tube intended for the display of visual images operating at an acceleration voltage exceeding 40 kV, authorization is required, or application of type approval (Bauartzulassung) and marking. <i>Justification:</i> German ministerial decree against ionizing radiation (Röntgenverordnung), in force since 2002-07-01, implementing the European Directive 96/29/EURATOM. NOTE Contact address: Physikalisch-Technische Bundesanstalt, Bundesallee 100, D-38116 Braunschweig, Tel.: Int+49-531-592-6320, Internet: http://www.ptb.de		N/A

Attachment No. 1

IEC 62368-1																																																								
Clause	Requirement + Test	Result - Remark	Verdict																																																					
ZD	IEC and CENELEC CODE DESIGNATIONS FOR FLEXIBLE CORDS (EN)		N/A																																																					
	<table><tr><th rowspan="2">Type of flexible cord</th><th colspan="2">Code designations</th></tr><tr><th>IEC</th><th>CENELEC</th></tr><tr><td colspan="3">PVC insulated cords</td></tr><tr><td>Flat twin tinsel cord</td><td>60227 IEC 41</td><td>H03VH-Y</td></tr><tr><td>Light polyvinyl chloride sheathed flexible cord</td><td>60227 IEC 52</td><td>H03VV-F H03VVH2-F</td></tr><tr><td>Ordinary polyvinyl chloride sheathed flexible cord</td><td>60227 IEC 53</td><td>H05VV-F H05VVH2-F</td></tr><tr><td colspan="3">Rubber insulated cords</td></tr><tr><td>Braided cord</td><td>60245 IEC 51</td><td>H03RT-F</td></tr><tr><td>Ordinary tough rubber sheathed flexible cord</td><td>60245 IEC 53</td><td>H05RR-F</td></tr><tr><td>Ordinary polychloroprene sheathed flexible cord</td><td>60245 IEC 57</td><td>H05RN-F</td></tr><tr><td>Heavy polychloroprene sheathed flexible cord</td><td>60245 IEC 66</td><td>H07RN-F</td></tr><tr><td colspan="3">Cords having high flexibility</td></tr><tr><td>Rubber insulated and sheathed cord</td><td>60245 IEC 86</td><td>H03RR-H</td></tr><tr><td>Rubber insulated, crosslinked PVC sheathed cord</td><td>60245 IEC 87</td><td>H03RV4-H</td></tr><tr><td>Crosslinked PVC insulated and sheathed cord</td><td>60245 IEC 88</td><td>H03V4V4-H</td></tr><tr><td colspan="3">Cords insulated and sheathed with halogen-free thermoplastic compounds</td></tr><tr><td>Light halogen-free thermoplastic insulated and sheathed flexible cords</td><td></td><td>H03Z1Z1-F H03Z1Z1H2-F</td></tr><tr><td>Ordinary halogen-free thermoplastic insulated and sheathed flexible cords</td><td></td><td>H05Z1Z1-F H05Z1Z1H2-F</td></tr></table>		Type of flexible cord	Code designations		IEC	CENELEC	PVC insulated cords			Flat twin tinsel cord	60227 IEC 41	H03VH-Y	Light polyvinyl chloride sheathed flexible cord	60227 IEC 52	H03VV-F H03VVH2-F	Ordinary polyvinyl chloride sheathed flexible cord	60227 IEC 53	H05VV-F H05VVH2-F	Rubber insulated cords			Braided cord	60245 IEC 51	H03RT-F	Ordinary tough rubber sheathed flexible cord	60245 IEC 53	H05RR-F	Ordinary polychloroprene sheathed flexible cord	60245 IEC 57	H05RN-F	Heavy polychloroprene sheathed flexible cord	60245 IEC 66	H07RN-F	Cords having high flexibility			Rubber insulated and sheathed cord	60245 IEC 86	H03RR-H	Rubber insulated, crosslinked PVC sheathed cord	60245 IEC 87	H03RV4-H	Crosslinked PVC insulated and sheathed cord	60245 IEC 88	H03V4V4-H	Cords insulated and sheathed with halogen-free thermoplastic compounds			Light halogen-free thermoplastic insulated and sheathed flexible cords		H03Z1Z1-F H03Z1Z1H2-F	Ordinary halogen-free thermoplastic insulated and sheathed flexible cords		H05Z1Z1-F H05Z1Z1H2-F	N/A
Type of flexible cord	Code designations																																																							
	IEC	CENELEC																																																						
PVC insulated cords																																																								
Flat twin tinsel cord	60227 IEC 41	H03VH-Y																																																						
Light polyvinyl chloride sheathed flexible cord	60227 IEC 52	H03VV-F H03VVH2-F																																																						
Ordinary polyvinyl chloride sheathed flexible cord	60227 IEC 53	H05VV-F H05VVH2-F																																																						
Rubber insulated cords																																																								
Braided cord	60245 IEC 51	H03RT-F																																																						
Ordinary tough rubber sheathed flexible cord	60245 IEC 53	H05RR-F																																																						
Ordinary polychloroprene sheathed flexible cord	60245 IEC 57	H05RN-F																																																						
Heavy polychloroprene sheathed flexible cord	60245 IEC 66	H07RN-F																																																						
Cords having high flexibility																																																								
Rubber insulated and sheathed cord	60245 IEC 86	H03RR-H																																																						
Rubber insulated, crosslinked PVC sheathed cord	60245 IEC 87	H03RV4-H																																																						
Crosslinked PVC insulated and sheathed cord	60245 IEC 88	H03V4V4-H																																																						
Cords insulated and sheathed with halogen-free thermoplastic compounds																																																								
Light halogen-free thermoplastic insulated and sheathed flexible cords		H03Z1Z1-F H03Z1Z1H2-F																																																						
Ordinary halogen-free thermoplastic insulated and sheathed flexible cords		H05Z1Z1-F H05Z1Z1H2-F																																																						

Attachment No. 2

National and Group Differences for IEC 62368-1:2018 (Third Edition) as per CB Bulletin

National Differences covered by this report					
Country	CENELEC Group differ. (see separate attachment)	National differ.	Base standard	National standard	Tested
AR Argentina	-	Yes	IEC 62368-1 ed3	-	Yes
AU Australia	-	Yes	IEC 62368-1 ed3	AS/NZS 62368.1:2022	Yes
AT Austria	Yes	-	IEC 62368-1 ed3	-	Yes
BY Belarus	-	-	IEC 62368-1 ed3	-	Yes
BE Belgium	Yes	-	IEC 62368-1 ed3	-	Yes
CA Canada	-	Yes	IEC 62368-1 ed3	CSA/UL 62368-1:2019	Yes
CH Switzerland	Yes	-	IEC 62368-1 ed3	-	Yes
CN China	-	-	IEC 62368-1 ed3	GB 4943.1-2022	Yes
DE Germany	Yes	-	IEC 62368-1 ed3	EN IEC 62368-1:2020+ A11:2020	Yes
DK Denmark	Yes	-	IEC 62368-1 ed3	DS/EN IEC 62368-1:2020+ A11:2020	Yes
FI Finland	Yes	-	IEC 62368-1 ed3	-	Yes
FR France	Yes	-	IEC 62368-1 ed3	EN IEC 62368-1:2020+ A11:2020	Yes
GB United Kingdom	Yes	-	IEC 62368-1 ed3	-	Yes
HU Hungary	Yes	-	IEC 62368-1 ed3	-	Yes
IT Italy	Yes	-	IEC 62368-1 ed3	-	Yes
IL Israel	-	-	IEC 62368-1 ed3	-	Yes
JP Japan	-	-	IEC 62368-1 ed3	J62368-1(2023), J3000(H25)	Yes
KR Korea	-	Yes	IEC 62368-1 ed3	KC 62368-1(2021-08)	Yes
MY Malaysia	-	-	IEC 62368-1 ed3	-	Yes
NO Norway	Yes	-	IEC 62368-1 ed3	-	No
NL Netherlands	Yes	-	IEC 62368-1 ed3	-	Yes
NZ New Zealand	-	Yes	IEC 62368-1 ed3	AS/NZS 62368.1:2022	Yes
SA Saudi Arabia	-	Yes	IEC 62368-1 ed3	SASO-IEC 62368-1:2020	Yes
SE Sweden	Yes	-	IEC 62368-1 ed3	-	Yes
SG Singapore	-	Yes	IEC 62368-1 ed3	-	Yes
SI Slovenia	Yes	-	IEC 62368-1 ed3	-	Yes
UA Ukraine	-	-	IEC 62368-1 ed3	-	Yes
US United States of America	-	Yes	IEC 62368-1 ed3	CSA/UL 62368-1:2019	Yes

Attachment No. 2

General remarks:

The test results presented in this report relate only to the object tested.

This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.

Throughout this report a point is used as the decimal separator.

See attachment 1 for European Group Differences and National Differences.

Notes: Before placing the products in the different countries, the manufacturer must ensure that:


1. Operating Instructions, Ratings Labels and Warnings Labels written in an Accepted or Official Language of the county in question.
2. The equipment complies with the National Standards and/or Electrical Codes of the country in question.
3. Mains plugs and internal wirings should be assessed to the national standard. (if necessary)
4. The power supply cordset of equipment should be assessed when submitted to national approval. (if necessary)
5. UL 62368-1:2019/R:2021-10 and CSA C22.2 No. 62368-1:2019/U1:2021-10 are also considered in this attachment.

Possible test case verdicts:

- | | |
|---|----------|
| - test case does not apply to the test object | N/A |
| - test object does meet the requirement | P (Pass) |
| - test object does not meet the requirement | F (Fail) |


Attachment No. 2



IEC 62368_1E ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
ATTACHMENT TO TEST REPORT IEC 62368-1 ARGENTINA NATIONAL DIFFERENCES Audio/video, information and communication technology equipment - Part 1: Safety requirements			
Differences according to: Special National Conditions			
TRF template used:: IECEE OD-2020-F3:2022, Ed. 1.2			
Attachment Form No.....: AR_ND_IEC62368_1_A			
Attachment Originator: IRAM – Instituto Argentino de Normalización y Certificación			
Master Attachment: 2024-06-06			
Copyright © 2022 IEC System for Conformity Testing and Certification of Electrical Equipment (IECEE), Geneva, Switzerland. All rights reserved.			
	National Differences		--
	Not applicable		--
	Special national conditions (if any)		--
	- Appliances other than SELV, ratings shall cover 220 VAC - 50 Hz or 3x380 VAC – 50 Hz	100V-240VAC, 50Hz/60Hz	P
	- Class 0 and Class 0I appliances are not allowed	Class I apparatus	N/A
	- Safety instructions and manuals shall be written in Spanish language	Should be evaluated during the national approval	N/A
	- Country of origin shall be shown on the marking plate	Marked on marking plate	P
	- Class I appliances provided with plugs shall be provided with the label specified in sheet "Class I" IMPORTANTE PARA EL USUARIO Los aparatos de la Clase I, poseen ficha de 3 espigas planas con toma de tierra, para aumentar su seguridad.  NO LA ELIMINE colocando un adaptador o reemplazando la ficha por otra de 2 espigas. PARA SU SEGURIDAD, su instalación debe estar provista de conductor de tierra. De no ser así, realice la adecuación con personal especializado.	Should be evaluated during the national approval	N/A

Attachment No. 2



IEC 62368_1E ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
	- Class II appliances provided with plugs shall be provided with the label specified in sheet "Class II" IMPORTANTE PARA EL USUARIO Los aparatos de la Clase II, que se identifican con el símbolo  poseen ficha de 2 espigas planas sin toma de tierra, pues poseen doble aislación o aislación reforzada en todas sus partes.  NO LA ELIMINE colocando un adaptador o reemplazando la ficha por otra de 2 espigas cilíndricas, ya que la misma es compatible con los tomacorrientes con toma de tierra. PARA SU SEGURIDAD, su instalación debe estar provista de conductor de tierra. De no ser así, realice la adecuación con personal especializado.		N/A
	- Plugs shall be in conformity with IRAM 2063 Standard for Class II appliances and IRAM 2073 Standard for Class I appliances	Should be evaluated during the national approval	N/A
	- Appliances with detachable interchangeable plug pins must include with its products, written instructions to inform the customer about the type of interchangeable and detachable plug pins approved and suitable for use in Argentina.		N/A
	- Direct plug-in appliances or appliances provided with integrated plugs shall be according to geometry of IRAM 2063 standard for Class II appliances or IRAM 2073 standard for Class I appliances		N/A
	- Appliances with integrated socket outlet shall be according to geometry of IRAM 2071 standard.		N/A

Attachment No. 2



IEC 62368_1E ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
ATTACHMENT TO TEST REPORT IEC 62368-1 (AUSTRALIA / NEW ZEALAND) NATIONAL DIFFERENCES (Audio/video, information and communication technology equipment)			
Differences according to : AS/NZS 62368.1:2022			
TRF template used:.....: IECEE OD-2020-F3, Ed. 1.1			
Attachment Form No. : AU_NZ_ND_IEC62368_1E			
Attachment Originator..... : JAS-ANZ			
Master Attachment..... : 2025-07-07			
Copyright © 2020 IEC System for Conformity Testing and Certification of Electrical Equipment (IECEE), Geneva, Switzerland. All rights reserved.			
	National Differences		--
Appendix ZZ	Variations to IEC 62368-1:2018 (ED. 3.0) for Australia and New Zealand		P
ZZ1 Scope	This Appendix lists the normative variations to IEC 62368-1:2018 (ED. 3.0)		P
ZZ2 Variations	The following modifications are required for Australian/New Zealand conditions:		P
2	After the first paragraph, <i>add</i> the following: The Australian or Australian/New Zealand Standards listed below are modified adoptions of, or not equivalent to, the IEC normative references and are required for the application of this Standard. All references in the source text to those IEC normative references shall be replaced by references to the corresponding Australian or Australian/New Zealand Standards. Australian or Australian/New Zealand Standards that are identical adoptions of international normative references may be used interchangeably -AS/NZS 3112, <i>Approval and test specification—Plugs and socket-outlets</i> -AS/NZS 3123, <i>Approval and test specification—Plugs, socket-outlets and couplers for general industrial application</i> -AS/NZS 3191, <i>Electric flexible cords</i> -AS/NZS 60884.1, <i>Plugs and socket-outlets for household and similar purposes, Part 1: General requirements</i> -IEC 60086-2 <i>Primary batteries — Part 2: Physical and electrical specifications</i> -AS/NZS 60065, <i>Audio, video and similar electronic apparatus—Safety requirements (IEC 60065:2015 (ED.8.0) MOD)</i> -AS/NZS 60320.1, <i>Appliance couplers for household and similar general purposes, Part 1: General requirements (IEC 60320-1, Ed.2.1 (2007) MOD)</i>	Should be evaluated during the national approval	N/A

Attachment No. 2



IEC 62368_1E ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
	-AS/NZS 60320.2.2, <i>Appliance couplers for household and similar general purposes Part 2.2: Interconnection couplers for household and similar equipment (IEC 60320-2-2, Ed.2.0 (1998) MOD)</i> -AS/NZS 60695.2.11, <i>Fire hazard testing, Part 2.11: Glowing/hot wire based test methods—Glow-wire flammability test method for end-products</i> -AS/NZS 60695.11.5, <i>Fire hazard testing, Part 11.5: Test flames—Needle-flame test method—Apparatus, confirmatory test arrangement and guidance</i> -AS/NZS 60695.11.10, <i>Fire hazard testing, Part 11.10: Test flames—50 W horizontal and vertical flame test methods</i> -AS/NZS 60884.1, <i>Plugs and socket-outlets for household and similar purposes, Part 1: General requirements</i> -AS/NZS 60950.1, <i>Information technology equipment—Safety, Part 1: General requirements (IEC 60950-1, Ed.2.2 (2013), MOD)</i> IEC 61032:1997, <i>Protection of persons and equipment by enclosures—Probes for verification</i> -AS/NZS 61558.1, <i>Safety of Power Transformers, Power Supplies, Reactors and Similar Products, Part 1: General requirements and tests (IEC 61558-1 Ed 3, MOD)</i> -AS/NZS 61558.2.16, <i>Safety of transformers, reactors, power supply units and similar products for voltages up to 1 100 V, Part 2.16: Particular requirements and tests for switch mode power supply units and transformers for switch mode power supply units.</i>		
4.7.2	Requirements Delete the text of the second paragraph and replace with the following: Equipment with a plug portion, suitable for insertion into a 10 A 3-pin flat-pin socket-outlet conforming to AS/NZS 3112, shall conform to the requirements in AS/NZS 3112 for equipment with integral pins for insertion into socket-outlets. Conformity is checked by inspection and, if necessary, by the tests in AS/NZS 3112. NOTE: Equipment with plug portions for use in countries other than Australia and New Zealand will need to conform to other countries' requirements Note Additional AS/NZS 3112 Appendix J,TRF is appended to end of this TRF.		N/A
4.7.3	Compliance Criteria Delete this clause		N/A

Attachment No. 2



IEC 62368_1E ATTACHMENT						
Clause	Requirement + Test		Result - Remark		Verdict	
4.8.1	General After second list, <i>add</i> the following: NOTE: Refer to the Consumer Goods (Products Containing Button/Coin Batteries) Safety Standard 2020 and Consumer Goods (Products Containing Button/Coin Batteries) Information Standard 2020 for more information on button cell batteries in Australia..				N/A	
5.4.10.2.1	General <i>Delete</i> the first paragraph and <i>replace</i> with the following: In Australia, the separation is checked by the test given in both Clause 5.4.10.2.2 and Clause 5.4.10.2.3. In New Zealand, the separation is checked by the test given in either 5.4.10.2.2 or 5.4.10.2.3..				N/A	
Table 28	<i>Delete</i> Table 28 and <i>replace</i> with the following:				N/A	
Parts		Impulse test		Steady state test		
		New Zealand	Australia	New Zealand	Australia	
Parts indicated in Clause 5.4.10.1 a) ^a		2.5 kV	7.0 kV for hand-held telephones and headsets, 2.5 kV for other equipment.	1.5 kV	3 kV	
Parts indicated in Clause 5.4.10.1 b) and c) ^b		1.5 kV ^c		1.0 kV	1.5 kV	
^a Surge suppressors shall not be removed. ^b Surge suppressors may be removed, provided that such devices pass the impulse test of Clause 5.4.10.2.2 when tested as components outside the equipment. ^c During this test, it is allowed for a surge suppressor to operate and for a sparkover to occur in a GDT.						
5.4.10.2.2	<i>Delete</i> “NOTE” and <i>replace</i> with “NOTE 1”. After NOTE 1, <i>add</i> the following: NOTE 2: For Australia, the 7 kV impulse simulates lightning surges on typical rural and semi-rural network lines. NOTE 3: For Australia, the value of 2.5 kV for Clause 5.4.10.1 a) was chosen to ensure the adequacy of the insulation concerned and does not necessarily simulate likely overvoltages.				N/A	
5.4.10.2.3	<i>Delete</i> “NOTE” and <i>replace</i> with “NOTE 1”. After NOTE 1, <i>add</i> the following: NOTE 2: For Australia, where there are capacitors across the insulation under test, it is recommended that d.c. test voltages are used. NOTE 3: The 3 kV and 1.5 kV values for Australia have been determined considering the low frequency induced voltages from the power supply distribution system.				N/A	

Attachment No. 2



IEC 62368_1E ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
6	Electrically-caused fire		P
6.6	After Clause 6.6, <i>add</i> the new Clauses 6.201 as follows: 6.201 External power supplies, docking stations and other similar devices (see special national conditions)		P
8.6	Stability of equipment		N/A
Table 36	Footnote ^a , after first sentence, <i>add</i> the following: Equipment having displays with moving images shall include "television sets and display devices".		N/A
8.6.1	After Clause 8.6.1 <i>add</i> the following new clauses: 8.6.201 Restraining Device fixing point (see special national conditions) 8.6.202 Restraining device (see special national conditions)		N/A
Annex F Paragraph F.3.3.4	Rated Voltage <i>Delete</i> "NOTE" and <i>replace</i> with NOTE1" After NOTE 1, <i>add</i> the following Equipment that is intended for connection to the supply mains in Australia and New Zealand shall be marked with: (a) A rated voltage of: • 230 V for single phase equipment • 400 V for poly phase equipment Or (b) A rated voltage range that includes: • 230 V for single phase equipment • 400 V for poly phase equipment NOTE 2: equipment that is not rated as above is not suitable for direct connection to the supply mains in Australia or new Zealand.		P
Annex F.3.3.5	After the list, <i>add</i> the following Equipment that is intended for connection to supply mains in Australia or New Zealand shall be marked with a rated frequency of 50 Hz or a rated frequency range or nominal value which includes 50Hz		P
Annex F.3.8	After "The DC output of an external power supply", insert "or docking stations and other similar external devices"		P
Annex G Paragraph G.4.2	Mains connectors 1 After "IEC 60320", insert "or AS/NZS 60320 series". 2 After "IEC 60906-1", insert "or AS/NZS 3123" 3 <i>After</i> first paragraph <i>add</i> the following: 10 A or 15 A 250 V flat pin plugs for the connection of equipment to mains-powered socket-outlets for household or similar general use shall comply with AS/NZS 3112 or AS/NZS 60884.1.	Should be evaluated during the national approval	N/A

Attachment No. 2



IEC 62368_1E ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
Paragraph G.5.3.1	Transformers, General 1 Third dashed point <i>replace</i> 'IEC 61558-1 and the relevant parts of IEC 61558-2' with 'AS/NZS 61558-1 and the relevant parts of AS/NZS 61558.2' 2 Fourth dashed point <i>replace</i> 'IEC 61558-2-16' with 'AS/NZS 61558.2.16'.		N/A
Annex G.7.1	Mains supply cords, General Fourth dashed paragraph, <i>replace</i> 'IEC 60320-1' with 'AS/NZS 60320.1'	Should be evaluated during the national approval	N/A
Table G.7	Sizes of conductors 1 First column, second row, <i>delete</i> "6" and <i>replace</i> with "7.5" 2 Second column, second row, <i>delete</i> '0,75' and <i>replace</i> with '0.75' ^b 3 <i>Delete</i> NOTE 1. 4 <i>Replace</i> 'NOTE 2' with 'NOTE:'. 5 <i>Delete</i> 'Footnote b' and <i>replace</i> with the following: ^b This nominal cross-sectional area is only allowed for Class II appliances if the length of the power supply cord, measured between the point where the cord, or cord guard, enters the appliance, and the entry to the plug does not exceed 2 m (0.5 mm ² three-core supply flexible cords are not permitted; see AS/NZS 3191). 6 Footnote c <i>replace</i> 'IEC 60320-1' with 'AS/NZS 60320.1' 7 Footnote d <i>replace</i> 'IEC 60320-1' with 'AS/NZS 60320.1'	Should be evaluated during the national approval	N/A
Annex M M 2.1	<i>Add</i> "IEC 60086-2" to the list		N/A
Annex M Paragraph M.3.2	Test method Delete "NOTE" and replace with "NOTE 1" After NOTE 1 <i>add</i> the following: NOTE 2: In cases where the voltage source is provided by power from an unassociated power source, consideration should be given to the effects of possible single fault conditions in the unassociated equipment. If the power source is unknown then it should be assumed that the maximum limit of ES1 may be applied to the source input under assumed single fault conditions in the source when assessing the charging circuit in the equipment under test.		N/A
	Special national conditions (if any)		P

Attachment No. 2



IEC 62368_1E ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
6.201	External power supplies, docking stations and other similar devices For external power supplies, docking stations and other similar devices, during and after abnormal operating conditions and during single fault conditions the output voltage— (a) at all ES1 outlets or connectors shall not increase by more than 10 % of the output rated voltage under normal operating conditions, measured after 3 s of introducing a single fault condition and after 3 s of introducing abnormal operating conditions; and (b) of a USB outlet or connector shall not increase by more than 3 V or 10 % of the output rated voltage under normal operating conditions, whichever is higher, measured after 3 seconds of introducing a single fault condition and after 3 s of introducing abnormal operating conditions For equipment with multiple rated voltages at the output, the requirements apply with the equipment configured for each output rated voltage in turn NOTE: This is intended to reduce the possibility of battery fire or explosion in attached equipment or accessories when charging secondary lithium batteries. The 3 s measurement delay is based on IEC document 108/742/INF, <i>TC 108, Standards Interpretation Panel Question 15 — Output voltage</i>, in relation to similar requirements in IEC 62368-3:2017. Conformity shall be checked by measurement, taking into account the abnormal operating conditions of Annex B.3 and the simulated single fault conditions of Annex B.4.		P
8.6.201	Restraining device fixing point Freestanding-capable MS2 and MS3 television sets and display devices shall be provided with a fixing point to facilitate the anchoring of the equipment from toppling The fixing point shall conform to Clause 8.7 where the fixing point uses a wall, ceiling or other structure mount. Alternatively, the fixing point shall be capable of withstanding a pull equal to the mass of the equipment in all directions without damage Instructions for installation or instructions for use shall be provided to specify correct use of the fixing point		N/A

Attachment No. 2



IEC 62368_1E ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
	Describe the Fixing Point		N/A
	Attache Photo of Fixing Point		N/A
8.6.202	Restraining device MS2 and MS3 television sets and display devices shall be provided with a restraining device and associated hardware to attach to the television set or display device. The restraining device shall be capable of withstanding a pull equal to the mass of the equipment in all directions. Instructions for installation or instructions for use shall be provided to specify correct use of the fixing point .		N/A
	Describe the Fixing Point		N/A
	Attache Photo of Fixing Point		N/A

Attachment No. 2



AS/NZS 3112:2017 Appendix J			
Clause	Requirement + Test	Result - Remark	Verdict
ATTACHMENT TO TEST REPORT AS_NZS_3112:2017_+A1:2021 Appendix J AUSTRALIAN / NEW ZEALAND NATIONAL DIFFERENCES (Approval and test specification—Plugs and socket-outlets)			
Differences according to : AS_NZS_3112:2017_Amendment 1:2021_Appendix J			
TRF template used: : IECEE OD-2020-F3, Ed. 1.1			
Attachment Form No. : AS_NZS_3112:2017_Appendix J			
Attachment Originator : JAS-ANZ			
Master Attachment : 2022-06			
Copyright © 2020 IEC System for Conformity Testing and Certification of Electrical Equipment (IECEE), Geneva, Switzerland. All rights reserved.			
	Note: AS/NZS 3112 is NOT covered by IECEE Accreditation for Testing / Reporting Please State Laboratory Accreditation for this Standard		N/A
	Accreditation		N/A
	Accreditation Stamp		N/A
J1 SCOPE	General: This Appendix specifies additional dimensional and constructional requirements for detachable plug portions, or equipment incorporating integral supply pins or equipment incorporating detachable plug portions. This Appendix shall be read in conjunction with Section 2 of this Standard. For the purposes of this Appendix, where the term 'plug' is used in Section 2 it shall be taken to mean the plug portion of equipment or the detachable plug portion. The equipment shall comply with the relevant product Standard. The tests and requirements specified in this Appendix are in addition to any test and requirements of the relevant product Standard for the equipment. (AS/NZS 3112:2017/A1:2021)		N/A

Attachment No. 2

AS/NZS 3112:2017 Appendix J

Clause	Requirement + Test	Result - Remark	Verdict
J2	DEFINITION		N/A
J2.1	Detachable plug portion A plug portion that is detachable from the equipment and with connections including the following standardized outputs and other contacts (a) Type A (see Figure J1): A detachable plug portion with a connection intended for plugging directly into equipment. The connection being via the equipment group 1 appliance inlet within the scope of AS/NZS 60320.1. (b) Type B (see Figure J2): A detachable plug portion with a non-standardized connection intended for plugging directly into equipment (c) Type C (see Figure J3): A detachable plug portion with a connection intended for use with an adaptor connected to a flexible cord so as to replicate a supply plug and flexible cord configuration. The connection being via a group 1 appliance outlet within scope of AS/NZS 60320.2.2, which is integral with the plug portion (AS/NZS 3112:2017)		N/A
J2.2	Integral plug portion A plug portion that is integral to the equipment enclosure and is not detachable (AS/NZS 3112:2017)		N/A
J2.3	Plug portion A plug portion is that portion of equipment with pins for insertion into a socket-outlet, including the plug pins, terminals of the plug pins, external dimensions of the 'maximum projection' and any connections of a detachable plug portion. (AS/NZS 3112:2017/A1:2021)		N/A
J3	REQUIREMENTS FOR THE PLUG PORTION		N/A
J3.1	General The following provisions apply to the dimensional and constructional requirements of plug portions of equipment and any detachable connection between the plug portion and the equipment:		N/A
(a)	For detachable plug portions intended for connection to the equipment in multiple orientations, the relevant tests are performed in the most onerous orientation.		N/A
(b)	For Type A detachable plug portion, the relevant requirements of AS/NZS 3105:2014 are applicable, in addition to conformance with relevant clauses of this Appendix	See Test Report xxx to AS/NZS 3105:2014 Test Report xxx to AS/NZS 60320.1 for the Group 1 appliance inlet portion.	N/A
(c)	For Type B detachable plug portions, the conformance is shown by the relevant clauses of this Appendix.		N/A
(d)	For Type C detachable plug portions, conformance is shown by assessment to Section 2 _of this	See also Test Report xxx to AS/NZS 60320.2.2 for the Group	N/A

Attachment No. 2

AS/NZS 3112:2017 Appendix J

Clause	Requirement + Test	Result - Remark	Verdict
	Standard (plugs) and relevant clauses of this Appendix (AS/NZS 3112:2017)	1 appliance outlet portion.	
J3.2	Plug pins of plug portions The requirements of Clause 2.2 are applicable for plug pins.		N/A

2.2	PLUG PINS		N/A
2.2.1	Current carrying parts of plug pins of metal having sufficient mechanical strength, electrical conductivity and resistance to corrosion adequate for the intended use		N/A
	Plug pin material?		
2.2.3	Plug pins adequately proportioned throughout and portion adjacent to the connection designed to not introduce a stress concentration which may lead to a fracture of the pin, and suitably shaped to prevent abrasion or cutting of conductor strands due to flexure in normal use		N/A
	Exposed ends of plug pins have a lead-in, bevel or radius to facilitate entry into socket-outlets and to operate shutters		N/A
	Flat-pins with the following profile are deemed to comply:		
(a)	Flat-pins with a radius on the end with side bevels may have a width and thickness profile as specified in Figure 2.1(h)		N/A
(b)	Flat-pins square on the end with corner and side bevels may have a width and thickness profile as specified in Figure 2.1(i)		N/A
(c)	Flat-pins square on the end with corner bevels and a radius on the sides may have a width and thickness profile as specified in Figure 2.1(j)		N/A
	Contact portion of the pins smooth and free from openings or indentations		N/A
	Flat pin plugs having a longitudinal seam or opening in the contact portion of one face; width not exceeding 0.3 mm and		N/A
	Thickness not exceeding 1.58 mm		N/A
	Exposed portion of earthing pins and pins other than insulated pins free from any non-metallic coverings or coatings (AS/NZS 3112:2017)		N/A
2.2.4	Live parts of insulated pin plugs not exposed when plug is partially or fully engaged with associated socket		N/A
	Compliance by measurement to Figure 2.4	(see appended table)	N/A

Attachment No. 2

AS/NZS 3112:2017 Appendix J

Clause	Requirement + Test	Result - Remark	Verdict
	Lacquer, enamel or sprayed insulating coating not considered to be insulation material		N/A
	All live pins on low voltage plugs except for those shown in Figure 2.1 (a2), (b) and (g) of the insulated pin type		N/A
	Colour green or green / yellow not used for insulation of insulated pins (AS/NZS 3112:2017)		N/A
J3.3	Ratings and dimensions for low-voltage plug portions Requirements of clauses 2.8.1 and 2.8.4 apply for rating and dimensions		N/A
2.8	Ratings and Dimensions of Low Voltage Plugs		
2.8.1	Plugs with ratings up to and including 20A; shall conform to the appropriate dimensions shown in Figure 2.1	(see appended results)	N/A
	Rating of plug	___A	
	Nominal dimensions covering disposition of pins checked by gauge of Appendix A		N/A
	Distance between live pin and edge of moulding to not less than 9 mm		N/A
	Measured distance	___mm	
	No point on plug face protrudes more than 0.5 mm		N/A
	Measured protrusion	___mm	
	Dimensional requirements of Figure 2.1(e2) did not applied to plugs with greater than three pins (AS/NZS 3112:2017)		N/A
2.8.4	Low voltage plugs comply with dimensions of Figure 2.1	(see appended table 2.8.1)	N/A
	Disposition of pins checked by gauge complying with Appendix A, B or F as appropriate		N/A
	Low voltage plug having rating up to 15A and of the Figure 2.1 (a1), (c), (d), (f) or (g) type; comply with dimensional requirements of Figure 2.1 (e1 and e2)		N/A
	20A plug of Figure 2.1 (a2) type complies with dimensional requirements of Figure 2.1 (e2)		N/A
	Plugs with insulated pins need not comply with dimension $R20.0 \pm 1$ mm requirement of Figure 2.1 (e3) provided there is at least 9mm from the edge of the live pins to the edge of the plug face Figure 2.1(e3). (AS/NZS 3112:2017)		N/A
J3.4	Internal connections for plug portions		N/A

Attachment No. 2



AS/NZS 3112:2017 Appendix J			
Clause	Requirement + Test	Result - Remark	Verdict
	Requirements of clause 2.9 apply for internal connections; unless requirements contained in the relevant product standard (AS/NZS 3112:2017)		
2.9	INTERNAL CONNECTIONS		N/A
	Plug provided with earthing connections designed and constructed so that when plug is correctly wired and assembled:		N/A
(a)	Loose terminal screw or conductive material cannot bridge any live or earthed parts		N/A
(b)	Earthing parts effectively isolated from contact with live conductor which may become detached		N/A
(c)	Live parts effectively isolated from contact with any earthing conductor which may become detached		N/A
	Any connections for auxiliary devices comply with above requirements (AS/NZS 3112:2017)		N/A
J3.5	Arrangement of earthing connections for plug portions Requirements of clause 2.10 apply for arrangement of earthing connections		N/A
2.10	Arrangement of earthing connections		N/A
	Earthing pin radial to the circle embracing the pins (AS/NZS 3112:2017)		N/A
J3.6	Configuration of plug portions Requirements of clause 2.12.6 apply for configuration of the plug portion (AS/NZS 3112:2017)		N/A
2.12	Marking		
2.12.6	Configuration of plugs		N/A
	Pins disposed so that configuration, as viewed from the pins, is earth, neutral and active in a clockwise direction		N/A
	Where there is no earthing pin; live pins conform to this configuration (AS/NZS 3112:2017)		N/A
J4	Tests		
J4.1	General Plug portions of equipment shall be subjected to the following tests and unless stated otherwise, shall comply with the requirements specified in Section 2 for each test.		N/A

Attachment No. 2

AS/NZS 3112:2017 Appendix J			
Clause	Requirement + Test	Result - Remark	Verdict
	The number of test samples shall be in accordance with Table J1 For equipment with a detachable plug portion, the assessment(s) of Table J1 tests 2, 3, 5, 10 and 11 shall be conducted on the— (a) assembled equipment with the detachable plug portion connected; and (b) the detachable plug portion after it has been separated from the equipment (AS/NZS 3112:2017/A1:2021)		
J4.2	High voltage test The requirements of Clause 2.13.3 are applicable unless requirements are contained in the relevant product standard (AS/NZS 3112:2017)		N/A
2.13.3	Test No.1 - High voltage test		N/A
	Plug withstands without failure electric strength test as specified (AS/NZS 3112:2017)	(see appended table)	N/A
J4.3	Mechanical strength		N/A
J4.3.1	Tumbling barrel test The tumbling barrel test is applied to determine the mechanical strength of the plug portions and equipment having integral or detachable plug portions. For equipment with a detachable plug portion, the detachable plug portion may become detached during the test. If this occurs the detachable plug portion shall be reassembled with the equipment when the pins are straightened as per (a) and (b) below. Three samples (Samples BCD in Table J1) that have not been subjected to any previous test are tested as specified in Clause 2.13.7.1, however the test is modified as follows:		N/A
	They are tested in a tumbling barrel as described in AS 60068.2.32 or test Free fall repeated – Procedure 2 in IEC 60068-2.31. The samples shall be dropped from a height of 500 mm onto a steel plate, 3 mm thick. The barrel shall be turned at a rate of 5 r/min, to yield 10 falls per minute. Only one sample shall be tested at a time. A sample is dropped— (a) 500 times if the mass of the specimen does not exceed 250 g. The pins being straightened after each 100 drops and at the completion of the test to pass through the appropriate gauge of Figure A1, Figure B1 or Figure F1; and (b) 250 times if the mass of the specimen exceeds 250 g. The pins being		N/A

Attachment No. 2

AS/NZS 3112:2017 Appendix J			
Clause	Requirement + Test	Result - Remark	Verdict
	straightened after each 25 drops and at the completion of the test to pass through the appropriate gauge of Figures A1 , Figure B1 or Figure F1 . (AS/NZS 3112:2017/A1:2021)		
	Mass of sample	_____ Grams	N/A
	Number of drops	500 / 250	N/A
	Compliance shall be checked by Paragraph J4.3.3	(See appended table)	N/A
J4.3.2	Test No.3 Impact test. Plug portions and equipment having integral plug portions or detachable plug portions shall withstand lateral impact forces. All samples that were subjected to the tests in Paragraph J4.3.1 (Samples BCD in Table J1) shall be tested as follows:		N/A
	(a) The sample shall be positioned at the centre of a steel plate with a thickness of at least 6 mm. Apertures in the steel plate for the plug pins to pass through shall conform to the corresponding socket Standard. The sample shall be held against the steel plate by clamping all the pins.		N/A
	(b) Samples shall be subjected to blows, with an impact energy of 1.0 ± 0.05 J by any means having the same performance as the spring-operated impact-test apparatus of AS/NZS 3100.		N/A
	(c) Three blows shall be applied to every point that is most likely to directly or indirectly stress the enclosure joints of the sample		N/A
	Compliance shall be checked by Paragraph J4.3.3		N/A
J4.3.3	Specific compliance criteria This Paragraph provides the common compliance assessment criteria for tests specified in Paragraphs J4.3.1 and J4.3.2 .		N/A
(a)	assembled equipment with the detachable plug portion connected;		N/A
	After the test, samples show no damage	(See appended table)	N/A
(b)	the detachable plug portion after it has been separated from the equipment.		N/A
	After the test, samples show no damage	(See appended table)	N/A
4.3.4	Pin bending test The pins of the plug portion of three samples (Samples EFG in Table J1) not subjected to any previous tests shall be tested for compliance with the pin bending test of Clause 2.13.7.2 (AS/NZS 3112:2017/A1:2021)		N/A

Attachment No. 2

AS/NZS 3112:2017 Appendix J

Clause	Requirement + Test	Result - Remark	Verdict
2.13.7.2	Test No.4 – Pin bending test		N/A
	All flat-pin plugs rated up to and including 15 A shall be subjected to the pin bending test		N/A
	Three samples are subjected by clamping the plug in a rigid holding block and applying the bending force as specified		N/A
	After the test the pins shall not be broken off. (AS/NZS 3112:2017)		N/A
J4.8.3	Test No.5 Plug portion detachment requirements		N/A
	For all Type B or C devices and for Type A devices where the outlet of the detachable plug portion is parallel to the plug supply pins, disengagement of the detachable plug portion from the equipment shall require at least two simultaneous independent actions or the use of a tool.		N/A
	The plug portion and the equipment/adaptor shall be connected and disconnected 50 times (100 strokes).		N/A
	Compliance is verified by the plugging test, a force which, over a period of 10 s, shall be increased steadily to 60 ± 0.6 N and held at this value for a further 10 s, shall be applied evenly at the connecting equipment in a direction parallel to the pins. This procedure shall be conducted three times on the same plug portion, at intervals of 5 min, without disturbing the plug portions between tests		N/A
	During the test the plug portion shall not separate		N/A
	The test of AS/NZS 3112 'temperature rise test' for plugs shall be conducted immediately after the above test without disturbing the sample. Test No 6 Temperature Rise test J4.4 (AS/NZS 3112:2017/A1:2021)		N/A
J4.4	Temperature rise test The relevant requirements of Clause 2.13.8 are applicable for the temperature rise test, except that the test current shall be that specified in the relevant product standard		N/A
	The temperature rise of the pins shall not exceed 45 K irrespective of the temperature rise of parts specified in end-product standards.		N/A
	For detachable plug portions the temperature rise of terminals and contacts shall not exceed 45 K. (AS/NZS 3112:2017)		N/A

Attachment No. 2

AS/NZS 3112:2017 Appendix J			
Clause	Requirement + Test	Result - Remark	Verdict
2.13.8	Test No.6 – Temperature rise test		N/A
	Plug tested in draught free environment as specified using clamping units as specified in Figure 2.10		N/A
	Test Current Relevant Product Standard	____ Amps ____ (Standard?)	N/A
	Temperature of terminals and contacts of detachable plug portion not exceeding 45 K (AS/NZS 3112:2017)	(see appended table)	N/A
J4.5	Securement of pins of the plug portion The requirements of Clause 2.13.9 are applicable for the securement of pins. (AS/NZS 3112:2017)		N/A
2.13.9	Test No.7. Securement of pins		N/A
2.13.9.1	Movement of pins		N/A
	Plug pins clamped 5 ± 0.5 mm from pin face; test equipment and sample pre-conditioning for 1 h at $40 \pm 1^\circ\text{C}$		N/A
	Force of 18 ± 1 N applied to pin 14 ± 0.5 mm from plug face; applied gradually over 10 s and maintained for 10 s; applied in four directions		N/A
	Maximum deflection during test not exceeding 2.0 mm	(see appended results)	N/A
	Any distortion 5 minutes after test does not prevent insertion of plug into standard gauge(s) (AS/NZS 3112:2017 + A1:2021)		N/A
2.13.9.2	Fixing of pins		
	Plug heated to $50 \pm 2^\circ\text{C}$ for 1h		N/A
	Force of 60 ± 0.6 N applied to each pin over 10 s and maintained for 10 minutes; applied in two directions along length of pin		N/A
	Maximum displacement during test not exceeding 2.4 mm		N/A
	Maximum measured displacement		
	Pin returns to within 0.8 mm of nominal length within 5 minutes of removal of test force (AS/NZS 3112:2017)		N/A
J4.6	Tests on the insulation material of insulated pin-plug portions The requirements of Clause 2.13.13 are applicable for insulating material of		N/A

Attachment No. 2

AS/NZS 3112:2017 Appendix J

Clause	Requirement + Test	Result - Remark	Verdict
--------	--------------------	-----------------	---------

	insulated plug pins. (AS/NZS 3112:2017)		
--	--	--	--

2.13.13	Test No.8 Tests for insulation material of insulated pin plugs		N/A
2.13.13.1	Material of pin-insulation resistant to stresses at temperature likely to occur		N/A
2.13.13.2	Pressure test at high temperature		N/A
	Specimen tested as per Figure 2.5 with force of 2.5 N applied as specified; maintained for 2 h at $160 \pm 5^{\circ}\text{C}$; removed and cooled by immersion in water within 10 s		N/A
	Thickness of insulation at point of impression not reduced by more than 50%		N/A
	Initial thickness	mm	
	Thickness after test	mm	
	No visible cracks on insulation material		N/A
	Dimension of insulating material not below minimum size in Figure 2.4 (AS/NZS 3112:2017)		N/A

2.13.13.3	Static damp heat test		N/A
	Specimen subjected to two damp heat cycles in accordance with AS 60068.2.30; Db (12 + 12h), 95% RH, $25 \pm 3^{\circ}\text{C}$; 40°C		N/A
	After this treatment and recovery to room temperature; specimen subjected to:		N/A
(a)	Insulation resistance test in accordance with clause 2.13.2 (e)	(see appended table)	N/A
(b)	High voltage test in accordance with clause 2.13.3	(see appended table)	N/A
(c)	Abrasion test in accordance with clause 2.13.13.6		N/A
2.13.13.4	Low temperature test		N/A
	Plug maintained at $-15 \pm 2^{\circ}\text{C}$ for minimum of 24 h and returned to room temperature; after which specimen subjected to:		N/A
(a)	Insulation resistance test in accordance with clause 2.13.2 (e)	(see appended table)	N/A
(b)	High voltage test in accordance with clause 2.13.3	(see appended table)	N/A
(c)	Abrasion test in accordance with clause 2.13.13.6		N/A
2.13.13.5	Impact test at low temperature		N/A
	Specimen maintained at $-15 \pm 2^{\circ}\text{C}$ for 24 h		N/A
	Specimen placed in position and subjected to impact test as per Figure 2.6; mass of 100 ± 1 g falling through 100 mm		N/A
	Four impacts applied; specimen rotated through 90°		N/A

Attachment No. 2

AS/NZS 3112:2017 Appendix J			
Clause	Requirement + Test	Result - Remark	Verdict
	between impacts		
	After return to room temperature; no visible cracks of insulating material		N/A
2.13.13.6	Abrasion test		N/A
	Plug held in clamp and tested as per Figure 2.7; pin loaded at 4 N; 20 000 movements		N/A
	After test; pins show no damage affecting safety or impairing further use of the plug		N/A
	Insulating sleeve not punctured or rucked up (AS/NZS 3112:2017)		N/A
J4.7	Test no.9 Equipment with a plug portion intended to be supported by the contacts of a socket-outlet		N/A
	Equipment with pins intended to be introduced into fixed socket-outlets not imposing undue strain on socket-outlet		N/A
	Applied torque not exceeding 0.25 Nm		N/A
	Measured torque (AS/NZS 3112:2017)	Nm	
J4.8	Additional requirements for detachable plug portions		N/A
J4.8.1	Test no.10 Access to live parts		N/A
	Small test finger of Figure 13 of IEC 61032 was not possible to contact live parts with the force of 20N		N/A
	incorrectly assemble the plug portion was not possible (AS/NZS 3112:2017)		N/A
J4.8.2	Test No.11 Construction of detachable contacts where the input current of the equipment exceeds 0.2 A		N/A
	Contacts of the equipment shall be such that they make and maintain, under normal service conditions, satisfactory electrical and mechanical contact with the corresponding contact of the detachable plug portion.		N/A
	For connections intended to accommodate pins, contact shall be made on two surfaces diametrically opposite, except if a single spring-assisted contact is used. (AS/NZS 3112:2017/A1:2021)		N/A
	Contacts shall not rely exclusively on the resilience of the contact material and shall have an opposite face of material other than thermoplastic or resilient insulating material. (AS/NZS 3112:2017/ A1:2021)		N/A
	The alignment and contact-making properties of contacts shall be independent of terminal screws		N/A

Attachment No. 2

AS/NZS 3112:2017 Appendix J			
Clause	Requirement + Test	Result - Remark	Verdict
	The effectiveness of the contacts shall be independent of pressure from any thermoplastic or resilient moulding.		N/A
	A visual inspection is conducted to determine the existence of interference between the metal contacts and the thermoplastic or resilient moulding to provide supplementary contact pressure to the metal contacts.		N/A
	Conformance of the effectiveness of the contacts is checked by inspection and by the inspection and tests in J4.8.3 (AS/NZS 3112:2017)		N/A

J4.8.4	Resistance of insulating material to heat and fire		N/A
J4.8.4.1	Test no.12 Resistance to heat For Type B detachable plug portions parts of non-metallic material, parts of insulating material supporting live parts including connections, and parts of thermoplastic material providing supplementary insulation or reinforced insulation, shall be sufficiently resistant to heat if their deterioration could cause the appliance to fail to comply with this Standard.		N/A
	Ball pressure test conducted in accordance with IEC 60695-10-2		N/A
(a)	75°C ± 2°C, for external parts;		N/A
(b)	125°C ± 2°C, for parts supporting live parts.		N/A

J4.8.4.2	Test no.13 Resistance to fire		N/A
	Plug portions comply with resistance to fire requirements of AS/NZS 3100 as follows:		N/A
	The glow wire test temperature 'T' for 'retaining parts' of fixed socket outlets shall be 750 C (AS/NZS 3112:2017)		N/A

TABLES OF RESULTS

2.2.4	TABLE: Dimensions of insulation on insulated pin plugs		N/A
Dimension (Figure 2.1 designation)		Measured (mm)	Allowed (mm)
Phase pin			8.7 ± 0.5
Neutral pin			8.7 ± 0.5

2.8.1	TABLE: Dimensions of plugs- 10A (a1)		N/A
Dimension (Figure 2.1 designation)		Measured (mm)	Allowed (mm)
Phase and neutral pin width (A)			6.35 ± 0.15
Earth pin width (B)			6.35 ± 0.15

Attachment No. 2



AS/NZS 3112:2017 Appendix J

Clause	Requirement + Test	Result - Remark	Verdict
	Pin thickness (C)	1.63 + 0.15, -0.05	
	Pin disposition (D)	checked by test gauge	
	Pin disposition (E)	checked by test gauge	
	Phase and neutral pin length (F)	17.06 ± 0.4	
	Earth pin length (G)	19.94 ± 0.8	
	Pin boss radius - maximum	21.0 max	
	Pin boss height	8.6 min	

2.8.1	TABLE: Dimensions of plugs- 15A (a1)		N/A
Dimension (Figure 2.1 designation)	Measured (mm)	Allowed (mm)	
Phase and neutral pin width (A)		6.35 ± 0.15	
Earth pin width (B)		9.08 ± 0.15	
Pin thickness (C)		1.63 + 0.15, -0.05	
Pin disposition (D)		checked by test gauge	
Pin disposition (E)		checked by test gauge	
Phase and neutral pin length (F)		17.06 ± 0.4	
Earth pin length (G)		19.94 ± 0.8	
Pin boss radius - maximum		21.0 max	
Pin boss height		8.6 min	

2.8.1	TABLE: Dimensions of plugs-20A (a2)		N/A
Dimension (Figure 2.1 designation)	Measured (mm)	Allowed (mm)	
Phase and neutral pin width (A)		9.08 ± 0.15	
Earth pin width (B)		9.08 ± 0.15	
Pin thickness (C)		1.63 + 0.15, -0.05	
Pin disposition (D)		checked by test gauge	
Pin disposition (E)		checked by test gauge	
Phase and neutral pin length (F)		17.06 ± 0.4	
Earth pin length (G)		19.94 ± 0.8	
Pin boss radius - maximum		21.0 max	
Pin boss height		8.6 min	

2.8.1	TABLE: Projection from plug face centroid		N/A
Direction of projection	Measured (mm)	Allowed (mm)	
Left		≤ 21.9 or ≥ 27.0	
Right		≤ 21.9 or ≥ 27.0	

Attachment No. 2

AS/NZS 3112:2017 Appendix J

Clause	Requirement + Test	Result - Remark	Verdict
Up			≤ 21.9 or ≥ 27.0
Down			≤ 21.9 or ≥ 27.0

2.13.3	TABLE: Test No. 1 – High voltage test		N/A
Test voltage applied between:		Test voltage (V)	Breakdown
All poles of the plug; taken in pairs		1000	Yes / No
Live poles of the plug and any external metal		3500	Yes / No
Live poles of the plug and the earthing terminal		1000	Yes / No
Live poles of the plug and a flexible electrode		3500	Yes / No
Live poles and metal foil applied around insulation on pins		1250	Yes / No

2.13.7.1	Test No.2 – Tumbling barrel test		N/A
	Following the test, the samples shall comply with Clause 2.13.7.1(a..e)		N/A
	(a) Live parts shall not have become exposed to the standard test finger		N/A
	(b) For earth pins, the resistance of the plug/socket-outlet circuit shall be such that conformance with Clause 3.14.7 is maintained. AS/NZS 3100 Cl 8.5 The resistance shall not exceed 0.1 Ω	___ Ω .	N/A
	(c) Any other function affecting safety shall not be impaired		N/A
	(d) No live part shall have become detached or loosened, to the extent that a hazardous situation is created (see Clause 2.9)		N/A
	(e) The pins shall be inspected with normal, or corrected to normal, vision. Insulation may be removed if necessary. Pins shall not be broken or show cracking		N/A

	Test No.3 Impact test for assembled equipment with the detachable plug portion connected and for equipment with an integral plug portion.		N/A
	Following the test, the samples shall comply with Clause 2.13.7.1 (a..e) as follows:		N/A
	(a) Live parts shall not have become exposed to the standard test finger (Figure 8.10 in AS/NZS 3100 or Test Probe B in IEC 61032)		N/A

Attachment No. 2



AS/NZS 3112:2017 Appendix J

Clause	Requirement + Test	Result - Remark	Verdict
	(b) For earth pins, the resistance of the plug/socket-outlet circuit shall be such that conformance with Clause 3.14.7 is maintained so that the resistance between the earthing terminal of any socket-outlet provided with an earthing contact and the earthing terminal of the plug used for testing shall be of a low resistance. Compliance is by the test of earthing connection in AS/NZS 3100 Clause 8.5. The resistance shall not exceed 0.1 Ω	___ Ω .	N/A
	(c) Any other function affecting safety shall not be impaired		N/A
	(d) No live part shall have become detached or loosened, to the extent that a hazardous situation is created		N/A
	(e) The pins shall be inspected with normal, or corrected to normal, vision. Insulation may be removed if necessary. Pins shall not be broken or show cracking.		N/A
	Following the test, the samples shall conform to the 'Guarding of live parts' requirements of AS/NZS 3100:2015 cl 5.1 as follows:		N/A
	Except for equipment intended for use only in a position not accessible to unauthorized persons, all equipment shall be so designed and constructed that, when the equipment is standing, supported, or fixed, in a normal manner, no person can inadvertently come into contact with any live part		N/A
	If a hole giving access to preset controls is marked as such on the enclosure or reference made to it in the instructions and the setting of this control requires a screwdriver or other tool, the adjustment of the control shall not allow contact with any live parts. A metal test pin having a diameter of 2 mm and a length of 100 mm shall not become live when it is inserted through the hole in every position with a force of 10 N.		N/A
	In addition, the opening or removal of any cover or component, with or without tools, where such opening or removal is necessary as a normal operation of the equipment as distinct from maintenance, repairs, or adjustment, shall not expose live parts to inadvertent personal contact.		N/A
	Any metal cover or casing enclosing live parts shall be of a strength sufficient to ensure that it cannot be deformed readily so as to come into contact with live parts.		N/A

Attachment No. 2

AS/NZS 3112:2017 Appendix J

Clause	Requirement + Test	Result - Remark	Verdict
	Compliance is checked by inspection, test and checking that live parts shall not have become exposed to the standard test finger (Figure 8.10 in AS/NZS 3100 or Test Probe B in IEC 61032)		N/A
	Class II equipment and class II constructions shall be constructed and enclosed so that there is adequate protection against accidental contact with basic insulation and metal parts separated from live parts by basic insulation only.		N/A
	It shall only be possible to touch parts which are separated from live parts by double insulation or reinforced insulation.		N/A
	Compliance is checked by application of the standard test finger (Figure 8.10 in AS/NZS 3100 or Test Probe B in IEC 61032)		N/A
	Following the test, the samples shall conform to the 'Separation of live parts from non-current-carrying conductive parts' requirements of AS/NZS 3100.CI 5.2.2 as follows:		N/A
	The support and insulation of every live part shall be such as will ensure that no live part can make contact with any non-current-carrying conductive part exposed to personal contact.		N/A
	In respect of terminals of components such as switches, adequate clearances shall be maintained or insulation shall be provided to prevent contact of the terminals, or loose strands of flexible cords intended to be terminated therein, with exposed conductive parts. Where necessary, provision shall be made to ensure that conductors protruding through terminals, when normally connected, will not contact exposed conductive parts.		N/A
	Compliance is checked by inspection.		N/A
	Test No.3 Impact test for the detachable plug portion after it has been separated from the equipment		N/A
	Following the test, the samples shall comply with Clause 2.13.7.1 (a..e)		N/A
	(a) Live parts shall not have become exposed to the standard test finger (Figure 8.10 in AS/NZS 3100 or Test Probe B in IEC 61032)		N/A

Attachment No. 2



AS/NZS 3112:2017 Appendix J

Clause	Requirement + Test	Result - Remark	Verdict
	(b) For earth pins, the resistance of the plug/socket-outlet circuit shall be such that conformance with Clause 3.14.7 is maintained so that the resistance between the earthing terminal of any socket-outlet provided with an earthing contact and the earthing terminal of the plug used for testing shall be of a low resistance. Compliance is by the test of earthing connection in AS/NZS 3100 Clause 8.5. The resistance shall not exceed 0.1 Ω	___ Ω .	N/A
	(c) Any other function affecting safety shall not be impaired		N/A
	(d) No live part shall have become detached or loosened, to the extent that a hazardous situation is created		N/A
	(e) The pins shall be inspected with normal, or corrected to normal, vision. Insulation may be removed if necessary. Pins shall not be broken or show cracking.		N/A
	Following the test, the samples shall conform to the 'Guarding of live parts' requirements of AS/NZS 3100:2015 cl 5.1 as follows:		N/A
	Except for equipment intended for use only in a position not accessible to unauthorized persons, all equipment shall be so designed and constructed that, when the equipment is standing, supported, or fixed, in a normal manner, no person can inadvertently come into contact with any live part		N/A
	If a hole giving access to preset controls is marked as such on the enclosure or reference made to it in the instructions and the setting of this control requires a screwdriver or other tool, the adjustment of the control shall not allow contact with any live parts. A metal test pin having a diameter of 2 mm and a length of 100 mm shall not become live when it is inserted through the hole in every position with a force of 10 N.		N/A
	In addition, the opening or removal of any cover or component, with or without tools, where such opening or removal is necessary as a normal operation of the equipment as distinct from maintenance, repairs, or adjustment, shall not expose live parts to inadvertent personal contact.		N/A
	Any metal cover or casing enclosing live parts shall be of a strength sufficient to ensure that it cannot be deformed readily so as to come into contact with live parts.		N/A
	Compliance is checked by inspection, test and checking that live parts shall not have become exposed to the standard test finger (Figure 8.10 in AS/NZS 3100 or Test Probe B in IEC 61032)		N/A

Attachment No. 2

AS/NZS 3112:2017 Appendix J

Clause	Requirement + Test	Result - Remark	Verdict
	Class II equipment and class II constructions shall be constructed and enclosed so that there is adequate protection against accidental contact with basic insulation and metal parts separated from live parts by basic insulation only.		N/A
	It shall only be possible to touch parts which are separated from live parts by double insulation or reinforced insulation.		N/A
	Compliance is checked by application of the standard test finger (Figure 8.10 in AS/NZS 3100 or Test Probe B in IEC 61032)		N/A
	Following the test, the samples shall conform to the 'Separation of live parts from non-current-carrying conductive parts' requirements of AS/NZS 3100.CI 5.2.2 as follows:		N/A
	The support and insulation of every live part shall be such as will ensure that no live part can make contact with any non-current-carrying conductive part exposed to personal contact.		N/A
	In respect of terminals of components such as switches, adequate clearances shall be maintained or insulation shall be provided to prevent contact of the terminals, or loose strands of flexible cords intended to be terminated therein, with exposed conductive parts. Where necessary, provision shall be made to ensure that conductors protruding through terminals, when normally connected, will not contact exposed conductive parts.		N/A
	Compliance is checked by inspection.		N/A

2.13.8	TABLE: Test No. 6 - Temperature rise test		N/A
	Ambient temperature	°C	
	Test current	A	
Measured part		dT measured (K)	dT allowed (K)
Active (phase) terminal			45
Neutral terminal			45
Earthing terminal			45

2.13.9.1	TABLE: Movement of pins		N/A
	Earth and neutral pins clamped – phase pin loaded		
Force direction		Measured deflection (mm)	Allowed deflection (mm)
Force towards neutral plane parallel to pin plane			2.0
Force from neutral plane parallel to pin plane			2.0
Force outwards at 90° to pin plane			2.0
Force inwards at 90° to pin plane			2.0

Attachment No. 2



AS/NZS 3112:2017 Appendix J

Clause	Requirement + Test	Result - Remark	Verdict
--------	--------------------	-----------------	---------

2.13.9.1	TABLE: Movement of pins		N/A
	Phase and neutral pins clamped – earth pin loaded		
Force direction		Measured deflection (mm)	Allowed deflection (mm)
Force inwards parallel to pin plane			2.0
Force outwards parallel to pin plane			2.0
Force towards neutral			2.0
Force towards phase			2.0

2.13.9.1	TABLE: Movement of pins		N/A
	Phase and earth pins clamped – neutral pin loaded		
Force direction		Measured deflection (mm)	Allowed deflection (mm)
Force towards phase plane parallel to pin plane			2.0
Force from phase plane parallel to pin plane			2.0
Force outwards at 90° to pin plane			2.0
Force inwards at 90° to pin plane			2.0

2.13.13.3	TABLE: Test No.13(b) – Insulation resistance test after static damp heat test		N/A
Applied between:		Insulation resistance (MΩ)	Minimum required (MΩ)
Live poles and metal foil applied around insulation on pins			5

2.13.13.3	TABLE: Test No.1 – High voltage test after static damp heat test		N/A
Test voltage applied between:		Test voltage (V)	Breakdown
Live poles and metal foil applied around insulation on pins		1250	Yes / No

2.13.13.4	TABLE: Test No.1 – Insulation resistance test after low temperature test		N/A
Applied between:		Insulation resistance (MΩ)	Minimum required (MΩ)
Live poles and metal foil applied around insulation on pins			5

2.13.13.4	TABLE: Test No.1 – High voltage test after low temperature test		N/A
Test voltage applied between:		Test voltage (V)	Breakdown
Live poles and metal foil applied around insulation on pins		1250	Yes / No

Attachment No. 2



AS/NZS 3112:2017 Appendix J			
Clause	Requirement + Test	Result - Remark	Verdict

J4.8.4.1	TABLE: Test no.12 Resistance to heat		N/A
Component tested		Temperature (°C)	Diameter of impression (mm)

Conformance is checked by subjecting the relevant part to the ball pressure test of IEC 60695-10-2.

J4.8.4.2	TABLE: Test no.13 Resistance to Fire		N/A
	Plug portions shall comply with the requirements for resistance to fire in accordance with AS/NZS 3100:2017 Annex A. The glow-wire test temperature 'T' shall be 750°C.		

Glow-wire testing was conducted in accordance with IEC 60695-2-11.

Test specimens arranged so that the surface in contact with the tip of the glow-wire was vertical and glow wire tip applied to surface of the specimen likely to be subjected to thermal stresses in normal use.

A layer of white pine board and wrapping tissue was placed beneath the sample at 200mm ± 5mm distance.

SPECIMEN NUMBER	1	2	3	4
SPECIMEN DESCRIPTION				
Material				
Colour				
Test specimen				
Glow wire tip temperature (°C)	750	750	750	750
Duration of glow wire application (t _a) (s)	30	30	30	30
OBSERVATIONS				
Duration from beginning of glow-wire tip application to ignition of specimen or layer (t _i) (s)				
Duration from beginning of glow-wire tip application to when flames extinguish (t _e) (s)				
Maximum height of flames after initial 1s (to nearest 5 mm) (mm)				
Flame impingement on other parts				
Degree of tip penetration				
Degree of specimen distortion				
Scorching of pinewood board				

Attachment No. 2

AS/NZS 3112:2017 Appendix J

Clause	Requirement + Test	Result - Remark	Verdict
EVALUATION CRITERIA			
	Visible flame or sustained glowing		
	Visible Flame Duration in Seconds during test.		
	Duration of flaming or glowing after tip removal (max. allowable 30 s) (s)		
	Surrounding parts burned away completely (not permitted)		
	Ignition of wrapping tissue layer (not permitted)		
RESULTS			
If parts tested withstand the glow-wire test, but during the test produce a flame that persists for longer than 2 s, then the consequential needle flame test of AS/NZS 3100:2017 Annex A 6.1.5 applies.			

LEGEND: CE Complete Equipment SA Sub Assembly SE Self Extinguished
EBD Emitted Burning Droplets SBD Specimen Burned and Distorted SMD Specimen Melted and Distorted
ME Manually Extinguished SC Separate Component SS Specimen Scorched
NA Not Applicable SCC Specimen Completely Consumed WPNI Wall Penetrated but no Ignition
NI No Ignition X Flame Appeared for an Instant

Glow-wire testing was conducted in accordance with IEC 60695-2-11.

Test specimens arranged so that the surface in contact with the tip of the glow-wire was vertical and glow wire tip applied to surface of the specimen likely to be subjected to thermal stresses in normal use. A layer of white pine board and wrapping tissue was placed beneath the sample at 200mm ± 5mm distance.

SPECIMEN NUMBER	5	6	7	8
SPECIMEN DESCRIPTION				
Material				
Colour				
Test specimen				
Glow wire tip temperature (°C)				
Duration of glow wire application (t _a) (s)	30	30	30	30
OBSERVATIONS				
Duration from beginning of glow-wire tip application to ignition of specimen or layer (t _i) (s)				
Duration from beginning of glow-wire tip application to when flames extinguish (t _e) (s)				

Attachment No. 2



AS/NZS 3112:2017 Appendix J

Clause	Requirement + Test	Result - Remark	Verdict
	Maximum height of flames after initial 1s (to nearest 5 mm) (mm)		
	Flame impingement on other parts		
	Degree of tip penetration		
	Degree of specimen distortion		
	Scorching of pinewood board		
	EVALUATION CRITERIA		
	Visible flame or sustained glowing		
	Visible Flame Duration in Seconds during test.		
	Duration of flaming or glowing after tip removal (max. allowable 30 s) (s)		
	Surrounding parts burned away completely (not permitted)		
	Ignition of wrapping tissue layer (not permitted)		
	RESULTS If parts tested withstand the glow-wire test, but during the test produce a flame that persists for longer than 2 s, then the consequential needle flame test of AS/NZS 3100:2017 Annex A 6.1.5 applies		

LEGEND: CE Complete Equipment SA Sub Assembly SE Self Extinguished
EBD Emitted Burning Droplets SBD Specimen Burned and Distorted SMD Specimen Melted and Distorted
ME Manually Extinguished SC Separate Component SS Specimen Scorched
NA Not Applicable SCC Specimen Completely Consumed WPNI Wall Penetrated but no Ignition
NI No Ignition X Flame Appeared for an Inst

TABLE: Needle- flame test (NFT)					N/A
Object/ Part No./ Material	Manufacturer/ trademark	Duration of application of test flame (ta); (s)	Ignition of specified layer Yes/No	Duration of burning (tb) (s)	Verdict

Supplementary information:

- NFT not relevant (or applicable) for Parts of material classified as V-0 or V-1
- NFT not relevant (or applicable) for Base material of PCBs classified as V-0 or if relevant VTM-0

Attachment No. 2



IEC 62368_1E ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
ATTACHMENT TO TEST REPORT IEC 62368-1 U.S.A. AND CANADA NATIONAL DIFFERENCES (Audio/video, information and communication technology equipment – Part 1: Safety requirements)			
Differences according to : CSA/UL 62368-1:2019			
TRF template used: : IECEE OD-2020-F3, Ed. 1.1			
Attachment Form No. : US_CA_ND_IEC62368_1E			
Attachment Originator : UL(US)			
Master Attachment : Dated 2022-03-04			
Copyright © 2022 IEC System for Conformity Testing and Certification of Electrical Equipment (IECEE), Geneva, Switzerland. All rights reserved.			
IEC 62368-1 - US and Canadian National Differences Special National Conditions based on Regulations and Other National Differences			
1 (1DV.1) (1.3)	All equipment is to be designed to allow installation in accordance with the National Electrical Code (NEC), ANSI/NFPA 70, the Canadian Electrical Code (CEC), Part 1, CAN/CSA C22.1, and when applicable, the National Electrical Safety Code, IEEE C2. Also, for such equipment marked or otherwise identified, installation is allowed per the Standard for the Protection of Information Technology Equipment, ANSI/NFPA 75.		P
1 (1DV.2.1)	This standard includes additional requirements for equipment used for entertainment purposes intended for installation in general patient care areas of health care facilities. See Annex DVB.		N/A
1 (1DV.2.2)	This standard includes additional requirements for equipment intended for mounting under cabinets. See Annex DVC.		N/A
1 (1DV.2.3)	IEC 62368-3 clause 5 for DC power transfer at ES1 or ES2 voltage levels is considered informative. IEC 62368-3 clause 6 for remote power feeding telecommunication (RFT) circuits is considered normative (see ITU K.50). Alternatively, equipment with RFT circuits are given in either UL 2391 or CSA/UL 60950-21. RFT-C circuits are not permitted unless the RFT-C circuit complies with RFT-V limits ($\leq 200V$ per conductor to earth).		N/A
1 (1DV.3)	For protection against direct lightning strikes, reference is made to NFPA 780 and CAN/CSA-B72 for additional requirements.		N/A

Attachment No. 2



IEC 62368_1E ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
1 (DV.5)	Additional requirements apply to some forms of power distribution equipment, including sub-assemblies.		N/A
4.1 (4.1.17)	For lengths exceeding 3.05 m, external interconnecting cable assemblies are required to be a suitable cable type (e.g., DP, CL2) specified in the NEC.		N/A
	For lengths 3.05 m or less, external interconnecting cable assemblies that are not types specified in the NEC generally are required to have special construction features and identification markings.		N/A
4.6 (4.6.2)	Wire-wrap terminals have special construction and performance requirements.		N/A
4.8 (4.8.3, 4.8.4.5, 4.8.5)	Coin / button cell batteries have modified special construction and performance requirements.		N/A
5.4.2.3.2 (5.4.2.3.2.1)	Surge Arrestors and Transient Voltage Surge Suppressors installed external to the equipment are required to comply with the appropriate NEC and CEC requirements.		N/A
5.5.9	Receptacles, rated 125-V, single phase, 15- or 20-A accessible to either ordinary, instructed, or skilled persons are required to be provided with GFCI Protection for Personnel if the equipment containing the receptacles is installed outdoors. The protection devices are required to comply with UL 943, and CAN/CSA C22.2 No.144.		N/A
5.6.3	Protective earthing conductors comply with the minimum conductor sizes in Table G.7, except as required by Table G.7ADV.1 for cord connected equipment, or Annex DVH for permanently connected equipment.		N/A
5.7.8 (5.7.8.1)	Equipment intended to receive telecommunication ringing signals is required to comply with a special touch current measurement tests.		N/A
6.5.1	PS3 wiring outside a fire enclosure is required to comply with single fault testing in B.4, or be current limited per one of the permitted methods.		N/A
Annex F (F.3.3.9)	Output terminals provided for supply of other equipment, except mains supply, are required to be marked with a maximum rating or reference to equipment permitted to be connected.		P
Annex F (F.3.7)	Outdoor Enclosures are required to be classified and marked in accordance with UL 50 or 50E, or CAN/CSA C22.2 No. 94.1 or 94.2.		N/A
Annex G (G.7)	Permanent connection of equipment to the mains supply by a power supply cord is not permitted, except for certain equipment, such as ATMs.		N/A

Attachment No. 2



IEC 62368_1E ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
	Power supply cords are required to have attachment plugs rated not less than 125 percent of the rated current of the equipment.		N/A
	Flexible power supply cords are required to be compatible with Article 400 of the NEC, and Tables 11 and 12 of the CEC.		N/A
	Minimum cord length is required to be 1.5 m, with certain constructions such as external power supplies allowed to consider both input and output cord lengths into the requirement. Power supply cords are required to be no longer than 4.5 m in length if used in ITE Rooms.		N/A
	Power supply cords for outdoor equipment are required to be suitable outdoor use type as required by Section 400.4 of the NEC and Rule 4-012 of the CEC, i.e., marked "W."		N/A
Annex H.2	Continuous ringing signals under normal operating conditions up to 16 mA only are permitted if the equipment is subjected to special installation and performance restrictions.		N/A
Annex H.4	For circuits with other than ringing signals and with voltages exceeding 42.4 V _{peak} or 60 V _{d.c.} , the maximum acceptable current through a 2000 ohm resistor (or greater) connected across the voltage source with other loads disconnected is 7.1 mA peak or 30 mA d.c. under normal operating conditions.		N/A
Annex Q (Q.3)	Equipment with paired conductor and/or coax communications cables/wiring connected to building wiring are required to have special voltage, current, power and marking requirements.		N/A
Annex DVA (1)	Equipment that is designed such that it may be powered from a separate electrical service, is required to meet applicable requirements for service equipment for control and protection of services and their installation and complies with Article 230 of the National Electrical Code (NEC), NFPA 70 and Section 6 of the Canadian Electrical Code, Part I, CSA C22.1.		N/A
	Equipment intended for use in spaces used for environmental air (plenums) are subjected to special flammability requirements for heat and visible smoke release.		N/A
	For ITE room applications, automated information storage systems with combustible media greater than 0.76 m ³ (27 cu ft) are required to have a provision for connection of either automatic sprinklers or a gaseous agent extinguishing system with an extended discharge.		N/A
	Consumer products designed or intended primarily for children 12 years of age or younger are subject to additional requirements in accordance with U.S. and Canadian Regulations.		N/A

Attachment No. 2



IEC 62368_1E ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
	Baby monitors are required to additionally comply with ASTM F2951, Consumer Safety Specification for Baby Monitors.		N/A
	Storage batteries and battery management equipment, other than associated with lead-acid batteries, and including battery backup systems that are not an integral part of stationary AV and ICT equipment, such as provided in separate cabinets, are required to be certified (listed) to the appropriate standard(s) for such storage batteries and equipment.		N/A
Annex DVA (5.6)	For Pluggable Equipment Type A, the protection in the installation is assumed to be 20A.		P
Annex DVA (6.3)	The maximum quantity of flammable liquid stored in equipment is required to comply with NFPA 30.		N/A
Annex DVA (6.4.8)	For ITE room applications, enclosures with combustible material measuring greater than 0.9 m ² (10 sq ft) or a single dimension greater than 1.8 m (6 ft) are required to have a flame spread rating of 50 or less. For equipment with the same dimensions for other applications, an external surface that is not a fire enclosure requires a minimum flammability classification of V-1.		N/A
Annex DVA (10.3)	Equipment with lasers is required to meet the U.S. Code of Federal Regulations 21 CFR 1040 (and the Canadian Radiation Emitting Devices Act, REDR C1370).		P
Annex DVA (10.5)	Equipment that produces ionizing radiation is required to comply with the U.S. Code of Federal Regulations, 21 CFR 1020 (and the Canadian Radiation Emitting Devices Act, REDR C1370).		N/A
Annex DVA (F.3.3.4)	Equipment for use on a.c. mains supply systems with a neutral and more than one phase conductor (e.g. 120/240 V, 3-wire) require a special marking format for electrical ratings. Additional considerations apply for voltage ratings that exceed the attachment cap rating or that are lower than the "Normal Operating Condition" in Table 2 of CAN/CSA C22.2 No. 235."		N/A
Annex DVA (F.3.3.6)	Equipment identified for ITE (computer) room installation is required to be marked with the rated current.		N/A

Attachment No. 2



IEC 62368_1E ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
Annex DVA (G.1)	Vertically-mounted disconnect switches and circuit breakers are required to have the "on" position indicated by the handle in the up position, where mounted in an enclosure, vertically mounted disconnect switches and circuit breakers with vertical operating means extending outside the enclosure are required to indicate in a location visible when accessing the external operating means whether the switch or circuit breaker is in the open (off) or closed (on) position.		N/A
Annex DVA (G.3.4)	Suitable NEC/CEC branch circuit protection rated at the maximum circuit rating is required for all standard supply outlets and receptacles (such as supplied in power distribution units) if the supply branch circuit protection is not suitable.		N/A
	Where a fuse is used to provide Class 2 or Class 3 current limiting, it is not operator-accessible unless it is non- interchangeable.		N/A
Annex DVA (G.4.2)	Equipment with isolated ground (earthing) receptacles is required to comply with NEC 250.146(D) and CEC 10-400 and 10-612.		N/A
Annex DVA (G.4.3)	Interconnection of units by conductors supplied by a limited power source, or a Class 2 circuit defined in the NEC/CEC may have field wiring connections other than specified in DVH.3, such as wire-wrap and crimp-on types, if the limited power source and Class 2 circuits are separated from all other circuits by barriers, routing or fixing.		N/A
Annex DVA (G.5.3)	Power distribution transformers distributing power at 100 volts or more, and rated 10 kVA or more, require special transformer overcurrent protection.		N/A
Annex DVA (G.5.4)	Motor control devices are required for cord-connected equipment with a mains-connected motor if the equipment is rated more than 12 A, or if the equipment has a nominal voltage rating greater than 120 V, or if the motor is rated more than 1/3 hp (locked rotor current over 43 A).		N/A
Annex DVA (G.7)	Flexible cords used outdoors are required to have the suffix "W" marked on the flexible cord.		N/A
Annex DVA (M)	For ITE room applications, equipment with battery systems capable of supplying 750 VA for five minutes are required to have a battery disconnect means that may be connected to the ITE room remote power-off circuit.		N/A

Attachment No. 2



IEC 62368_1E ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
Annex DVA (Q)	If applicable per NEC 725.121(C), some limited power sources supplied from AV/ICT equipment are required to have a label indicating the maximum voltage and rated current output for per conductor for each connection point. Where multiple connection points have the same rating, a single label is permitted to be used.		N/A
	Wiring terminals intended to supply Class 2 outputs in accordance with the NEC or CEC Part 1 are required to be marked with the voltage rating and "Class 2" or equivalent. The marking is located adjacent to the terminals and visible during wiring.		N/A
	Applicable parts of Chapter 8 of the NEC, and Rules 54 and 60 of the CEC, may be applicable to ITE installed outdoors with connections to communication systems.		N/A
Annex DVB (1)	Additional requirements apply for equipment used for entertainment purposes intended for installation in general patient care areas of health care facilities.		N/A
Annex DVC (1)	Additional requirements apply for equipment intended for mounting under kitchen cabinets.		N/A
Annex DVE (4.1.1)	Some equipment, components, sub-assemblies and materials associated with the risk of fire, electric shock, or personal injury are required to have component or material ratings in accordance with the applicable national (U.S. and Canadian) component or material requirements. These equipment and components include: appliance couplers, attachment plugs, battery backup systems, circuit breakers, communication circuit accessories, connectors (used for current interruption of non-LPS circuits), direct plug-in equipment, electrochemical capacitor modules (energy storage modules with ultracapacitors), enclosures (outdoor), flexible cords and cables, fuses (branch circuit), ground-fault current interrupters, interconnecting cables, modular data centres, power supply cords, some power distribution equipment, printed wiring, protectors for communications circuits, receptacles, surge protective devices, vehicle battery adapters, wire connectors, and wire and cables.		P
Annex DVH	Equipment for permanent connection to the mains supply is subjected to additional requirements.		N/A
Annex DVH (DVH.1)	Wiring methods (terminals, leads, etc.) used for the connection of the equipment to the mains are required to be in accordance with the NEC/CEC.		N/A

Attachment No. 2



IEC 62368_1E ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
Annex DVH (DVH.2.1)	For safe and reliable connection to a mains, permanently connected equipment is to be provided.		N/A
Annex DVH (DVH.2.2)	Additional considerations for D.C. mains.		N/A
Annex DVH (DVH.3.2.1)	Terminals for permanent wiring, including protective earthing terminals, are required to be suitable for U.S./Canadian wire gauge sizes, rated 125 percent of the equipment rating, and be specially marked when specified.		N/A
Annex DVH (DVH.3.2.3)	Wire binding screws are not permitted to attach conductors larger than 10 AWG (5.3 mm ²).		N/A
Annex DVH (DVH.3.2.4)	All associated mains supply terminals are located in proximity to each other and to the main protective earthing terminal, if any.		N/A
Annex DVH (DVH.3.2.5)	Terminals are located, guarded or insulated so that, should a strand of a conductor escape when the conductor is fitted, there is no likelihood of accidental contact between such a strand and accessible conductive parts or unearthed conductive parts separated from accessible conductive parts by supplementary insulation only.		N/A
Annex DVH (DVH.3.3)	When field connection to an external circuit is via wires (example, free conductors), the wires are not smaller than 18 AWG (0.82 mm ²) and the free length of the wire inside an outlet box or wiring compartment is 150 mm or more.		N/A
Annex DVH (DVH.3.4)	Size of protective earthing conductors and terminals	(See sub-clause 5.6.5)	N/A
Annex DVH (DVH.4)	Permanently connected equipment is required to have a suitable wiring compartment and wire bending space.		N/A
Annex DVH (DVH.4.1)	Wire bending space		N/A
Annex DVH (DVH.4.2)	Volume of wiring compartment		N/A
Annex DVH (DVH.4.3)	Separation of circuits		N/A
Annex DVH (DVH.5)	Equipment markings and instructional safeguards		N/A
Annex DVH (DVH.5.1)	Identification of protective earthing terminal		N/A
Annex DVH (DVH.5.2)	Identification of terminal for earthed conductor (neutral)		N/A
Annex DVH (DVH.5.3)	Identification of terminals for aluminum conductors		N/A
Annex DVH (DVH.5.4)	Wire temperature ratings		N/A

Attachment No. 2



IEC 62368_1E ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
Annex DVH (DVH 5.5)	Equipment connected to a centralized d.c. power system, and having one pole of the DC mains input terminal connected to the main protective earthing terminal in the equipment, is required to comply with special earthing, wiring, marking and installation instruction requirements.		N/A
Annex DVI (6.7)	Equipment intended for connection to telecommunication network outside plant cable is required to be protected against overvoltage from power line crosses.		N/A
Annex DVJ (10.6.1)	Equipment connected to a telecommunication and cable distribution networks and supplied with an earphone intended to be held against, or in the ear is required to comply with special acoustic pressure requirements.		N/A

Attachment No. 2



IEC 62368_1E ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
ATTACHMENT TO TEST REPORT IEC 62368-1 CHINA NATIONAL DIFFERENCES (Audio/video, information and communication technology equipment -Part 1: Safety requirements)			
Differences according to : GB 4943.1-2022			
TRF template used: : IECEE OD-2020-F3, Ed. 1.1			
Attachment Form No. : CN_ND_IEC62368_1E			
Attachment Originator : CQC			
Master Attachment : Dated 2022-12-01			
Copyright © 2020 IEC System for Conformity Testing and Certification of Electrical Equipment (IECEE), Geneva, Switzerland. All rights reserved.			
	National Differences		P
4.1.2	Use of components Add a paragraph: A component used shall comply with related requirements corresponding altitude of the equipment.	Should be evaluated during the national approval.	N/A
4.11	Add clause 4.11, as follows: Protection in PRIMARY CIRCUITS against overcurrent short-circuits and earth faults shall be provided as an integral part of the equipment except the device shall meet the all requirement of Fault conditions. If pluggable equipment type B or permanently connected equipment depends on protective devices outside the equipment for protection, this shall be stated in the installation instructions of the equipment, with requirements for short-circuit protection, over-current protection, or both if necessary.		P
5.3.2.2	Contact requirements Amend the 2 nd paragraph of table 8 to be: For equipment intended to be used at altitude of 2000m to 5000m, the values in this table are multiplied by the multiplication factor corresponding altitude of 5000m.	At altitude of 5000m	P

Attachment No. 2



IEC 62368_1E ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
5.4.2.5	Multiplication factors for altitudes higher than 2 000 m above sea level Amend the 1st paragraph to be: For equipment to be operated at more than 2000 m above sea level and up to 5000m above sea level, the minimum CLEARANCE in tables 10,11 and 14, and resistance test voltages required in table 15, shall meet the requirements of 5000 m above sea level, this is multiplied by the multiplication factor corresponding altitude of 5000m in table 16. For equipment to be used at equal or less than 2000 m above sea level, the minimum CLEARANCE in tables 10, 11 and 14, and resistance test voltages required in table 15, shall meet the requirements of 2000 m above sea level. This is multiplied by the multiplication factor corresponding altitude of 2000m in table 16. Delete note 2 of Clause 5.4.2.5.		P
5.4.5.1	General Delete the 2nd paragraph of Clause 5.4.5.1: This test does not apply to equipment where one antenna terminal on the equipment is connected to earth in accordance with 5.6.7. Add the following: The Insulation resistance between CATV antenna coaxial sockets and protective earth of apparatus shall comply with BASIC INSULATION. If it's possible that CLASS II apparatus with CATV antenna coaxial sockets connect with protective earth of another CLASS I apparatus by other terminals, the insulation resistance between them shall comply with BASIC INSULATION as well. If antenna cable separated from the protective earth before connection to the apparatus, there is no requirements of Insulation resistance between them but F.4 requirements shall be meet. Delete "NOTE" of Clause 5.4.5.1		N/A
5.4.8	Humidity conditioning Amend clause 5.4.8 as follows: The humidity conditioning is conducted for 120 h in a cabinet or room containing air with ambient temperature $(40\pm 2)^\circ\text{C}$ and a relative humidity of $(93\pm 3)\%$. During this conditioning, the component or subassembly is not energized. For equipment not to be operated at tropical climatic conditions, humidity conditioning is conducted for 48 h in a cabinet or room containing air with a relative humidity of $(93\pm 3)\%$. The temperature of the air, at all places where samples can be located, is maintained within 2°C of any convenient value between 20°C and 30°C such that condensation does not occur.		P

Attachment No. 2



IEC 62368_1E ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
	Add note: For equipment to be operated at 2000 m - 5000m above sea level, assessment and requirement of humidity conditioning for Insulation material properties are considered. Pre-processing conditions and requirements below 2000m can be used until additional data is available.		
6.4.9 Y.4.3	Delete references to ASTM and NEMA.		N/A
6.5.1	General requirements Delete the text of the Note "Wire complying with UL 2556 VW-1 is considered to comply with these requirements".	Should be evaluated during the national approval.	N/A
F.1	Amend the second paragraph of annex F.1 to be: Unless symbols are used or otherwise specified, safety related equipment markings, instructions, and instructional safeguards shall be in normative Chinese.	Should be evaluated during the national approval	N/A
F.2.2	After the first paragraph of annex F.2.2 ,add the following: For apparatus intended to be used at altitude not exceeding 2000m, a warning label containing the following or a similar appropriate wording or a symbol shown below shall fixed to the equipment at readily visible place. "Only used at altitude not exceeding 2000m."  For apparatus intended to be used in not-tropical climate regions, a warning label containing the following or a similar appropriate wording or a symbol shown below shall fixed to the equipment at readily visible place. "Only used in not-tropical climate regions."  If only symbol used, the explanation of the symbol shall be contained in the instruction manual. The statements above shall be given in a language acceptable to the regions where the apparatus is intended to be used.	Should be evaluated during the national approval	N/A
F.3.3.4	After the last paragraph, Added: ...for single rated voltage, "220 V" or three-phase "380V" shall be marked only. For a rating voltage range, 220 V or three-phase 380V shall be covered. For multiple rated voltages, one of them shall be 220 V or three-phase 380V and which default setting from manufacture shall be 220 V or three-phase 380V as well.		P
F.3.3.5	After the last paragraph, Added: Rated frequency shall be 50Hz or frequency range shall cover 50Hz.		P

Attachment No. 2



IEC 62368_1E ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
F.4	Instructions Added: For apparatus incorporating antenna coaxial sockets which is non-separated with CATV network, a warning wording or a similar shall be given in the instruction manual: "A CATV cable intended to be connected to apparatus shall be separated with the protective earth of the apparatus, otherwise fire hazard might be caused."		N/A
F.5	Instructional safeguards In table F.2, change 230V to 220V, change 400Y/230V 3Ø to 380 Y/220 V 3Ø		N/A
G.4.2	Amend clause G.4.2 as follows: Plugs connected to the MAINS in apparatus shall comply with GB/T 1002, GB/T 1003, GB/T 2099.1 or GB/T 11918 (All parts) series. Appliance coupler shall comply with GB/T 17465 (All parts) series or GB/T 11918 (All parts) series.	Should be evaluated during the national approval.	N/A
	Special national conditions (if any)		P
0.12	Add clause 0.12 Description of relevant information.		N/A
1	GB 4943.1-2022 applies to equipment used at altitudes not exceeding 5000m above sea level, For apparatus intended to be used at altitude not exceeding 2000m, the requirements can be appropriately reduced, but warning instructions shall be provided. Revise the sixth paragraph of 1 as: In addition to specified by the manufacturer, this document assumes a maximum altitude of 5000m		N/A
B.2.6.1	Amend T_{ma} as follows: T_{ma} is the maximum ambient temperature permitted by the manufacturer's specification, or 35 °C, whichever is greater. Add note 1: For equipment not to be operated at tropical climatic conditions, T_{ma} is the maximum ambient temperature permitted by the manufacturer's specification, or 25 °C, whichever is greater. Add note 2: For equipment to be operated at 2000m-5000m above sea level, its temperature test conditions and temperature limits are under consideration. temperature test conditions and temperature limits below 2000m can be used until additional data is available.		P

Attachment No. 2



IEC 62368_1E ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
Annex Z (normative)	Added annex Z: Instructions of the new safety warning labels.	Should be evaluated during the national approval.	N/A
Annex AA (informative)	Added annex AA: Illustration relative to safety explanation in normative Chinese, Tibetan, Mongolian, Zhuang Language and Uighur.	Should be evaluated during the national approval.	N/A

Attachment No. 2



IEC 62368_1E ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
ATTACHMENT TO TEST REPORT IEC 62368-1:2018 JAPAN NATIONAL DIFFERENCES (Audio/video, information and communication technology equipment – Part 1: Safety requirements)			
Differences according to : J62368-1 (2023)			
TRF template used: : IECCE OD-2020-F3:2022, Ed. 1.2			
Attachment Form No. : JP_ND_IEC62368_1E			
Attachment Originator : UL Solutions (JP)			
Master Attachment : Date 2023-05-12			
Copyright © 2023 IEC System for Conformity Testing and Certification of Electrical Equipment (IECEE), Geneva, Switzerland. All rights reserved.			
	National Differences		—
4.1.2	Where the component, or a characteristic of a component, is a safeguard or a part of a safeguard, components shall comply with the requirements of this document or, where specified in a requirements clause, with the safety aspects of the relevant JIS component standards or IEC component standards, or components shall have properties equivalent to or better than these.		P
5.6.1	Mains socket-outlet and interconnection coupler shall comply with Clause G.4.2A if they are incorporated as part of the equipment.		N/A
5.6.2.1	Connection for protective conductor of class 0I equipment provided with instructional safeguard in accordance with Clause F.3.6.1A is considered to make earlier and break later than supply connection. Mains plug having a lead wire for protective earthing connection of class 0I equipment shall comply with all of the following: – Not to be used for equipment having a rated voltage of 150 V or more – Clip is not used for the earthing connection of the lead wire. – The lead wire for earthing is at least 10 cm long If class 0I equipment provides an independent main protective earthing terminal and is intended to be installed by ordinary person, earthing wire shall be provided in the package of the equipment.		N/A

Attachment No. 2



IEC 62368_1E ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
5.6.2.2	Internal earthing conductor of the cord set that is covered by the sheath of mains cord and is formed together with mains plug and appliance connector need not be green-and-yellow.		N/A
5.6.3	In case of class 0I equipment using power supply cord having two conductors (no earthing conductor), the conductor of protective earthing lead wire shall comply with either of the following: – use of annealed copper wire with 1.6 mm diameter or corrosion-inhibiting metal wire having size and strength that are equivalent to or more than the above copper wire – single core cord or single core cable with 1.25 mm ² or more cross-sectional area		N/A
5.7.3	For class 0I equipment that is provided with mains socket-outlet in the configuration as specified in JIS C 8282 series, JIS C 8300 or JIS C 8303, or that is provided with mains appliance outlet as specified in JIS C 8283 series for the purpose of interconnection, the measurement is conducted on the system of the interconnected equipment having a single connection to the mains.		N/A
5.7.5	In case of class 0I equipment, touch current shall not exceed 1.41 mA peak or for sinusoidal wave, 1.0 mA r.m.s. when measured using the network specified in Figure 4 of IEC 60990:2016.		N/A
6.4.3.2	A fuse complying with JIS C 6575 series or a fuse having equivalent characteristics shall open within 1 s. A fuse having time/current characteristics other than those specified in IEC 60127 shall be tested with the characteristics taken into account. In case of Class A fuse of JIS C 6575, replace “2.1 times” by “1.35 times” and in case of Class B fuse of JIS C 6575, replace “2.1 times” by “1.6 times”.		P
8.5.4.3.1	Only three-phase stationary equipment rated more than AC 200 V can be considered as being for use in locations where children are not likely to be present, when complying with Clause F.4.		N/A
8.5.4.3.2	For equipment installed where children may be present, an instructional safeguard shall be provided by easily understandable wording in accordance with Clause F.5, except that element 3 is optional.		N/A
8.5.4.3.4	The media destruction device is tested according to Clause V.1.2 with applicable jointed test probes to the opening. And then the wedge probe per Figure V.4 shall not contact any moving part.		N/A

Attachment No. 2



IEC 62368_1E ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
8.5.4.3.5	The wedge probe of Figure V.4 and applicable jointed test probes specified in Clause V.1.2 shall not contact any moving part. Instructional safeguard shall not be used instead of equipment safeguard for preventing access to hazardous moving parts.		N/A
F.3.5.1	When the mains socket-outlet is configured in accordance with JIS C 8282 series, JIS C 8300 or JIS C 8303, the assigned current or power shall be marked. If the voltage of the socket-outlet is the same as the mains voltage, the voltage need not be marked. Instructional safeguard of Class 0I equipment shall be provided with an instructional safeguard in accordance with Clause F.5 when a mains socket-outlet as specified in JIS C 8282 series, JIS C 8300 or JIS C 8303 to which class I equipment can be connected is provided in accordance with Clause G.4.2A except for the cases where the socket-outlet is accessible only to skilled persons.		N/A
F.3.5.3	If the fuse is necessary for the safeguard function, the symbols indicating pre-arcing time-current characteristic shall be included.		P
F.3.6.1A	Marking for class 0I equipment The requirements of Clauses F.3.6.1.1 and F.3.6.1.2 shall be applied to class 0I equipment. For class 0I equipment, a marking of instructions shall be provided regarding the earthing connection. In addition to the above, for class 0I equipment, an instruction to connect earthing before and disconnect earthing after the connection of supply conductors shall be marked on the visible place of the main body or shall be in the text of an accompanying document.		N/A
F.3.6.2	Symbols, IEC 60417-5172 (2003-02) or IEC 60417-6092 (2011-10), shall not be used for class I equipment or class 0I equipment.		P
F.3.8A	Attention marking for aging deterioration of CRT television Year of manufacture, standard usage period by design according to JIS C 9921-5 and cautionary statement for possible risks of aging deterioration when used beyond the specified period shall be marked on CRT television except for industrial use CRT television.		N/A

Attachment No. 2



IEC 62368_1E ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
F.4	For audio equipment with terminals classified as ES3 in accordance with Table E.1, and for other equipment with terminals marked in accordance with F.3.6.1 and F.3.6.1A, the instructions shall require that the external wiring connected to these terminals shall be installed by a skilled person, or shall be connected by means of ready-made leads or cords that are constructed in a way that would prevent contact with any ES3 circuit. For class 0I equipment provided with independent main protective earthing terminal, where the cord for the protective earthing connection is not provided in the package of the equipment, if the protective earthing connection is made by instructed person or skilled person, the suitable installation instruction for the protective earthing connection shall be provided.		N/A
G.3.2.1	The thermal link when tested as a separate component, shall comply with the requirements of JIS C 6691 or have properties equivalent to or better than that.		N/A
G.3.4	Except for devices covered by Clause G.3.5, overcurrent protective devices used as a safeguard shall comply with the applicable JIS or IEC standard in accordance with 4.1.2 or shall have equivalent or better properties. Such a protective device shall have adequate breaking (rupturing) capacity to interrupt the maximum fault current (including short-circuit current) that can flow.		P
G.4.1	This requirement does not apply to connectors covered in Clauses G.4.2 and G.4.2A.		N/A

Attachment No. 2



IEC 62368_1E ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
G.4.2	Mains connectors, mains plugs and socket-outlets shall comply with JIS C 8283 series, JIS C 8285, IEC 60309 series, JIS C 8282 series, JIS C 8300, JIS C 8303, or have equivalent or better properties. A power supply cord set provided with appliance connector that can fit appliance inlet complying with JIS C 8283-1 shall comply with JIS C 8286. Construction shall prevent mechanical stress not to transmit to the soldering part of appliance inlet terminal. When an equipment is rated not more than 125 V and all of the following are met, Type C14 and C18 appliance inlet complying with JIS C 8283-3 can be considered as rated 15 A. – The temperature of appliance inlet does not exceed the value specified in JIS C 8283-1 under the most unfavourable normal operating condition as specified in Clause B.2.1. – "Use only designated cord set attached in this equipment" or equivalent text is described in the operating instruction. If the cord set is not provided in the package of the equipment, suitable information regarding to the cord set is described in the operating instruction.	Should be evaluated during the national approval.	N/A
G.4.2A	Mains socket-outlet and interconnection coupler provided with the class II, class I and class 0I equipment respectively		N/A
G.7.1	A mains supply cord need not include the protective earthing conductor for class 0I equipment provided with independent protective earthing conductor.	Should be evaluated during the national approval.	N/A
G.7.2 Table G.7	Cross-sectional area of equipment rated up to and including 3 A shall be 0.75 mm ² .	Should be evaluated during the national approval.	N/A
G.7.6.1 Table G.9	The cross-sectional area of mains cords according to JIS C 3010 may comply with relevant Japanese wiring regulation. For cables other than those complying with JIS C 3662 series or JIS C 3663 series, the terminals shall be suitable for the size of the intended cables.		N/A

APPENDIX	J3000 (H25) Special National conditions, National deviation and other information according to MITI Ordinance No. 85.	--
----------	---	----

Attachment No. 2



IEC 62368_1E ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
1	General requirement When equipment provides with appliance inlet complying with JIS C 8283-1 (2008), soldered parts of appliance inlet is not applied by force during insert or removal of connector. This is not applied when inlet body is fixed itself and not fixed by solder.		P
2	Requirement for equipment		N/A
2.1	Electric heater, and the matches that are connected in parallel to power regulation diode, and that there is no abnormality in a state of being opened diode 1. Compliance is checked by the following.		N/A
	- Diode 1 has a rated capacity of more than the current of the main circuit, a diode which are connected in parallel, that this is the same specifications.		N/A
	- When subjected to a temperature rise test as specified in 11 JIS C 9335-2-30 (2006) and uncoupled one of the diode connected in parallel, to conform thereto. "		N/A
	In and an electric heating device, it can be in one that is connected in parallel rectifier connected to the power supply to adjust the power consumption, and that there is no abnormality in a state where the rectifier 1 is opened. Compliance is checked by the following.		N/A
	- Rectifier 1 has a rated capacity of more than the current of the main circuit, rectifiers connected in parallel, that this is the same specifications.		N/A
	- The Addition 11. JIS C 9335-1 (2003), when subjected to temperature rise test specified in the individual requirements of the application, can be adapted to this in uncoupled one of the rectifier connected in parallel. "		N/A
2.2	Electronic heater with glowing heating elements		N/A
	Surface treatment by paint or adhesive on protective frame or protective mesh shall not be used.		N/A
	Caution marking like below shall be on -easily visible place of the equipment or -Instruction manual		N/A
3	Components used in equipment		N/A

Attachment No. 2



IEC 62368_1E ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
3.1	To be used for electric freezer Electric Cooling machines, electric washing machine, or electric refrigerator "		N/A
	To be used for electricity Freezer hood, electric fan, electric cooling machines, electric washing machine, or electric refrigerator		N/A
	Due to malfunction of the capacitor, which are housed to prevent the spread of flame or melt, the outer shell of metal or ceramic. However, the shell, there may be openings for connecting wires to the motor capacitor.		N/A
	Due to malfunction of the capacitor, which are housed to prevent nucleic acid melt or flame, the outer metal or ceramic. However, the shell, there may be openings for connecting wires to the motor capacitor.		N/A
	In this case, the expression "are housed in a ceramic shell or metal" is housed case ceramic (inner shell) metal or prevent the diffusion of the melt flame or means of the shell except the capacitor touches the test finger even if there to within 50mm of the capacitor is non-metallic section that refers to, housed along with capacitor not specified JIS C 4908 (2007) in the case of metal or ceramic thereof, and the melt or flame shall be deemed to prevent it from spreading.		N/A
	No non-metallic materials within 50 mm from capacitor surface		N/A
	Non-metallic material with 50 mm from capacitor surface comply with needle frame test of JIS 9335-1(2003), Annex E		N/A
	Non-metallic material with 50 mm from capacitor surface comply with V-1 test of JIS C 60965-11-10(2006)		N/A
3.2	Plug directly inserted to outlet used refrigerator or electric freezer. Shall comply with - Face contact with outlet shall have CTI with more than 400 according to JIS C 2134(2007) or - Supporting material of blades shall comply with glow wire test by temperature of 750°C according to JIS C 60695-2-11(2004) or JIS C 60695-2-12(2004). Materials having glow wire frame temperature of 775°C are acceptable.		N/A

Attachment No. 2



IEC 62368_1E ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
ATTACHMENT TO TEST REPORT IEC 62368-1:2018 Republic of Korea NATIONAL DIFFERENCES Audio/video, information and communication technology equipment - Part 1: Safety requirements			
Differences according to : KC 62368-1(2021-08)			
TRF template used: : IECEE OD-2020-F3, Ed. 1.2			
Attachment Form No. : KR_ND_IEC62368_1E			
Attachment Originator : KTL			
Master Attachment : 2024-09-02			
Copyright © 2024 IEC System for Conformity Testing and Certification of Electrical Equipment (IECEE), Geneva, Switzerland. All rights reserved.			
	National Differences		--
4.1.1	As of January 1, 2023, internal and external components and subassemblies that comply with IEC 60950-1 or IEC 60065 are not acceptable if those components and subassemblies mandates KC certification.		N/A
G.4.2	Plugs for the connection of the apparatus to the supply main shall comply with the Korean requirement (KS C 8305 or KC 60884-1 or KC 60799).	Should be evaluated during the national approval.	N/A
	Special national conditions (if any)		-
Voltage	The marking of rated voltage or rated voltage range, for appliances intended to be connected to the supply mains, shall include 110 V, 220 V or 380 V.	100V-240VAC	P
Frequency	Only appliances having supply frequency of 60 Hz or a frequency range including 60 Hz are accepted.	50Hz/60Hz	P
Instruction	Instruction manuals and appliance marking related safety, including nameplate shall be in Korean.	Should be evaluated during the national approval	N/A

Attachment No. 2



IEC 62368_1E ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
ATTACHMENT TO TEST REPORT IEC 62368-1:2018 SAUDI ARABIA NATIONAL DIFFERENCES (Audio/video, information and communication technology equipment Part 1: Safety requirements)			
Differences according to : National standard SASO-IEC 62368-1:2020			
TRF template used: : IECEE OD-2020-F3, Ed. 1.1			
Attachment Form No. : SA_ND_IEC62368_1E			
Attachment Originator : SASO			
Master Attachment : 2022-12-22			
Copyright © 2022 IEC System for Conformity Testing and Certification of Electrical Equipment (IECEE), Geneva, Switzerland. All rights reserved.			
	National Differences		P
	Plugs used for pluggable equipment comply with standard SASO-2203.	Should be evaluated during the national approval	N/A
--	Frequency (Hz)		P
	60 Hz	50Hz/60Hz	P
--	Rated voltage (V)		P
	Single phase 230 V Three phase 400 V	100V-240VAC	P

Attachment No. 2



IEC 62368_1E ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
ATTACHMENT TO TEST REPORT IEC 62368-1 SINGAPORE NATIONAL DIFFERENCES Audio/video, information and communication technology equipment - Part 1: Safety requirements			
Differences according to : Special National Conditions			
TRF template used: : IECEE OD-2020-F3, Ed. 1.1			
Attachment Form No. : SG_ND_IEC62368_1E			
Attachment Originator : Intertek Testing Services (Singapore) Pte Ltd			
Master Attachment : 2022-07-08			
Copyright © 2022 IEC System for Conformity Testing and Certification of Electrical Equipment (IECEE), Geneva, Switzerland. All rights reserved.			
	National Differences		--
	Not Applicable		--
Chapter 4.2	Special national conditions (if any) Controlled goods under the Consumer Protection (Safety Requirements) Registration Scheme (CPS) are required to be tested to additional requirements stipulated by the Consumer Product Safety Office (CPSO) of Enterprise Singapore in Chapter 7 of the CPS information booklet. The CPS information booklet is updated on an ongoing basis. At the point of testing, refer to the latest copy of the CPS information booklet for the minimum edition of standard to apply for testing of products under the CPS scheme and any new requirements. Link to CPS information booklet: https://www.consumerproductsafety.gov.sg/files/cps-info-booklet.pdf		N/A
<u>Clause</u> 1	All appliances must be tested to 230 VAC, 50 Hz.	All tests were conducted under the worst condition based on 100VAC and 240VAC	P
4	Appliance fitted with voltage selector shall be tested as follows: Connect appliance to 230 VAC mains with voltage selector switch to settings not suitable for operation at 230 VAC.		N/A
5	All appliances (with tropical test requirements in applicable Standards) shall comply with the tropical condition test as stated in the relevant IEC Standards.		P

Attachment No. 2



IEC 62368_1E ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
7	All Class I appliances must be fitted with 3-pin mains plugs that are registered with the CPSO.	Should be evaluated during the national approval.	N/A
8	a) All Class II appliances must be fitted with 2-pin mains plug complying with EN 50075. b) Class II appliances that are fitted with 3-pin mains plugs must use plugs that are registered with the CPSO.		N/A
9	Detachable power cord set must be listed in the test report critical component list.	Should be evaluated during the national approval.	N/A
14	AC Adaptor incorporated with 13A socket-outlet to be tested to additional tests clauses 13, 17 and 18 of SS 145 Part 3: 2020.		N/A
15	Supplier who is supplying AC adaptors with detachable interchangeable plug pins must include with its products, written instructions to inform customer on the type of detachable interchangeable plug pins that are approved and suitable to use in Singapore. These instructions are to be submitted to the Conformity Assessment Body for verification when applying for Certificate of Conformity.		N/A
16	For AC Adaptors supplied together with Personal Mobility Devices: 1. Registered Supplier to declare the model of the AC adaptor that is to be used with/ bundled together with the PMDs; 2. Registered Supplier to provide valid IEC 60950-1 or IEC 62368-1 test reports for certification and registration of the declared AC adaptor under the CPS scheme; and 3. Registered Supplier to provide the UL 2272 test report as supporting document, showing that the listed AC adaptor in the UL 2272 test report is the model declared to be used with/ bundled together with the PMDs.		N/A
18	CD/ DVD ROMs (used in personal computers) to have test certificate showing that CD/DVD ROM drive has complied with IEC 60825- 1.		N/A
19	Modem card incorporated in the personal computer must be tested at set level (sub-clauses 5.1 & 6 of IEC 60950) or at component level.		N/A
20	Powerline Ethernet Adaptor incorporated with 13A socket-outlet, to be tested to additional test clauses 13, 17 & 18 of SS 145 Part 3: 2020.		N/A
	Other additional requirements which may be included in Chapter 7 of the information booklet in ongoing basis at the time of testing.		N/A

Attachment No. 3

Details of: External view 1 for models XR06B and XR03B



Details of: External view 2 for models XR06B and XR03B




Attachment No. 3

Details of: External view 3 for models XR06B and XR03B




Details of: External view 4 for models XR06B and XR03B



Attachment No. 3

Details of: External view 5 for models XR06B and XR03B



Remark: The above marking plate is only a draft, refer final marking plate in page 4 of test report for details.

Details of: External view 6 for models XR06B and XR03B




Attachment No. 3

Details of: Internal view 1 for model XR06B



Details of: Internal view 2 for model XR06B



Attachment No. 3

Details of: Internal view 3 for model XR06B



Details of: Internal view 4 for model XR06B




Attachment No. 3

Details of: Internal view 5 for model XR06B



Details of: Internal view 6 for model XR06B




Attachment No. 3

Details of: Internal view 7 for model XR06B




Details of: Internal view 8 for model XR06B




Attachment No. 3

Details of: Internal view 9 for model XR06B




Details of: Internal view 10 for models XR06B and XR03B



Attachment No. 3

Details of: Internal view 11 for models XR06B and XR03B



Details of: Internal view 12 for models XR06B and XR03B




Attachment No. 3

Details of: Internal view 13 for models XR06B and XR03B




Details of: Internal view 14 (PCB view) for models XR06B and XR03B




Attachment No. 3

Details of: Internal view 15 (Protective earthing) for models XR06B and XR03B



Details of: Internal view 16 for model XR03B




Attachment No. 3

Details of: Internal view 17 for model XR03B




Details of: Internal view 18 for model XR03B



Attachment No. 3

Details of: Internal view 19 for model XR03B



Details of: Internal view 20 for model XR03B




Attachment No. 3

Details of: Internal view 21 for model XR03B



Details of: PCB view 1 for model XR03B




Attachment No. 3

Details of: PCB view 2 for model XR03B




Details of: PCB view 3 for model XR06B



Attachment No. 3

Details of: PCB view 4 for model XR06B




Details of: Remote controller view 1 for models XR06B and XR03B



Attachment No. 3

Details of: Remote controller view 2 for models XR06B and XR03B



--- End ---